MIL-J-25718B (USAF)
AMENDMENT 4
14 SEP 87
SUPERSEDING
AMENDMENT 3
12 FEBRUARY 1987

MILITARY SPECIFICATION

JUG, INSULATED, TYPE CNU-2/C

This amendment forms a part of Military Specification MIL-J-25718B (USAF) dated 14 November 1969 and is approved for use by the Department of the Air Force and is available for use by all departments and agencies of the Department of Defense.

PAGE 1

2.1:

Federal Specifications:

Delete: "PPP-B-636 Box, Fiberboard"
Add: "PPP-B-636 Boxes, Shipping, Fiberboard"

Military Specifications:

Delete: "MIL-W-5088 Wiring, Aircraft, Installation of"
Add: "MIL-W-5088 Wiring, Aerospace Vehicle"

Federal Standards:

Add: FED-STD-H28 Screw Thread Standards for Federal Services"

Military Standards:

Delete: MIL-STD-129 Marking for Shipment and Storage"
Delete: MIL-STD-130 Identification Marking of U.S. Military Property"

PAGE 2

2.1:

Military Standards:

Delete: "MIL-STD-147 Palletized and Containerized Unit Loads, 40 Inch X 48 Inch Pallets, Skids, Runners, or Pallet Type Base."
Add: "MIL-STD-147 Palletized Units Loads"

FSC 7330

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:09Z
Check the source to verify that this is the current version before use.

Delete: "MIL-STD-461 Electromagnetic Interference Characteristics Requirements for Equipment"
Add: "MIL-STD-461 Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference"

Delete: "MS33586 Metals, Definition of Dissimilar"
Add: "MIL-STD-889 Dissimilar Metals"

2.2 Other Publications. Delete this paragraph in its entirety.

PAGE 3

3.2.4 Material. Delete this paragraph in its entirety and replace with the following:

3.2.4 Reclaimed materials. Recycled and recovered raw materials should be used to the maximum extent possible in lieu of virgin raw materials as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which would affect the performance or maintainability of individual components of the overall assembly.

3.3.2 Dissimilar metals. In the second sentence delete "MS33586" and replace with "MIL-STD-889."

PAGE 4

*3.4.1 Container body. Delete:

Insert following sentence after first sentence: "The corrosion resistant steel shall be passivated per QQ-P-35."

Change: A spigot tube shall connect with the inner case, shall extend through the outer case, shall be straight and smooth, and have provisions for attaching the spigot to a spigot tube and shall connect with the inner case, shall extend through the outer case, and shall be straight and smooth."

Add: Spigot tube shall be either 3/8 inch size with 3/8 inch straight pipe male RH threads extending out from container body .750+.015 inch or 1 1/2 inch size with 1 1/2 X 20, class 2, RH female threads extending out from container body a distance of .312+.015 inch.

3.4.3 Spigot. Change first sentence to read: The spigot shall have either 3/8 inch straight pipe RH female threads or 1 1/2 X 20, class 2, RH female threads."

Add the following as last sentence: "The configuration of the spigot shown in Figure 1 is only for reference and is not restrictive."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:09Z
Check the source to verify that this is the current version before use.

3.4.5 Handle. On lines three and seven delete "or 304" and insert "304, 304L or 305."

PAGE 7

3.6 Identification. In the first sentence delete "In accordance with MIL-STD-130."

PAGE 12

4.5.5 Leakage test (see 3.5.5) Delete paragraph 4.5.5 and insert the following paragraph:

4.5.5 Leakage test (see 3.5.5) The assembled jug shall be weighed and it's weight recorded. With its cover propped in a partially open attitude, the jug assembly shall be submerged in not less than ten (10) feet of water for not less than five (5) minutes. After the jug assembly has been removed from the water and interior and exterior surfaces dried off, its weight will again be checked. Any increase in weight will indicate leakage between inner and outer shells and shall be cause for rejection.

PAGE 13

5.3 Markings. In the first sentence delete "in accordance with MIL-STD-129" and replace with "as specified."

"The margins of the amendment are marked with an asterick or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

CUSTODIAN
Air Force - 99

PREPARING ACTIVITY
Air Force - 84
PROJECT NUMBER
7330-F576

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:09Z
Check the source to verify that this is the current version before use.