MIL-P-25716C(USAF)
AMENDMENT 3
5 December 1967
SUPERSEDING
AMENDMENT 2
9 April 1964

MILITARY SPECIFICATION

PARACHUTE SYSTEM, HEAVY DUTY, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification
MIL-P-25716C(USAF) dated 23 August 1962.

Page 1, paragraph 2.1, SPECIFICATIONS: Under Military Delete "MIL-T-7807 Thread Nylon". Add the heading "Federal" and thereunder add "V-T-295 Thread, Nylon".

Page 2, paragraph 3.1: Delete and substitute:

"3.1 QUALIFICATION. - The parachute systems furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.5 and 6.2)."

Page 2, paragraph 3.3, lines 3 and 4: Delete "except as provided in 3.3.1 and 3.3.2".

Page 2, paragraphs 3.3.1 and 3.3.2: Delete.

Page 4, paragraph 3.13, line 2: Delete "MIL-T-7807" and substitute "V-T-295".

Page 5, table I: Delete and substitute:

TABLE I - THREAD SIZE AND STITCHES PER INCH

Thread or Cord	Stitches Per Inch		
		Zigzag Stitch	
	Straight Stitch 1/ Type 301	Type 304 Single Throw	Type 308 Double Throw
E	7 to 11 2/	12 to 16	8 to 12
F	7 to 11 2/	12 to 14	7 to 10
FF	6 to 9 2/	12 to 14	7 to 10
3 cord	5 to 8		4 to 6
5 cord	4 to 6		3 to 5
6 cord	4 to 6		3 to 5
8 cord	4 to 6		

1/ Where abrupt changes occur in the thickness of material in excess of 1/32 inch, the number of stitches specified in this table may vary plus or minus 2 stitches per inch for a distance not exceeding 3/4 inch.

2/ Up to 16 stitches per inch will be acceptable for length not exceeding 2 inches in any one place with a minimum distance between locations of 12 inches. If more than 16 stitches per inch occur, the section of gore will be rejected.

FSC 1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:08Z
Check the source to verify that this is the current version before use.

Page 7 paragraph 3.17.2: After the first sentence add "For canopy cloth and h zontal ribbons only, the hole shall not be within 1/2 inch of any selvage edge o constructed seam, splice, or joint." Delete the last sentence.

Page 13, paragraph 4.3.2.1: Delete and substitute:

"4.3.2.1 SAMPLING PLAN A. - Samples of parachute systems from each production contract shall be selected at random by procuring activity (see 6. accordance with table V. Selections will be made from contract scheduled d At the discretion of the procuring activity, these samples will be subjected t all of the following tests as described under 4.4 Test Methods of this specifi

a. Conformance with drawings

b. Drop tests

c. Compliance with this specification."

Page 12, paragraph 4.1: Delete and substitute:

"4.1 RESPONSIBILITY FOR INSPECTION. - Unless otherwise specified in contract or purchase order, the supplier is responsible for the performance inspection requirements as specified herein. Except as otherwise specified supplier may utilize his own facilities or any commercial laboratory accepta the Government. The Government reserves the right to perform any of the set forth in the specification where such inspections are deemed necessary t supplies and services conform to prescribed requirements."

Page 16, paragraph 6.2e.: Delete "specified in 4.3.2.1, 4.5.1, and 4.5.1.1" stitute "specified in 4.5.1 and 4.5.1.1". Delete "ASNPSP-4" and substitute "A

Page 16, paragraph 6.3: Delete the first sentence and substitute "With respec products requiring qualification, awards will be made only for products which the time set for opening of bids, qualified for inclusion in the applicable Qualif Products List whether or not such products have actually been so listed by tha In the last sentence delete "ASNPSP-4" and substitute "ASNMH-20".

Page 17: Add:

"6.6 SELECTION OF SAMPLES. - The selection of samples of parachute sy as specified in 4.3.2.1 will be made by SAAMA, Kelly AFB, Texas."

Page 17. NOTICE: Delete.

Custodian:
Air Force - 11

Preparing
Air Forc

Reviewers: 82, 85

Project No. 167

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:08Z
Check the source to verify that this is the current version before use.