MIL-S-85069/9A
30 October 1980
SUPERSEDING
MIL-S-85069/9
15 July 1978

MILITARY SPECIFICATION SHEET

SLEEVES, FASTENER, GROOVED, 100° FLUSH FULL HEAD, TENSION, 1/32 OVERSIZE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The complete requirements for procuring the sleeves described herein shall consist of this document and the latest issue of MIL-S-85069.

DESIGN INFORMATION

Sleeves covered by this specification sheet are for use in the repair of discrepant holes and in new design where the holes require protection.
The sleeves are subject to the limitations of MIL-S-85069/1.


REQUIREMENTS

MATERIAL: A286 per AMS5525 (Stainless Steel)

LUBRICATION: Cetyl Alcohol or bare (5)

PROTECTIVE TREATMENT: Passivated per QQ-P-35.

PLATING: Cadmium per QQ-P-416, Type I, class 2 exterior only (for identification). Flash plating on bore acceptable. (5)



FSC 5365

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:20Z
Check the source to verify that this is the current version before use.

DASH No.	FOR FAST. SIZE (REF)	A DIA. ±.005	D_I DIA.	D_O DIA.	G	L ±.010	H_F HEAD HEIGHT FAST. (REF)	H_S HEAD HEIGHT SLEEVE (REF)	RECOM. ③ HOLE PREP. DRILL NO.	RECOM. ③ HOLE PREP. DRILL DIA.
06	#10	.380	.1895 .1880	.2210 .2200	.125	1.00	.080	.090	2	.2210
08	1/4	.505	.2495 .2480	.2812 .2802	.188	1.00	.108	.118	9/32	.2812
10	5/16	.631	.3120 .3105	.3437 .3427	.250	1.00	.135	.145	11/32	.3437
12	3/8	.758	.3745 .3730	.4062 .4052	.312	1.00	.162	.172	13/32	.4062

NOTES:

① Dimensions are in inches.

② Sleeves supplied in standard lengths - adjust to required length when needed.

③ Recommended for metal-to-metal to clearance fit of sleeve to hole.

④ Sleeves 06-08 ungrooved last 1/4
Sleeves 10-12 ungrooved last 5/16


⑤ L after part number designates lubricated with cetyl alcohol-B = No Lubrication

P after slash number designates cadmium plated - per QQ-P-416, Type I, Class 2

N after slash number designates no finish except passivated per QQ-P-35.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:20Z
Check the source to verify that this is the current version before use.

EXAMPLE OF PART NUMBER



The sleeves covered by this specification are manufactured under United States Patent number 3835615 and 3835525. Both patents expire on 9/1/91. the Government does not have a Royalty-Free license.

Custodians:
Navy - AS
Air Force - 11
Army - AV

Review Activities:
DLA - IS
Air Force - 99
Army - AR

Preparing Activity:
Navy - AS
(Project No. 5365-0048-08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:20Z
Check the source to verify that this is the current version before use.