NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND


MIL-PRF-83536/14
27 March 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 10 AMPERES, MAGNETIC LATCH, HERMETICALLY SEALED,
ALL WELDED, AC COILS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-PRF-83536.




RAISED VERTICAL FLANGE MOUNT (RVFM) WITH SOLDER HOOKS

FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.



RAISED VERTICAL FLANGE MOUNT (RVFM) WITH SOCKET PINS

FIGURE 1. Dimensions and configurations - Continued.


Source: https://assist.dla.mil -- Downloaded: 202610-23T08:52Z
Check the source to verify that this is the current version before use.




HORIZONTAL FLANGE MOUNT (HFM) WITH SOLDER HOOKS

FIGURE 1. Dimensions and configurations - Continued.


Source: https://assist.dla.mil -- Downloaded: 202610-23T08:52Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM



MOUNTING HOLE LAYOUT (RVFM)



MOUNTING HOLE LAYOUT (HFM)

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.000	0.00	.156	3.96	.525	13.34
.001	0.03	.172	4.37	.562	14.27
.002	0.05	.200	5.08	1.025	26.04
.005	0.13	.260	6 60	1.062	26.98
.020	0.51	.270	6.86	1.125	28.58
.030	0.76	.281	7.14	1.396	35.46
.040	1.02	.300	7.62	1.406	35.71
.062	1.58	.310	7.87	1.446	36.73
.100	2.54	.485	12.32	1.718	43.64
.150	3.81	.500	12.70		

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± 010 (0 25 mm).
4. There shall be affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified.
5. Permanent magnet drive consists of a permanent magnet with its flux path switched and combined with the electro-magnet flux.
6. Applicable to horizontal flange mount only. The circuit diagram, manufacturer's PIN, and the military PIN shall be marked on the near side. The remaining portion of the nameplate data shall be marked on the far side.
7. Applicable to horizontal flange mount only. Relays shall be marked with the manufacturer's name or CAGE code and date code. Marking shall be with the bottom of the print adjacent to the near side.
8. Socket pin terminals, except the polarizing pin, shall be gold-plated in accordance with MIL-G-45204, type II, class I. The nickel underplating shall be 50 to 150 microinches thick minimum.
9. Silicone rubber gasket, AMS 3332, shore hardness 15 to 35, thickness .050 ±.005 (1.27 ±0.13 mm).
10. Indicated terminal shall be identified by contrasting beads.
11. Direction of hook openings does not affect function
12. Plane of critical motion for vibration and shock is Y-axis

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-23T08:52Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Load ratings: See table I

Low level: 10 to 50 μA at 10 to 50 mV dc or peak ac.

Intermediate current: Applicable

Mixed loads: Applicable.

TABLE I. Rated contact load and cycles (amperes per pole).

Type of load (high level)	Cycles x 10^3	28 V dc	115 V ac 1 phase 400 Hz	115 V ac 1 phase 50/60 Hz 1/	115/200 V ac 3 phase 400 Hz	115/200 V ac 3 phase 50/60 Hz 1/
Resistive	100	10	10	2 5	10	2.5
Inductive	20	8	8	N/A	8	N/A
Inductive	10	N/A	N/A	2.5	N/A	2.5
Motor	100	4	4	2	4	2
Lamp	100	2	2	1	N/A	N/A

1/ For 50/60 Hz rating, rupture and overload are not applicable and life for each load shall be 10,000 cycles.

Life: 100,000 cycles, unless otherwise specified (see table I).

Contact voltage drop or resistance·

Initial contact voltage drop: 0.100 volt maximum. Rated resistive current at 6 V dc or peak ac Relays shall not make or break this load.

Initial contact resistance· 0.010 ohm maximum. 50 mA max at 6 V dc or peak ac.

High level life (contact voltage drop).

During life· 10 percent open circuit voltage maximum

After life: 0.125 volt maximum.

Intermediate current (contact resistance)

During intermediate current: 3 ohms maximum

After intermediate current: 0.150 ohm maximum

Low level (contact resistance):

During low level: 100 ohms maximum.

After low level: 0.150 ohm maximum at 100 mA and 28 V dc.

Contact bounce: 1.0 millisecond maximum.

Contact stabilization time: 2.5 milliseconds maximum

Overload current: 40 amperes dc (60 amperes ac)

Source: https://assist.dla.mil -- Downloaded: 202610-23T08:52Z
Check the source to verify that this is the current version before use.

Rupture current: 50 amperes dc, 80 amperes ac.

Time current relay characteristics: See table II.

TABLE II. Time current relay characteristics. 1/

Successive application	Amperes	Time
1	15	1 hour
2	50	5 seconds
3	100	1.2 seconds
4	250	0.2 second
5	350	0.1 second

1/ All relays shall withstand overload and fault currents. Relays must be able to sustain five applications (make and carry only) of power concurrently on adjacent poles at each of five different current levels in the sequence listed in table II. Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz 3-phase. Cooling time between successive applications shall be 30 minutes. Tests shall be performed on both normally open and normally closed contacts. There shall be no failures or evidence of welding or sticking and relays shall pass contact voltage drop at the conclusion.

Coil data 1/: See table III.

Operate time: 15 milliseconds maximum (for 400 Hz coils) with rated coil voltage over the temperature range.

Duty rating Continuous.

Coil transient suppression: Not applicable.

Neutral screen: Applicable.

Electrical data:

Insulation resistance:

Initial 100 megohms minimum at 500 V dc.

After life or environmental tests: 50 megohms minimum at 500 V dc.

1/ CAUTION: Due to possible interaction of relay magnetic fields, the following spacing requirements, as a minimum, shall be considered in dense packaging situations:

a. Row to row assisting fields: .125 (3.18 mm).

b. Row to row opposing fields: .1875 (4.763 mm).

c. Side to side alternating fields: .0625 (1.588 mm).

d Side to side like fields: .125 (3.18 mm).

Source: https://assist.dla.mil -- Downloaded: 202610-23T08:52Z
Check the source to verify that this is the current version before use.

TABLE III Dash numbers and characteristics. 1/

Dash number 2/		Mount	Coil data						
			Coil voltage (V ac) 4/		Frequency (Hz)	Coil current (ampere)	Pickup voltage 3/		
Solder hook	Socket pin		Rated	Max			Normal	High temperature test	Continuous current test
001	---	RVFM	115	122	400	.04	90	95.4	103.5
---	002	RVFM	115	122	400	.04	90	95.4	103.5
003	---	HFM	115	122	400	.04	90	95.4	103.5

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits are not recommended for subsequent use in low level applications.
2/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number. Failure rate level (percent per 10,000 cycles): L, 3.0; M, 1.0; P, 0.1; R, 0.01. Example: 001L, 002R.
3/ Pickup voltage as shown is for test purposes only and is not to be used for design criteria.
4/ CAUTION: The use of any coil voltages less than the rated coil voltage will compromise the operation of the relay.

Dielectric withstanding voltage 2/:

Sea level	Coil to case	Coil to coil	All other points
Initial:	1000	1000	1250
After life:	1000	1000	1000
Altitude			
At 80,000 feet:	350	350	350
At 300,000 feet:	500	500	500

Maximum leakage current: 100 microamperes rms in accordance with MIL-R-83536.

Environmental characteristics:

Temperature range: -70°C to +125°C.

Maximum altitude rating: 300,000 feet.

2/ Dielectric may be improved by suitable insulation of terminals and wiring after installation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

Shock (specified pulse): Applicable, MIL-STD-202, method 213, test condition C, except peak value shall be 200 g's for 6 ±1 ms. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (sinusoidal): Applicable, MIL-STD-202, method 204, 30 g's except frequency range shall be 10 to 3,000 Hz. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (random): Applicable to qualification and group C inspection. Test in accordance with MIL-STD-202, method 214, test condition IG (0.4 g^2/Hz., 50 to 2000 Hz), 15 minutes each plane. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Acceleration: Applicable, except 15 g's.

Physical data:

Dimensions and configurations: See figure 1.

Weight: DC coils .090 pound (40.9 g's).

Terminal strength:

Solder hook terminals:

Pull force:

For .030 diameter terminals: 3 pounds ±0.3 pound

For .062 diameter terminals: 10 pounds ±1.0 pound.

Bend: Applicable.

Twist: Applicable to coil terminals Y1 and Y2 only.

Socket pin terminals:

Pull force:

For .031 diameter terminals: 3 pounds ±0.3 pound.

For .062 diameter terminals: 10 pounds ±1.0 pound.

Bend: Applicable.

Twist: Applicable to coil terminals Y1 and Y2 only.

Terminal solderability: Applicable to solder hook terminals only.

Seal: Hermetic.

Marking: Applicable.

Part or Identifying Number (PIN): M83536/14 (dash number from table III and suffix letter designating failure rate level). PIN is a new term encompassing previous terms used in specifications such as part number, type designator, and identification number.

Qualification inspection:

Qualification inspection and sample size: See table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.

TABLE IV. Qualification inspection and sample size.

Single submission	Group submission	
18 units plus 1 open unit for level L at C = 0 1/ 33 units plus 1 open unit for level M at C = 0 1/ Qualification inspection as applicable	M83536/14-002 " " M83536/14-001 M83536/14-003	18 units plus 1 open unit for level L at C = 0 1/ 33 units plus 1 open unit for level M at C = 0 1/ Qualification inspection as applicable 2 units, qualification inspection table, group II, shock, vibration, acceleration, terminal strength, and seal

1/ The number of units required for qualification testing shall be increased as required in group V, table II of MIL-R-83536, if the contractor elects to test the number of units permitting one or more failures. Prior to performance of qualification testing, the relay manufacturer shall preselect the sampling plan.

Supersession data: See table V

TABLE V. Supersession data

Superseded PIN M6106/50-	Replacement PIN M83536/14-
007	001
008	002
009	003

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-0856)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:52Z
Check the source to verify that this is the current version before use.