INCH-POUND

MS24586E
AMENDMENT 1
31 JANUARY 2000

MILITARY STANDARD

SPRING, HELICAL, EXTENSION: FOR LOADS BELOW 30 POUNDS

This amendment forms a part of MS24586E, dated 30 DECEMBER 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

SHEET 1

In graphics, delete callout “d/2 or 1/64 MAX WHICHEVER IS GREATER” and substitute with “HOOK OPENING (SEE TABLE III)”

Delete “ENDS: Machine full loop. End loops shall be parallel within 22°. Relative position of end loop openings is optinal” and substitute with “ENDS: Machine full hook. Ends hooks shall be parallel within 22°. Relative position of end hook openings is optinal”.

SHEET 7

Add new Table:

“TABLE III – DIMENSIONS FOR HOOK OPENING”

TABLE III – DIMENSIONS FOR HOOK OPENING	
d Wire Dia.	Hook Opening
.016	d/2 + .008 - .000
.018	d/2 + .007 - .000
.020	d/2 + .006 - .000
.026	d/2 + .003 - .000
.031	d/2 ± .001
.037	
.041	
.045	
.055	
.063	

Custodians:
Army - AR
Navy - OS
Air Force - 99

Preparing Activity:
DLA-IS

(Project 5360-0031)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:57Z
Check the source to verify that this is the current version before use.