**INCH-POUND**

**MS24586E**
**AMENDMENT 2**
**10 AUGUST 2001**
**SUPERSEDING**
**MS24586E**
**AMENDMENT 1**
**31 JANUARY 2000**

**MILITARY STANDARD**

# SPRING, HELICAL, EXTENSION: FOR LOADS BELOW 30 POUNDS

**This amendment forms a part of MS24586E, dated 30 DECEMBER 1991, and is approved for use by all Departments and Agencies of the Department of Defense.**



**In graphics, delete callout "d/2 or 1/64 MAX WHICHEVER IS GREATER" and substitute with "d/2 or 1/64 MAX WHICHEVER IS GREATER, MINIMUM GAP .005".**

**Delete "ENDS: Machine full loop. End loops shall be parallel within 22°. Relative position of end loop openings is optinal" and substitute with "ENDS: Machine full hook. Ends hooks shall be parallel within 22°. Relative position of end hook openings is optinal".**

**Custodians:**
**Army - AR**
**Navy - OS**
**Air Force - 99**

**Preparing Activity:**
**DLA-IS**

**(Project 5360-0032)**

**AMSC N/A** **FSC 5360**

**DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:57Z
Check the source to verify that this is the current version before use.