MILITARY SPECIFICATION

CHRONOGRAPH AUTOMATIC RELIABILITY RATER: 10552370

This amendment forms a part of Military Specification MIL-C-60690A(MU), dated 3 April 1968.

Paragraph 3.4.7.2: Delete "milliamperes" and substitute "microamperes"; delete "+1.80 ± 0.05 vdc" and substitute "+2.50 ± 0.05 vdc".

Paragraph 4.6.2.6a: Delete "1.80 ± 0.05 vdc" and substitute " +2.50 ± 0.05 vdc".

Paragraph 4.6.2.6b: Delete in its entirety and substitute:

"b. With Switch S4 in "OSC", "METER", and "OFF" positions, rotate the delay switch from 1 thru 10. A scope connected from J2-A to ground shall indicate less than 5 millivolts peak-to-peak for all noise having a pulse width greater than one (1) microsecond for each S4 position and each delay switch position. Any noise having a pulse width less than one (1) microsecond shall have an amplitude less than 20 mv peak-to-peak for each S4 position and each delay switch position."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1290-A232

FSC 1290

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.