INCH-POUND

MIL-C-70574B (AR)
AMENDMENT 1
30 October 1992

MILITARY SPECIFICTION

CIRCUIT BOARD ASSEMBLY, BUILT IN TEST 2A8 UNIT 2:
9361010

This amendment forms a part of Military Specification MIL-C-70574B (AR), dated 5 March 1992, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.5.1: Add a new first sentence as follows:

"3.5.1 Functional description. The functional block diagram shall be per figure 1. The Unit 2 BIT..."

PAGE 7

3.5.7, sixth line: Delete "TBRL" and substitute "TBRL" .

PAGE 10

3.5.10.2, Third and fourth line: Delete "...channel S1 per Table I shall cause the..." and substitute: "...channel S1 per Table I and figure 2 shall cause the..."

3.5.10.2, Fourth line: Delete "outputs with values per Table I:" and substitute "outputs as specified in Table I."

PAGE 12

Table I, under heading 'INPUT DESCRIPTION" for channel S13:
Delete: "MODULAR" and substitute "MODULATOR".

Table I, in heading "Vin (Vdc)": Delete "(Vdc)" and substitute "(in Vdc unless stated otherwise)".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:43Z
Check the source to verify that this is the current version before use.

Table I, heading "Vin (in Vdc unless otherwise stated)" Channel S5 : Delete "+0.360 TO +0.400" and substitute "+0.490 TO +0.510 Vpk".

Table I, heading "Vin. (in Vdc unless otherwise stated)" Channel S8 : Delete "+0.004 TO +0.005" and substitute **"+0.160 To +0.220** vpk" .

Table I, heading "A2U3 MUX OUTPUT" channel S1: Delete '-3.972 TO -4.168" and substitute '-3.900 TO -4.200".

Table I, heading "A2U3 MUX OUTPUT" Channel S2: Delete '+2.713 TO +2.875" and substitute "+2.600 TO +2.900".

Table I, heading "A2U3 MUX OUTPUT" channel S5: Delete "+3.568 TO +4.109" and substitute "+2.600 TO +2.900".

Table I, heading "A2U3 MUX OUTPUT" channel S8: Delete "+3.178 TO +4.290" and substitute "+2.000 TO +2.800".

Table I, heading "A1U4 A/D INPUT VOLTAGE (Vdc)" channel S1: Delete "-3.962 TO -4.168" and substitute '-3.900 TO -4.200".

Table I, heading "A1U4 A/D INPUT VOLTAGE (Vdc)" Channel S2: Delete "+2.703 TO +2.875" and substitute "+2.600 TO +2.900".

Table I, heading "A1U4 A/D INPUT VOLTAGE (Vdc)" Channel S5: Delete "+3.558 TO +4.109" and substitute "+2.600 TO +2.900".

Table I, heading "A1U4 A/D INPUT VOLTAGE (Vdc)"Channel S8: Delete "+3.168 TO +4.290" and substitute"+2.000 TO +2.800".

Table I, heading "A1U4 A/D CONVERTER OUTPUT RANGE" channel S1: Delete "00011011, 00010011" and substitute "OOO11110, 00010011".

Table I, heading "A1U4 A/D CONVERTER OUTPUT RANGE Channel S2: Delete "11000100, 11001010" and substitute "11000001, 11001100".

Table I, heading "A1U4 A/D CONVERTER OUTPUT RANGE" Channel S5: Delete "11011001, 11101010" and substitute "11000001, llOO1100".

Table I, heading "A1U4 A/D CONVERTER OUTPUT RANGE" Channel S8: Delete "11010000, **11101111" and substitute "10110010, 11001001".**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:43Z
Check the source to verify that this is the current version before use.

Table 11, Corm. Pin #A2J1-1: Delete “RADIATE OPERATE CONTROL” and substitute ‘RADAR OPERATE CONTROL”.

Table II, Corn. Pin #A2J1-4: Delete ‘MODULAR POWER SUPPLY OVLD” and substitute “MODULATOR POWER SUPPLY OVLD”.

Table II, Corm. Pin #A2J1-7: Delete ‘-29V PULSES” and substitute ‘PULSES (NOTE l)”.

Table II, Corm. Pin #A2J1-8: Delete "+2(W PULSES” and substitute "+20V PULSES (Note 2)”.

Table II, Corn. Pin #A2J1-13: Delete “+.04v” and substitute “+0.04vdc”.

Table 11, Corn. Pin #A2J2: Delete ’60 MHz PULSES” and substitute “60 MHz SINEWAVE”.

Table II, Corm. Pin #A2J3: Delete ’16 MHz PULSES” and substitute ‘COSINE SQUARED-BURSTS (Note 3)”.

Table II: Add notes at bottom as follows:

‘Notes:

1. Waveshape: Rectangular negative-going pulse from +13 to -29V.
   PW : 2.55 +/-0.07 US.
   PRF : 20 kHz.

2. Waveshape: Rectangular positive-going pulse from O to +20V .
   PW : 0.8 +/-0.2 US.
   PRF : 20 kHz.

3. Waveshape: Cosine-squared
   Burst frequency: 60 MHZ
   PW : 280 +/-10 ns at 50% amplitude points
   PRF : 20 kHz.”

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:43Z
Check the source to verify that this is the current version before use.

PAGE 19

Table VIII, 'Test equipment list": Delete "8. Oscilloscope" and substitute "8. Oscilloscope".

custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1285-A830)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:43Z
Check the source to verify that this is the current version before use.