INCH-POUND

MIL-I-60522A(OS)
10 August 1994
SUPERSEDING
MIL-I-60522
11 August 1969

MILITARY SPECIFICATION

INITIATOR, CARTRIDGE ACTUATED, M5A2 METAL PARTS ASSEMBLY

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Departments of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M5A2 Cartridge Actuated Initiator Metal Parts Assembly (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550	Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-109	Quality Assurance Terms And Definitions
MIL-STD-413	Visual Inspection Guide for Elastomeric O-rings

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 8420), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.
(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

Naval Surface Warfare Center, Indian Head (CAGE Codes 19200 and 19203)

8596171	Initiator, Cartridge Actuated, M5A2 Metal Parts Assembly
8796541	Box, Fiberboard (Inner), Packing, Ammunition, For Initiator, Cartridge Actuated, M3A2, M5A2
8796542	Box, Packing, Ammunition, For Initiator, Cartridge Actuated, M3A2, M5A2
9216934	Box, Fiberboard (Outer), Alternative, Packing Ammunition, for Initiator, Cartridge Actuated, M3A2, M5A2

U.S. Air Force

TPO 00-932-5031	Initiator, Cartridge Actuated, M3A2, M5A2

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Attn: Data Control Branch (Code 8410), Indian Head, MD 20640-5035.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to the first article inspection (see 4.4 and 6.3).

3.2 Materials. All materials used in the manufacture of the initiators shall conform to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Raw material. The contractor shall be responsible for selecting from the classification list contained in the raw material specification the surface and physical condition of the raw material intended for use in manufacture.

3.3 Hardness and other physical properties. Hardness and other physical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

3.4 Hydrostatic pressure. The initiator chamber and cap shall withstand a hydrostatic pressure of 5500 to 6500 pounds per square inch (psi) for 15 seconds, minimum, without deformation or mechanical failure (see 6.4.1).

3.5 Shear pin strength. The shear pin, after application of protective finish, shall shear when a load of 41 ± 5 pounds is applied at the steady rate of 0.125 inches per minute.

3.6 Metal parts assembly. Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled handtight.

3.7 Protective finish. Protective finish shall be in accordance with the applicable specifications and shall apply to all surfaces of the component regardless of contour configuration.

3.8 Residual magnetism. The metal parts assembly shall not deflect the indicator of the compass more than five degrees in either direction using procedures in 4.6.5.

3.9 Workmanship. Initiators shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

3.9.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.9.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.9.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements (see 6.2).

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.1.2 Quality assurance terms and definitions. Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.3 Inspections. Inspections shall be in accordance with MIL-A-2550.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: room ambient (68 to 77•F)
b. Altitude: sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psi

4.4 First article inspection. At the beginning of regular production, the contractor shall submit an initial production sample to a Government approved facility for evaluation. The sample shall consist of five metal parts assemblies, nine sets of unassembled parts, one set of unassembled parts without plating or final protective finish, and fifty shear pins from the same lot of shear pins tested by the contractor. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, must be the same as will be used for regular production and shall be obtained from the same source of supply. After inspection and provisional acceptance at source, the first article sample shall be inspected for all requirements of the drawings and specifications. The Government reserves the right to require new first article samples until an acceptable sample is submitted (see 6.3).

4.5 Quality conformance inspection.

4.5.1 Lot.

4.5.1.1 Submission of product. Unless otherwise specified by the contracting activity, formation and identification of lots shall be in accordance with MIL-STD-105.

4.5.1.2 Size of lot. For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 1200 assemblies, maximum, provided the homogeneity requirements of inspection lots have been retained.

4.5.2 Examination. One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects. Four power (4x) magnification may be used in performing visual examination for such defects as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability. All nonconforming material shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.5.2.1 Retainer, Cartridge, Drawing 8593013, covering a detail of Drawing 8596171.

Characteristics	Defect	Method of Inspection
Critical		
1	Metering slots in base missing	Visual
Major		
101	Pitch diameter of thread, max	Gage
102	Minor diameter of thread, max	Gage
103	Concentricity of cavity with pitch diameter of thread	Gage
104	Perpendicularity of pitch diameter of thread with base	Gage
105	Symmetry of metering slots in base with body	Gage
106	Diameter of cavity, max	Gage
107	Depth of cavity	Gage
108	Depth to bottom of counterbore	Gage
109	Depth of metering slots in base	Gage
110	Length of effective thread, min	Gage
111	Internal radius at mouth cavity	Gage
112	Total length	Measure
113	Width of metering slots in base	Measure
114	Drill point in base, max	Measure
115	Number of elongated slots incorrect	Visual
116	Thread damaged or not full	Visual
117	Metal defective	Visual
118	Protective finish inadequate or defective	Visual
119	Surface finish on internal radius and base improper	Visual
120	Burr	Visual
121	Foreign matter	Visual
Minor		
201	Pitch diameter of thread, min	Gage
202	Diameter of cavity, min	Gage
203	Diameter of head	Gage
204	Diameter of body	Gage
205	Length of elongated slots	Measure
206	Length of head	Measure
207	Width of elongated slots	Measure
208	Location of elongated slots	Measure
209	Angle between head and body	Measure
210	Angular location of metering slots	Visual
211	Marking missing, incorrect, or illegible	Visual
212	Profile of elongated slots	Visual
213	Radius missing or incorrect	Visual
214	Surface finish improper, except as otherwise classified	Visual

4.5.2.2 Chamber, Initiator, Drawing 8593014, covering a detail of Drawing 8596171.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

Critical		
1	Metal defective	Visual
Major		
101	Pitch diameter of large thread, min	Gage
102	Major diameter of large thread, min	Gage
103	Pitch diameter of small thread, min	Gage
104	Major diameter of small thread, min	Gage
105	Concentricity of counterbore with pitch diameter of large thread	Gage
106	Concentricity of datum diameter with small thread	Gage
107	Diameter of counterbore	Gage
108	Depth of cavity	Gage
109	Thickness of wall, min	Gage
110	Location of datum diameter	Gage
111	Profile of gas port	Gage
112	Thread damaged or not full	Visual
113	Chamfer at base of cavity missing or incorrect	Visual
114	Protective finish inadequate or defective	Visual
115	Surface finish at end of gas port improper	Visual
116	Burr	Visual
117	Foreign matter	Visual
Minor		
201	Pitch diameter of large thread, max	Gage
202	Pitch diameter of small thread, max	Gage
203	Diameter of cavity	Gage
204	Diameter of hole	Gage
205	Diameter of small thread pilot	Gage
206	Diameter of large thread pilot	Gage
207	Length of large thread pilot	Gage
208	Length of gas port	Gage
209	Thickness of wall, max	Gage
210	Location of small thread	Gage
211	Depth of counterbore	Measure
212	Total length	Measure
213	Length to end of large thread	Measure
214	Marking missing, incorrect, or illegible	Visual
215	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
216	Surface finish improper, except as otherwise classified	Visual

4.5.2.3 Pin, Shear, Drawing 8594745, covering a detail of Drawing 8596171.

Critical
None defined

Major

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

101	Diameter, max	Gage
102	Total length, min	M e a s u r e
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Surface finish improper	Visual
106	Burr	Visual
107	Foreign matter	Visual

Minor

201	Total length, max	Measure
202	Profile of end	Measure

4.5.2.4 Cap, Drawing 8595254, covering a detail of Drawing 8596171.

Critical
None defined

Major

101	Pitch diameter of thread, max	Gage
102	Minor diameter of thread, max	Gage
103	Concentricity of pitch diameter of thread with center hole, including perpendicularity with base of cavity	Gage
104	Symmetry of flats with pitch diameter of thread	Gage
105	Diameter of hole	Gage
106	Depth of cavity	Gage
107	Length of effective thread, min	Gage
108	Length to thread centerline	Gage
109	Thickness of base	Gage
110	Height, max Gage	
111	Profile of body	Measure
112	Internal radius at base of large thread cavity missing or incorrect	Visual
113	Thread damaged or not full	Visual
114	Metal defective	Visual
115	Protective finish inadequate or defective	Visual
116	Burr	Visual
117	Foreign matter	Visual

Minor

201	Pitch diameter of thread, min	Gage
202	Pitch diameter of setscrew thread	Gage
203	Minor diameter of setscrew thread, max	Gage
204	Diameter of flange holes	Gage
205	Length between flange holes	Gage
206	Width across body flats	Gage
207	Location of flange holes	Measure
208	Length of flange	Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

209	Width of flange	Measure
210	Thickness of flange	Measure
211	Location of setscrew holes	Measure
212	Marking missing, incorrect, or illegible	Visual
213	Radius of chamfer missing or incorrect, except as otherwise classified	Visual
214	Surface finish improper	Visual

4.5.2.5 Housing, Firing Pin, Drawing 8593012, covering a detail of Drawing 8596171.

Critical		
1	Surface finish of cavity	Gage
Major		
101	Pitch diameter of internal thread, max	Gage
102	Minor diameter of internal thread, max	Gage
103	Pitch diameter of external thread, min	Gage
104	Major diameter of external thread, min	Gage
105	Concentricity of pitch diameter of internal thread with cavity	Gage
106	Concentricity of groove with flange	Gage
107	Concentricity of boss cavity with cavity	Gage
108	Concentricity of pitch diameter of external thread with cavity	Gage
109	Concentricity of cavity with flange	Gage
110	Concentricity of striker hole with cavity	Gage
111	Concentricity of body, flange end, with flange	Gage
112	Perpendicularity of flange face with cavity	Gage
113	Perpendicularity of face of boss with pitch diameter of external gage	Gage
114	Symmetry of pin hole with cavity	Gage
115	Symmetry of width across flat with body, flange end	Gage
116	Diameter of cavity, max	Gage
117	Diameter of datum location	Gage
118	Diameter of pin hole, max	Gage
119	Diameter of groove	Gage
120	Diameter of flange, min	Gage
121	Depth of counterbore, internal thread	Gage
122	Depth of thread cavity	Gage
123	Length of effective internal thread, min	Gage
124	Angle at datum diameter	Gage
125	Height of boss	Gage
126	Diameter of chamfer at internal thread cavity	Measure
127	Length of internal thread, max	Measure
128	Angle at bottom of thread cavity, min	Measure
129	Angles at mouth of internal thread cavity	Measure
130	Radius at root of boss	Measure
131	Profile of groove	Visual
132	Thread damaged or not full	Visual
133	Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

134	Protective finish inadequate or defective	Visual
135	Surface finish of cavity chamfer, thread cavity improper	Visual
136	Burr or sharp corner	Visual
137	Foreign matter present	Visual

Minor

201	Pitch diameter of internal thread, min	Gage
202	Pitch diameter of external thread, max	Gage
203	Pitch diamter of pin hole thread	Gage
204	Minor diameter of pin hole thread, max	Gage
205	Diameter of cavity, min	Gage
206	Diameter of boss cavity	Gage
207	Diameter of body, flange end	Gage
208	Diameter of pin hole, min	Gage
209	Diameter of counterbore, internal thread	Gage
210	Diameter of undercut in cavity, if applicable	Gage
211	Diameter of flange, max	Gage
212	Diameter of striker hole	Gage
213	Depth of striker hole	Gage
214	Depth of drill hole, pin thread, max	Gage
215	Total length	Gage
216	Length of effective thread, pin hole	Gage
217	Length across flanges	Gage
218	Length from bottom of cavity to boss face	Gage
219	Width of rear flange	Gage
220	Location of pin hole	Gage
221	Diameter of body, midsection	Measure
222	Length of body, midsection	Measure
223	Length of flat, flange end	Measure
224	Width across flats	Measure
225	Width of rear flange	Measure
226	Width of groove	Measure
227	Widht of undercut in cavity, if applicable	Measure
228	Marking missing, incorrect, or illegible	Visual
229	Radius or chamfer or both missing or incorrect, except as otherwise classified	Visual
230	Surface finish improper, except as otherwise classified	Visual

4.5.2.6 Pin, Firing, Drawing 8594744, covering a detail of Drawing 8596171.

Critical
None defined

Major

101	Concentricity of groove with body	Gage
102	Concentricity of striker with body	Gage
103	Concentricity of striker shoulder with body	Gage
104	Symmetry of pin hole with body	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

105	Diameter of body, min	Gage
106	Diameter of groove	Gage
107	Diameter of striker, max	Gage
108	Diameter of pin hole, max	Gage
109	Depth of pin hole, max	Measure
110	Profile of striker	Measure
111	Profile of groove	Measure
112	Metal defective	Visual
113	Protective finish inadequate or defective	Visual
114	Surface finish of body and striker tip improper	Visual
115	Burr or sharp corner	Visual
116	Foreign matter	Visual

Minor

201	Diameter of body, max	Gage
202	Diameter of striker shoulder	Gage
203	Diameter of pin hole, min	Gage
204	Depth of pin hole, min	Gage
205	Length from body to tip of striker	Gage
206	Length of striker	Gage
207	Location of pin hole	Gage
208	Location of groove	Gage
209	Depth of slot in base	Measure
210	Total length	Measure
211	Width of groove	Measure
212	Width of slot in base	Measure
213	Location of slot in base	Visual
214	Marking missing, incorrect, or illegible	Visual
215	Radius missing or incorrect	Visual
216	Surface finish improper, except as otherwise classified	Visual

4.5.2.7 Assembly, Firing Pin Housing, Drawing 8596171, less all components except Drawings 8593012, 8594744, MS28775-009, and MS28775-214.

Critical

1	Protrusion of firing pin	Gage
2	O-ring missing	Visual
3	Metal defective	Visual

Major

101	O-ring not lubricated	Visual
102	Thread damaged or not full	Visual

Minor
None defined

4.5.2.8 Assembly, Drawing 8596171.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

Critical		
1	Any part missing	Visual
2	Improper assembly	Visual
3	Marking missing, incorrect, or illegible	Visual
Major		
101	Height of cap, max	Gage
102	Setscrew missing, loose, above flush or not covered with barium material	Visual/Manual
Minor		
201	Total length, max	Gage
202	Location of labels incorrect	Gage
203	Protective cap or plug missing	Visual
204	Protective finish inadequate or defective	Visual

4.5.2.9 Box, Fiberboard (Inner) Packing Ammunition, Drawing 8796541.

Critical
None defined

Major
None defined

Minor		
201	Contents loose	Manual
202	Box damaged	Visual
203	Marking missing, incorrect, or illegible	Visual
204	Cut, damaged, or improperly sealed bag	Visual

4.5.2.10 Box, Packing, Ammunition, Drawing 8796542.

Critical
None defined

Major
None defined

Minor		
201	Contents loose	Visual/Manual
202	Strapping missing, loose, broken, or improperly assembled	Visual/Manual
203	Contents of box exposed	Visual
204	Box damaged	Visual
205	Marking missing, incorrect, or illegible	Visual
206	Number of units incorrect	Visual

4.5.2.11 Box, Fiberboard (Outer) Alternative, Packing Ammunition, Drawing 9216934.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

Critical
None defined

Major
None defined

Minor

201	Contents loose	Manual/Visual
202	Carton broken or damaged	Visual
203	Number of units contained incorrect	Visual
204	Marking missing, incorrect, or illegible	Visual
205	Tape incomplete	Visual

4.5.3 Inspection testing. The following tests shall be performed in accordance with 4.6.

4.5.3.1 Hardness. Fifty units from each heat treated lot of components shall be tested for compliance with the requirements on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.5.3.2 Hydrostatic pressure. Each chamber and cap shall be subjected to the hydrostatic pressure test. Failure of any cap or chamber subassembly to comply with 3.4 shall be cause for rejection of the subassembly.

4.5.3.3 Shear pin strength. Fifty pins from each lot of shear pins shall be subjected to the hydrostatic pressure test. Failure of any shear pin to comply with 3.5 shall be cause for rejection of the lot.

4.5.3.4 Protective finish. The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.5.3.5 Residual magnetism. Each assembly shall be subjected to the test for excessive residual magnetism as specified in 4.6.5. Failure of any unit in the inspection sample to comply with 3.9 shall be cause for rejection of the assembly.

4.6 Test methods and procedures.

4.6.1 Hardness. Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the requirements of the applicable drawing.

4.6.2 Hydrostatic pressure. Prior to application of protective finish the cap and chamber shall be mounted in the device, using a fixture for properly sealing all openings, and subjected to the internal hydrostatic pressure to determine compliance with 3.4.

4.6.3 Shear pin strength. After application of protective finish, the pin shall be subjected to the shear pin strength test to determine compliance with 3.5. The test shall be performed in a fixture in conjunction with a tensile testing machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.6.4 Protective finish. Test procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing.

4.6.5 Residual magnetism. The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly for four full passes.

4.7 Inspection of packaging. The sampling and inspection of the packaging, packing, and container marking shall be in accordance with the requirements of section 5.

5. PACKAGING

5.1 Packing and marking. Packing and marking shall be Level A or B, as specified by the contracting activity (see 6.2). Level A shall be in accordance with Drawings 8796541 and 8796542. Level B shall be in accordance with Drawings 8796541 and 9216934.

5.2 Air Force packaging. Air Force packaging shall be in accordance with TPO-00-932-5031.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The initiator assembly is used in conjunction with other propellant actuated devices in Aircrew Emergency Escape Systems.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2)

c. If first article inspection is required (see 3.1 and 6.3)

d. The responsible inspection activity (see 4.1)

e. Any special inspection requirements (see 4.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

f. Level of packing and marking (see 5.1)

6.3 First article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors that the items should be a first article sample. The first article should consist of five metal parts assemblies, nine sets of unassembled parts, one set of unassembled parts without plating or final protective finish, and fifty shear pins. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Definition.

6.4.1 Mechanical failure. Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

6.5 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.6 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Preparing activity

Navy - OS

(Project 1377-NE19)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.