MILITARY SPECIFICATION

LOGIC FLIP-FLOP: 10526505

This amendment forms a part of Military Specification MIL-L-60196(MU), dated 24 February 1965.

Table III, Characteristic 305, test procedures column: Delete "3.5.2.1.3" and substitute "4.5.2.1.3"; Characteristic 308, test procedures column: Delete "4.5.3.1".

Paragraph 4.4.1.1: Delete item 7; item 9, description column line 2: Delete "Millicroseconds" and substitute "Millimicroseconds"

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating. - This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24-hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.2.1.3. In order to demonstrate this capabibility, the tests of 4.5.2.1.3 shall be performed a minimum of once each 6 hours of the 24-hour period. The final test shall be conducted during the final portion of the 24-hour period. Between tests, the board shall be electrically energized as described in 4.5.2.1"

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray. - This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 period salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2.1 and 4.5.2.1.3.1 for compliance with 3.3.6".

Paragraph 4.5.2.1.4: Delete second sentence in its entirety.

Paragraph 4.5.2.1.5: Delete "and pin 24B"

Paragraph 4.5.2.1.5.1, line 3: Delete "± .180" and substitute "+.180". Line 5: Delete "± .360 volts" and substitute "+.360 volts."

Paragraph 4.5.2.1.6: Add the following sentence at the beginning of this paragraph "Remove the plus 15 volt power supply from pin 39A".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.

Second sentence; following "Pin 39A": Delete "and pin 24B".

Paragraph 4.5.2.1.7, First sentence, following "Pin 39A": Delete "and pin 24B".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A047

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.