MILITARY SPECIFICATION

NETWORK C: 10526476

This amendment forms a part of Military Specification MIL-N-60211(MU), dated 3 March 1965.

Paragraph 3.4.7.3(b): Delete in its entirety.

Paragraph 3.4.7.3(d): Delete in its entirety and renumber remaining paragraphs of 3.4.7.3.

* Following paragraph 4.1.1, add paragraphs 4.1.2, 4.1.2.1 and 4.1.2.2.

"4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) units manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected and a record of this inspection, including certificates of conformance for materials shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

* Paragraph 4.2.3: Add the following sentence: "No lots shall be accepted until control samples have been satisfactorily tested."

* Paragraph 4.3.2: Delete first sentence and substitute:

"The units shall be selected at random by a Government representative as control samples from each three (3) months production or portion thereof as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

3 units per first 100 produced
5 units per 200
7 units per 300
9 units per 400
10 units per 500
12 units per 700
15 units per 1000
and 2 units for each 100 items produced in excess of 1000."

* Paragraph 4.3.3: Add to end of paragraph"(see 4.2.3)".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926 except that the humidity shall be maintained at 92 to 97 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.2.1.5, 4.5.2.4.3.4, 4.5.2.5.2.3, 4.5.2.6.3 and 4.5.2.7.5.2. In order to demonstrate this capability, the tests of 4.5.2.1.5, 4.5.2.4.3.4, 4.5.2.5.2.3, 4.5.2.6.3 and 4.5.2.7.5.2 shall be performed a minimum of once each 6 hours of the 24 hour period. The final test shall be conducted during the final portion of the 24 hour period. Between tests, the board must be electrically energized as described in Table IV and using the loads specified in 4.5.2.1.2.1, 4.5.2.4.1.1, 4.5.2.5.2.1, 4.5.2.6.2 and 4.5.2.7.5.1."

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft-hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.2."

Paragraph 4.5.1.5: Delete the second sentence in its entirety and substitute: "While at the operating temperatures of 3.3.3.1, the network shall be tested in accordance with 4.5.2.1.5, 4.5.2.4.3.4, 4.5.2.5.2.3, 4.5.2.6.3 and 4.5.2.7.5.2 to determine compliance with the requirements as specified in 3.3.3.1."

Table IV, Item No. Column, line 14: Delete "21" and substitute "20".

Paragraph 4.5.2.1.3.1: Delete the second sentence in its entirety and substitute: "The voltage measured from pin 17B to ground shall be plus 112 ± 15 volts dc."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.2.4.3, line 3: Delete "- ± 1 to" and substitute "0 ± 1 volt to".

Paragraph 4.5.2.4.3.2, line 4: Delete "at 1.5" and substitute "at minus 1.5".

Table X: Delete Column C, Volts dc, in its entirety and substitute:

C Voltage less positive than
+0.3 vdc
+0.8 vdc
+0.7 vdc

Paragraph 4.5.2.6.2, line 5: Delete "4.10.2, item 20" and substitute "4.4.1.1, item 19".

Paragraph 4.5.2.7.2.1, line 2: Delete "90.0" and substitute "90.9". Also in line 8: Delete "between".

Paragraph 4.5.2.7.3.3: Delete in its entirety.

Paragraph 4.5.2.7.4(a), line 5: Delete "micro seconds" and substitute "Milliseconds".

Figure 6A: Delete time base numbers of 0, 5, 10, 15, 20 and substitute time base numbers of 0, 10, 20.

Figure 7: Delete "-40°F +0 +140°F" and substitute "-40°F +0 +135°F".

Paragraph 4.5.2.5.2.3, line 3: Delete "4B" and substitute "4A".

Paragraph 4.5.2.7.3.3: Delete in its entirety and substitute:

"4.5.2.7.3.3 Disconnect the plus 35 volts from the module. The voltage from pin 5B to pin 24A shall be less than 1 volt. Remove power connections from pin 15A and pin 12B."

Paragraph 4.5.2.7.4(a), line 2: Delete "6V ± 1.2 Volts" and substitute "10 ± 1.2 Volts".

Paragraph 4.5.2.7.4(a), line 3: Delete "6 to 0" and substitute "10 to 0".

*The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:
Army - MU

Preparing activity:
Army - MU

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.