INCH-POUND

MIL-P-63316 (AR)
AMENDMENT 2
09 April 1993
SUPERSEDING
AMENDMENT 1
9 February 1981

MILITARY SPECIFICATION

PRIMER, BATTERY, ELECTRIC PARTS, FOR AND LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of MIL-P-63316 (AR), dated 24 July 1979, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 3.4.1.1 No-fire test. Delete "(70° ± 10°F)" and substitute "(Ambient only)".

* 3.4.1.2 All-Fire output test. Delete "(70° + 10°F)".

* Add the following paragraph:

"3.4.2 Test temperatures and conditioning. The battery primers shall be temperature conditioned for a minimum of one (1) hour prior to testing. Conditioning temperatures are as follows:

a. Cold: Minus forty-five degrees Fahrenheit, minus five degrees Fahrenheit (-40°F - 5°F).

b. Ambient: Seventy degrees Fahrenheit plus or minus ten degrees Fahrenheit (+70°F ± 5°F)".

c. Hot: One hundred and forty-five degrees Fahrenheit, plus five degrees Fahrenheit (+145°F + 5°F)".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

PAGE 4

* Submission. Delete "Primer, Battery, Electric 9292624 150" and substitute "Primer, Battery, Electric 9292624 300"

PAGE 7

* TABLE I - FIRST ARTICLE INSPECTION, Sheet 2 of 2:

Prime, Battery, Electric, Delete "150" and substitute "300".

Sensitivity and output test, Delete in its entirety and substitute the following:

"Sensitivity and Output Tests 225

No-fire test (Ambient only) (+70°F ± 10°F)	225-0-1	3.4.1.1	4.5,4.1
All-fire output test-Hot (+145°F + 5°F)			
Sleeve enlargement	75-0-1	3.4.1.2	4.5.4.2
Dent in plate	75-0-1	3.4.1.2	4.5.4.2
All-fire output test-Cold (-40°F - 5°F)			
Sleeve enlargement	75-0-1	3,4.1.2	4.5.4.2
Dent in plate	75-0-1	3.4.1.2	4.5.4.2
All-fire output test-Ambient (+70°F ± 10°F)			
Sleeve enlargement	75-0-1	3.4.1.2	4.5.4.2
Dent in plate	75-0-1	3.4.1.2	4.5,4.2"

PAGE 14

4.4.2.6, Major 101: "Certificaiton" corrected to "Certification".

PAGE 15

4.4.2.7, Major 101: "Diametr" corrected to "Diameter" - "Gage" to "Visual".

Major 104: "Separted" corrected to "Separated".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.2.8:

* Delete "Sensitivity and Output Test. (+70°F ± 10°F) 125 ..." and substitute "Sensitivity and output test. 150 ...".

* Major 111: Delete "... (a) 125-1-2 ..." and substitute "...1/ 150-1-2 ...".

* Major 112: Delete "... 125-1-2 ..." and substitute " ...2/ 150-1-2...".

* Major 113: Delete "... dent in place 125-1-2 ..." and substitute "...dent in plate 2/ 150-1-2 ...".

NOTES:

* Delete note a in its entirety and substitute the following:

"1/ 150 samples from No-fire test to be used to perform All-fire tests below."

2/ 50 Samples at each temperature (Hot, Cold, and Ambient) shall be tested for All-fire tests. See 3.4.2 for temperature conditioning."

PAGE 17

4.4.2.8, Major 118: Add 3.5.2 to the requirement paragraph.

PAGE 19

4.4.5.1: Delete Dwg 9275629.

4.4.5.1.a: Delete Dwg "9275663" to "9275631". Change ".003 to 0.55 ± .001" to ".003 to 0.055 ± .001".

4.4.5.1.b: Delete "copper-zinc lead allor rod ... on the outside diameter". Add "Brass allow 360, having a hardness equivalent to Rockwell A40-55 measured on the outside diameter while supporting the inside diameter."

4.4.5.1: Add paragraph d and e:

"d. The material for the witness plate, Dwg 9275633 shall be Grade C lead.

e. The iridite finish of the base, Dwg 9275632 is optional.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

PAGE 20

4.5.4.1: Add sentence: “No-fire may be performed on a group of units connected in series before assembly to test equipment for output test. If one or more primers function, the remaining primers connected in series shall be retested."

* 4.5.4.2 All-fire output test. Delete "(70° ± 10°F). Following the ... shall be fired ..." and substitute “Following the No-fire test of 4.5.4.1, the battery primer samples shall be equally divided into three (3) groups: one group tested at hot (+145°F + 5°F), one group tested at cold (-40°F - 5°F), and one group tested at ambient (+70°F ± 10°F). The battery primers shall be temperature conditioned for a minimum of one (1) hour prior to testing per their respective group temperatures. The battery primers shall be fired ...”.

PAGE 22

4.5.7: Delete “The measurement shall be made with a meter capable of measurement to the nearest 0.01 ohm.”.

PAGE 23

6.1 Change "XM74” and “XM75 AT/AV" to "M74" and "M75 AT".

Add XM77 AP, XM78 AT/AV.

6.5: After the words “period of time” add “or at the request of the Contracting Officer.”

* 6.5.1 Sensitivity and output: Delete "Two hundred (200) battery primers ..." and substitute “Two hundred and ten (210) battery primers ...".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1345-A616)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.