INCH-POUND

MIL-S-63523A (AR)
AMENDMENT 1
03 January 1996

MILITARY SPECIFICATION

SIMULATOR, LAUNCHING, ANTI-TANK GUIDED MISSILE AND ROCKET, M22, PERFORMANCE SPECIFICATION

FOR

This Amendment forms a part of MIL-S-63523A (AR), dated 20 September 1985, and is approved for use by the U.S. Army Armament, Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add new paragraph:

"3.4.2.3 Hydrogen gas generation. The pyrotechnic materials used in the manufacture of the simulator shall not cause the generation of hydrogen gas when reacted with moisture as evidenced by item distortion and/or packaging swelling. The simulators shall be safe to handle and fire after being subjected to the test specified in 4.5.8.9.

PAGE 7

3.6.12: Temperature-Humidity. Delete in its entirety.

PAGE 10

TABLE I: Delete "Temperature-Humidity/Function 30, 1 box, 1-2, 3.6.12, 4.5.8.9, 4.5.3" and substitute "Humidity, 30, 1-2, 3.4.2.3, 4.5.8.9, 4.5.3 (ambient only)".

PAGE 18

4.5.8.9: Delete in its entirety and substitute:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:03Z
Check the source to verify that this is the current version before use.

"4.5.8.9 Hydrogen gas generation. The simulators in their packaging shall be tested in accordance with MIL-STD-810E, Method 507, Humidity, Procedure III-Aggravated (15 cycles). Any evidence of item distortion and/or packaging swelling shall cause the lot to be rejected. Observations shall be made for compliance with the applicable functioning requirements."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1370-0004)

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.