MIL-T-63263(AR)
AMENDMENT 2
11 October 1979
SUPERSEDING
AMENDMENT 1
7 June 1979

MILITARY SPECIFICATION

TEST SET, ELECTRONICS SYSTEMS: M91

This Amendment forms a part of Military Specification MIL-T-63263(AR), dated 3 May 1978.

* Add paragraph 4.4.2.18 as shown on page 4 of this amendment.

PAGE 2

* Under "Military Standards" - Delete the following:

"MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For"

PAGE 3

* Paragraph 3.4 - Delete: "except for temperature humidity which is contained in MIL-STD-331".

* Paragraph 3.4.1 - Add to end of paragraph: "using curve AW of Figure 514.2-7."

Delete paragraph 3.4.2.

* Paragraph 3.4.3 - Delete "Test 105.1 of MIL-STD-331..." and substitute "Method 507.1, Procedure I".

FSC: 4925

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

PAGE 5

Table I - Delete the following line:

"Helicopter vibration 2 100% 3.4.2 4.4.3.1"

PAGE 11

* Paragraph 4.4.2.5 - Delete "9326142" and substitute "9326146".

PAGE 15

* Paragraph 4.4.2.9 - Delete Minor Defect 201.

PAGE 20

* Paragraph 4.4.2.14 - Delete Major Defect 102.

PAGE 24

Delete paragraph 4.4.3.2.

PAGE 28

* Paragraph 4.5.1, Pre-Setting Requirement - Add the following:

"5. Test Set Tester. - Set Dispenser Counter M1 to 'thirty'."

PAGE 30

Delete paragraph 4.5.2.

* Paragraph 4.5.3 - Add after "Procedure X": "using curve AW of Figure 514.2-7".

Source: https://assist.dla.mil Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

* Paragraph 4.5.4 - Delete in its entirety and substitute:

"4.5.4 Temperature humidity. Using equipment in accordance with 4.4.4, subject each first article unit to Test Method 507.1, Procedure I of MIL-STD-810. Replace Step 6 & 7 of test method with the following:

> Step 6 - At the end of the tenth cycle, remove and inspect the test item and condition the test item at 25 ± 5°C (ambient) for at least one (1) hour, operate the test item and obtain results in accordance with General Requirements, 3.2.

Any item which fails to meet the applicable requirements shall cause the first article sample to be rejected."

PAGE 32

* Add paragraph 6.6:

"6.6 Asterisks. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 4925-A037

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Spring		9326072
			NEXT HIGHER ASSEMBLY: 9326211

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Coil diameter incorrect		0.65%	3.2	Gage
202	Minimum free length incorrect		0.65%	3.2	Gage
203	Maximum solid height incorrect		0.65%	3.2	Gage
204	Spring rate incorrect		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.