INCH-POUND

MIL-B-44388(GL)
29 December 1989

MILITARY SPECIFICATION

BREAD CRISP BARS, RATION LIGHTWEIGHT, 30-DAY

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers bread crisps in bar form for use by the Department of Defense as a component of operational rations.

1.2 Classification. The bread crisps shall be of the following types, as specified (see 6.1).

Type I - Cheese bread crisp bars

Type II - Cheese-bacon bread crisp bars

Type III - Coconut bread crisp bars

Type IV - Orange-nut bread crisp bars

Type V - Pizza bread crisp bars

Type VI - Tamale bread crisp bars

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

SPECIFICATIONS

FEDERAL

L-P-378	- Plastic Sheet and Strip, Thin Gauge, Polyolefin
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-C-843	- Cushioning, Material, Cellulosic
PPP-C-1752	- Cushioning Material, Packaging, Unicellular Polyethylene Foam, Flexible
PPP-C-1797	- Cushioning Material, Resilient, Low Density, Unicellular Polypropylene Foam

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Grades of Cheddar Cheese

U.S. Standards for Grades of Canned Pimientos

U.S. Standards for Grades of Canned Tomato Paste

(Copies are available from the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550, 401 M Street, S.W., Washington, DC 20460.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

NATIONAL ACADEMY OF SCIENCE

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of

Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Copies should be obtained from the American Association of Cereal Chemists, 3340 Pilot Knot Road, St. Paul, MN 55121.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

THE UNITED STATES PHARMACOPOEIAL CONVENTION, INC.

The United States Pharmacopoeia (USP)

(Application for copies should be addressed to the United States Pharmacopoeial Convention, Inc., 12601 Twinbrook Parkway, Rockville, MD 20852.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated

Onion and Garlic Association for Dehydrated Onion and

Garlic Products

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, 650 California Street, Suite 800, San Francisco, CA 94108.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

F 88 - Seal Strength of Flexible Barrier Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-11887.)

NATIONAL CHEESE INSTITUTE

National Cheese Institute Color Reference Standards

(Application for copies should be addressed to National Cheese Institute, 410 North Franklin Street, Chicago, IL 60606).

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:53Z
Check the source to verify that this is the current version before use.

3.2.1 Basil, ground. The ground basil shall be derived from the dried leaves of Ocimum basilicum L. and shall possess a sweet anise-like odor and aromatic, warm, slightly pungent flavor. The volatile oil content shall be not less than 0.4 mL per 100 grams of ground basil. A minimum of 95 percent, by weight, shall pass through a U.S. Standard No. 35 sieve.

3.2.2 Bits, formulated, cheddar cheese based. The bits shall have a distinct cheddar cheese flavor, and shall consist of hydrogenated soybean oil, dehydrated cheddar cheese, wheat starch, sugar, sodium caseinate, annatto powder, and yellow No. 5 color. The color of the bits shall be yellow to orange. The analytical requirements are: protein (N x 5.75), 14.0 to 16.0 percent; fat, 43.5 to 47.5 percent; fiber, 3.0 to 5.0 percent; ash, 2.0 to 4.0 percent; and carbohydrates, 29.0 to 37.0 percent (see 6.4.1).

3.2.3 Bits, wheat germ formulated, bacon flavored. The bits shall have a distinct bacon flavor and shall consist of hydrogenated soybean oil, wheat germ, sodium caseinate, salt, sugar, natural or artificial bacon flavor or a combination thereof, and artificial color. The color shall be tan to brown. The analytical requirements are: moisture, not more than 3.0 percent; protein (N x 5.75), 12 to 14.0 percent; fat, 62.0 to 66.0 percent; and carbohydrate, 17.0 to 23.0 percent (see 6.4.1).

3.2.4 Bits, wheat germ formulated, orange flavored. The bits shall have a distinct orange flavor and color, and shall consist of hydrogenated soybean oil, sugar, wheat germ, wheat starch, sodium caseinate, soy protein material or artificial flavor or a combination thereof; and yellow No. 6 color. The analytical requirements are: moisture, not more than 3.0 percent, protein (N x 5.75), 6.0 to 9.0 percent; fat, 42.0 to 48.0 percent; carbohydrate, 40.0 to 44.0 percent (see 6.4.1).

3.2.5 Bread crumbs. The bread crumbs shall be derived from fresh, white yeast raised, enriched, bread only. The shortening used in the bread rising shall be of vegetable origin only and shall contain BHA at a level not in excess of 0.02 percent of the fat content of the bread. The bread crumbs shall not have a moisture content exceeding 8.0 percent and shall be coarse ground, free flowing, and free from burnt, rancid, moldy or musty odors and flavors. The bread crumbs shall be manufactured in accordance with current manufacturing practices promulgated under Federal Food, Drug and Cosmetic Act regulations and applicable state statutes and regulations.

3.2.6 Cheese, cheddar, sharp, dehydrated, uncolored. Dehydrated cheddar cheese shall be derived from sharp, Grade A or better cheddar cheese of the U.S. Standards for Grades of Cheddar Cheese. The dehydrated cheese shall be uniform in composition and appearance, free from lumps that do not fall apart under light finger pressure, burnt specks, foreign material, and rancid flavors and odors. It shall be uncolored and shall contain not more than 3.0 percent moisture and 5.0 percent salt, and not less than 48.0 percent milkfat (uncolored).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

3.2.7 Cheese, cheddar, sharp, dehydrated, colored. Dehydrated cheddar cheese shall be derived from U.S. Grade A or better sharp, aged cheddar cheese of the U.S. Standards for Grades of Cheddar Cheese. The dehydrated cheese shall be uniform in composition and appearance, free from lumps that do not fall apart under light finger pressure, burnt specks, foreign material, and rancid flavors and odors. The color shall be within the range of No. 5 to No. 8 level when compared to the National Cheese Institute Cheese Color Reference Standards. The dehydrated cheese shall contain not more than 3.5 percent moisture and 5.0 percent salt, and not less than 48.0 percent milkfat.

3.2.8 Cheese, Parmesan, grated. The Parmesan cheese shall be grated and conform to the U.S. Standard of Identity for Parmesan cheese (21 CFR 133.165). The cheese shall have been aged 10 months or more and shall be free from musty, oxidized, tallowy or unclean flavors. The grated cheese shall be free-flowing uniform in color, and free from lumps that do not fall apart under light finger pressure.

3.2.9 Chili powder. Chili powder shall be a blend of 77 to 82 percent chili pepper; not less than 8.0 percent cumin; not less than 4.0 percent oregano; not less than 1 percent garlic; and not more than 8.0 percent salt. Anti-caking agents may be included at a level not to exceed 2.0 percent. The chili powder shall have a Scoville Pungency Value of not less than 900 and the moisture content shall not exceed 13.0 percent. Not less than 95 percent, by weight, of the chili powder shall pass through a U.S. Standard No. 20 sieve.

3.2.10 Coconut, shredded, dehydrated. The coconut shall be shredded, dry, unsweetened coconut. It shall have an odor and flavor typical of unsweetened coconut. The coconut shall be certified by the manufacturer to be salmonella negative.

3.2.11 Cream cheese, dehydrated. The dehydrated cream cheese shall be derived from fresh cream cheese complying with the FDA Standard of Identity for Cream Cheese (21 CFR 133.133). The dehydrated cheese shall be white to light cream in color, uniform in appearance and composition, and shall possess a characteristic pleasing and desirable flavor. The product shall be free from specks and burnt particles. The dehydrated cheese shall contain not more than 3.0 percent moisture and not less than 65.0 percent milkfat.

3.2.12 Fennel, ground. The ground fennel shall be derived from the ripe fruit of Foeniculum vulgare Mill. The ground fennel shall be light green-brown to yellow-brown in color and shall possess a pleasant aromatic odor with a flavor resembling that of anise. The fennel shall contain not less than 1.0 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 25 sieve.

3.2.13 Garlic powder. Garlic powder shall be Fancy Grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association (ADOGA) for Dehydrated Onion and Garlic Products.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

3.2.14 Lecithin, powder. Lecithin powder shall comply with the Food Chemical Codex.

3.2.15 Mineral pre-mix. All ingredients in the pre-mix shall be USP food grade and shall have a granulation that is free-flowing, free from hard agglomerates, and of a size that aids in maintaining a stable mixture. All encapsulated minerals shall have a particle size, after breaking up loose agglomerates, such that a minimum of 98 percent passes through a No. 20 U.S. Standard sieve, and a maximum of 20 percent through a No. 100 U.S. Standard sieve. The pre-mix shall consist of the following ingredients (see 6.4.2):

Ingredients	Percent by weight
Magnesium oxide, granular, heavy	51.29
Ferrous sulfate, encapsulated (see 3.2.15.1)	5.56
Zinc sulfate monohydrate, encapsulated (see 3.2.15.2)	4.17
Cupric sulfate, anhydrous, encapsulated (see 3.2.15.3)	0.83
Sugar, granulated	38.15

The above represents metallic compounds; therefore in order to obtain adequate minerals in the final product, the mineral pre-mix should be certified to contain the following minimum amounts of each elemental mineral:

a. 30.7 grams magnesium
b. 1.2 grams iron
c. 0.9 grams zinc
d. 0.16 grams copper

3.2.15.1 Ferrous sulfate, encapsulated. The ferrous sulfate, encapsulated, shall contain a minimum of 58 percent ferrous sulfate, encapsulated with a 42 percent edible coating of mono and diglycerides. One gram of encapsulated ferrous sulfate shall yield approximately 200 mg of iron.

3.2.15.2 Zinc sulfate, encapsulated. The encapsulated zinc sulfate shall contain a minimum of 58 percent zinc sulfate monohydrate ($ZnSO_4$ H_2O) encapsulated with a 40 percent edible coating of mono and diglycerides. One gram of encapsulated $ZnSO_4$ H_2O shall yield approximately 218 mg zinc.

3.2.15.3 Cupric sulfate, encapsulated. The encapsulated cupric sulfate ($CuSO_4$) anhydrous shall contain a minimum of 48 percent cupric sulfate with a 50 percent edible coating of mono and diglycerides. One gram of encapsulated cupric sulfate shall yield approximately 199 mg of copper.

3.2.16 Nitrogen. Nitrogen shall be U.S. Pharmacopoeia grade and shall be water or liquid nitrogen pumped.

3.2.17 Nuts, formulated, wheat-based, almond-flavored. Formulated wheat-based almond flavored nuts shall consist of a mixture of hydrogenated soybean oil, wheat germs, sugar, sodium caseinate, soy protein, artificial almond flavor

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

and artificial coloring. The formulated wheat-based nuts shall have an odor and flavor characteristic of almonds. The color of the nut shall be light tan or beige on the exterior with an interior color that is similar to the fresh nut. The moisture content shall not be greater than 3.0 percent. The formulated wheat-based nut shall have a protein content in the range of 8.5 to 14.0 percent, and a fat content ranging from 59.0 to 65.0 percent. Granulation percentages, as determined by using a round hole screen, are as follows: (see 6.4.4)

Screen	Percent weight on screen
5/16 inch	5 max
1/4 inch	60 ± 10
3/16 inch	35 ± 10
1/8 inch	5 max

3.2.18 Oil, vegetable. The vegetable oil shall be corn, cottonseed, or sunflower oil. Vegetable oil shall possess a clean, bland flavor and shall have a minimum stability of 25 hours (A.O.M.), a free fatty acid value not to exceed 0.05 percent, a moisture/volatile matter content not to exceed 0.06 percent, a peroxide value not to exceed 1.0 meg of peroxide per kg of fat, and shall pass a cold test of 5.5 hours (minimum).

3.2.19 Oregano, ground. Ground oregano shall be derived from the dried leaves of Origanum vulgare L and shall have a strong camphoraceous aroma and a pungent, slightly bitter flavor. The ground oregano shall contain not less than 2.0 mL of volatile oil per 100 grams and shall be of such size that 95 percent shall pass through a U.S. Standard No. 30 sieve.

3.2.20 Pectin, extra slow set. The extra slow set pectin shall be highly methoxylated, and shall have a setting time between 260 to 330 seconds. The extra slow set pectin shall comply with the requirements of the Food Chemical Codex (see 6.4.3).

3.2.21 Pepper, black, ground. Ground black pepper shall have been ground from the deep brown to black, deep-set, wrinkled, immature berries of Piper nigrum L. The ground pepper shall have a characteristic, penetrating odor, a hot, biting, pungent flavor and a light gray to speckled black-gray color. The ground pepper shall contain not less than 2.0 mL of volatile oil per 100 grams of ground black pepper and be of such size that 95 percent shall pass through a U.S. Standard No. 16 seive.

3.2.22 Pimentos, canned. Pimentos shall be chopped in pieces of 1/4 inch to 1/2 inch in size and shall be U.S. Grade C or better of the U.S. Standards for Grades of Canned Pimentos.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

3.2.23 Pepper, red. ground. Ground red pepper shall be derived from red, ripe fruit of Capsicum frutescens L. and shall possess the characteristic yellowish-red to red color. The Scoville Pungency Value shall be not less than 30,000 units. The red pepper shall be uniformly ground to allow a minimum of 95 percent, by weight, to pass through a U.S. Standard No. 40 sieve and not less than 95 percent, by weight, to be retained on a U.S. Standard No. 60 sieve.

3.2.24 Salt. Salt shall be iodized, white, refined sodium chloride, with or without anti-caking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.25 Sugar, white, granulated. Sugar shall be white, refined, granulated cane or beet sugar or a combination thereof.

3.2.26 Tomato paste. The tomato paste shall contain from 24 to 28 percent solids, shall be U.S. Grade A of the U.S. Standards for Grades of Canned Tomato Paste. See formulation (3.3.1.5) for required soluble solids content.

3.2.27 Vegetable shortening, powdered. The powdered vegetable shortening shall yield the following typical analysis: fat 75.0 ± 1.5 percent; protein 5.5 ± 0.5 percent; carbohydrate 15.0 ± 1.0 percent; and moisture 2.0 percent maximum.

3.2.28 Water. Water used for product preparation, ice making and sanitizing, shall conform to the National Primary Drinking Water Regulations.

3.2.29 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this specification. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formula.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Formulas for bread crisp bars.

3.3.1.1 Type I. Cheese bread crisp bars.

Ingredients	Percent by weight
Bread crumbs	36.82
Water, chilled, 35°F	24.75
Oil, vegetable	12.38
Cheese, cheddar, dehydrated, uncolored	10.89
Bits, formulated, cheddar cheese based	6.59
Vegetable shortening, powdered	4.13
Sugar, white, granulated	3.14
Mineral pre-mix	1.30

Source: https://assist.dla.mil -- Downloaded: 20261O-22T01:53Z
Check the source to verify that this is the current version before use.

3.3.1.2 Type II. Cheese-bacon bread crisp bars.

Ingredients	Percent by weight
Bread crumbs	33.11
Water, chilled, 35°F	24.75
Oil, vegetable	12.37
Cheese, cheddar, dehydrated, uncolored	10.89
Bits, formulated, cheddar cheese based	6.19
Bits, wheat germ formulated bacon flavored	4.14
Vegetable shortening, powdered	4.12
Sugar, white granulated	3.13
Mineral pre-mix	1.30

3.3.1.3 Type III. Coconut bread crisp bars.

Ingredients	Percent by weight
Bread crumbs	30.94
Water, chilled, 35°F	29.20
Coconut	14.85
Oil, vegetable	11.58
Sugar, white, granulated	5.94
Cream cheese, dehydrated	4.95
Mineral pre-mix	1.30
Pectin, extra-slow set	0.99
Lecithin	0.25

3.3.1.4 Type IV. Orange-nut bread crisp bars.

Ingredients	Percent by weight
Bread crumbs	29.41
Water, chilled 35°F	28.71
Nuts, formulated, wheat-based, almond flavored	10.89
Bits, wheat germ formulated orange flavored	10.89
Nuts, formulated, wheat-based, almond flavored ground, 1/8 inch	7.42
Oil, vegetable	5.94
Sugar, white, granulated	5.44
Mineral pre-mix	1.30

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

3.3.1.5 Type V. Pizza bread crisp bars.

Ingredients	Percent by weight
Bread crumbs	35.66
Water, chilled, 35°F	28.21
Oil, vegetable	13.86
Cheese, cheddar, dehydrated, uncolored	9.80
Cheese, parmesan	1.98
Tomato paste (26% solids) 1/	5.94
Sugar, white, granulated	3.13
Mineral pre-mix	1.30
Pepper, black, ground	0.04
Fennel, ground	0.02
Oregano, ground	0.02
Basil, ground	0.02
Garlic powder	0.02

1/ If the tomato solids available are higher than specified, the tomato solids must be adjusted to bring the solids level to that specified.

3.3.1.6 Type VI. Tamale bread crisp bars.

Ingredients	Percent by weight
Bread crumbs	38.04
Water, chilled, 35°F	25.48
Bits, formulated, cheddar cheese based	9.80
Oil, vegetable	9.31
Cheese, cheddar, dehydrated, colored	8.82
Vegetable shortening, powdered	4.90
Mineral pre-mix	1.30
Pimientos, chopped, drained	0.98
Chili powder	0.73
Salt	0.39
Garlic powder	0.20
Red pepper	0.05

3.3.2 Mixing of bread crisp bars ingredients.

3.3.2.1 Preparation of the pectin solution (coconut bread crisp type III bars only). The pectin solution shall be prepared by adding the pectin powder into part of the formula water in a blender.

3.3.2.2 Combining ingredients. All dry ingredients shall be mixed for a sufficient time to ensure thorough blending. The water, chilled to approximately 35°F (and the pectin solution for coconut bread crisp, type III bars) shall be added and mixed until blended. The oil shall be added slowly and mixed until blended. ture may be chilled to 40°F to facilitate forming.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

3.4 Forming of bars.

3.4.1 Direct forming into bars. The mixture shall be machine formed into 2.0 (± 0.2) inches wide by 3.0 (± 0.2) inches long by 0.5 (± 0.1) inch thick bars. The mixture may be chilled to 40°F to facilitate forming. The machine formed bars shall be placed in a freezer operating at 0°F or below within 1 hour after forming and shall have an internal temperature of 0°F or below within 8 hours after placing in the freezer. The frozen bars shall be in the freeze dehydration process within 24 hours after forming. Alternatively, the formed bars may be stored (see 3.4.2).

3.4.2 Handling, storage, and shipment of bars (prior to dehydration). The formed and frozen bars may be stored for not longer than 30 days provided they are protected from freezer burn, contamination, and deterioration. All packaging shall be approved for food contact by FDA. If bars are shipped between plants, they shall be protected from contamination and deterioration at all times. The internal temperature during storage and shipment shall be 0°F or below.

3.4.3 Dehydration. Bread crisp bars shall be freeze dehydrated at an absolute pressure not to exceed 1.5 millimeters of mercury and product temperatures not to exceed 150°F. If the platen temperature is maintained at 155°F or below with radiant heating, the product temperature may be disregarded. After dehydration is completed, the pressure shall be equalized to atmospheric level with nitrogen. In no case shall more than 72 hours elapse between dehydration and completion of packaging. During this interim period, the product shall be adequately protected from oxygen and moisture by either holding under a nitrogen atmosphere with 2.0 percent or less oxygen, or under a vacuum of at least 27 inches of mercury for the entire period. If vacuum is used, it shall be broken with nitrogen.

3.5 Pouch filling and sealing. The freeze-dehydrated bars shall be packaged immediately in accordance with 5.1.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. Each bar shall be 1.9 (± 0.2) inches by 2.8 (± 0.2) inches long by 0.5 (± 0.1) inch thick.

e. The weight of each bar shall be not less than 36 grams nor greater than 44 grams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

f. There shall be no forming streaks or stains

g. The shape of the bar(s) shall not be distorted.

h. No pouch shall contain a bar which has been broken or crumbled (more than three pieces).

i. The moisture content shall be not greater than 2.0 percent.

j. The aerobic plate count shall be not greater than 75,000 per gram in four of five samples and not greater than 150,000 per gram in any sample.

k. The E. coli count shall be less than 3 per gram (no positive tubes in the standard 3 tube MPN technique) in four of five samples and not greater than 20 per gram in any sample.

l. Each bar shall contain at least the following amounts of minerals:

Mineral	mg
Magnesium	200.0
Iron	7.5
Zinc	5.0
Copper	0.9

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The product shall be prepared, processed and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110, "Current Good Manufacturing Practice in Manufacturing, Packing or Holding of Human Food", and the plant sanitation requirements of the appropriate Government inspection agency.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to ensure compliance with the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance of palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.1.2 Laminated pouch material certification. A certificate of compliance may be accepted as evidence that the characteristics listed below conform to the specified requirements.

Material requirement	Requirement paragraphs	Test procedure
Thickness of films	5.1.1.1.1	As specified in L-P-378, except that a machinist's micrometer may be used provided that its graduations and accuracy conform to the requirements of L-P-378.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

Laminated material identification and construction	5.1.1.1.1 and 5.1.1.2.1	Laboratory evaluation.
Total thickness	5.1.1.2.1	As specified in L-P-378, except that a machinist's micrometer may be used provided that its graduations and accuracy conform to the requirements of L-P-378.

4.5.1.3 Unfilled pouch certification. A certificate of compliance may be accepted as evidence that unfilled pouches conform to requirements specified in 5.1.1.1.1. When deemed necessary by the USDA, testing of the unfilled preformed pouches for seal strength and integrity and air tightness of manufacturer's seals shall be as specified in 4.5.1.3.1 and 4.5.1.3.2.

4.5.1.3.1 Unfilled preformed pouch seal strength testing. The unfilled pouches shall be tested for seal strength in accordance with ASTM F 88, except that the testing speed shall be 10 or 12 inches per minute. Machines that apply the tensile load to the test specimen by movement of the upper or lower clamp may be used. Test specimens shall be cut 1/2 or 1 inch in width and to a length suitable for proper mounting. The lot size shall be expressed in pouches. The sample unit shall be one unfilled pouch. The sample size shall be the number of pouches indicated by inspection level S-1. Three adjacent specimens shall be cut from each of the three sealed sides of each pouch in the sample. The results shall be reported to the nearest 0.1 pound per inch of width. The average seal strength of each seal shall be calculated by averaging the test results of the three test specimens cut from that seal. Any test specimen failing to meet the individual test specimen seal strength requirement or any seal failing to meet the average seal strength requirement specified in 5.1.1.1.1 or 5.1.1.2.1 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.1.3.2 Unfilled preformed pouch integrity and air tightness of manufacturer's seals testing. Pouch integrity and air tightness of seals shall be determined by placing rigid material similar in size and shape to the bars into the pouch and sealing under a vacuum of not less than 25 inches of mercury. Not less than 96 hours after vacuum sealing, the pouch shall be examined for vacuum loss in acordance with the procedure in 4.5.4. The lot size shall be expressed in pouches. The sample unit shall be one unfilled pouch. The inspection level shall be I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 0.65.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

4.5.2.1 In-process examination at the assembly plant. Bulk-packed bread crisp bars shall be examined before unit packing into individual pouches. The lot size shall be expressed in shipping containers. The sample shall be the number of shipping containers indicated by inspection level S-3. Two bars shall be randomly selected from each of the shipping containers in the sample. Any bar found to have objectionable taste or odor (for example, burnt, scorched, stale, sour, rancid, moldy) shall be cause for rejection of the lot.

4.5.3 Filled and sealed pouch examination (applicable to unit packed and bulk packed pouches). The filled and sealed pouches shall be examined for defects listed in table I. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expessed in terms of defects per hundred units, shall be 0.65 for major defects and 4.0 for minor defects.

TABLE I. Filled and sealed pouch defects (Applicable to unit packed and bulk packed pouches) 1/

Category		Defect
Major	Minor	
101		Pouch size not as specified 2/
102		Not heat sealed as specified
103		Not clean 3/
104		Tear, hole, or open seal
105		Pouch has foreign odor
106		Evidence of delamination 4/
107		Seal widths not as specified
108		Closure seal not located as specified 5/
109		Presence of foldover wrinkles, occluded matter, and entrapped moisture or grease that reduces the effective closure seal to less than 1/8 inch 5/
110		Required labeling or marking missing, incorrect illegible, or that smudges

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:53Z
Check the source to verify that this is the current version before use.

TABLE I. Filled and sealed pouch defects (Applicable to unit packed and bulk packed pouches) 1/ (cont'd)

Category		Defect
Major	Minor	
	201	Tear notch missing 6/
	202	Tear notch not located as specified 6/
	203	Depth of tear notch not as specified 6/

1/ Any evidence of rodent or insect infestation shall be cause for rejection of the lot.

2/ Measurement may be accomplished on unfilled pouches being used for current production lot.

3/ Outer packaging shall be free from foreign matter which is unwholesome, has the potential to cause pouch damage (for example, glass, metal filings or generally detracts from the clean appearance of the package. The following examples shall not be scored as defects for unclean:

a. Foreign matter which presents no health hazard or potential pouch damage and which can be readily removed by gently shaking the package or by gently brushing the package with a clean dry cloth.

b. Dried product which affects less than 1/8 of the total surface area of one pouch face (localized and aggregate).

c. Water spots.

4/ Delamination shall be scored as a defect except delamination of outer ply when located in the seal area 1/16 inch or further from food product edge of seal. Pouches exhibiting this type of delamination shall be tested by manually flexing the delaminated area 10 times. The area of delamination shall be held between the thumb and forefinger of each hand with both thumbs and forefingers touching each other. The delamination area shall then be rapidly flexed by rotating both hands in alternating clockwise-counterclockwise directions. Care shall be exercised when flexing delaminated area near the tear notches to avoid tearing the pouch material. After flexing, the separated outer ply shall be grasped between the thumb and forefinger and gently lifted toward the food product edge of the seal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

If the separated area is too small to be held between the thumb and forefinger, a number two stylus shall be inserted into the delaminated area and a gentle lifting force applied against the outer ply. If separation of the outer ply can be made to extend to less than 1/16 inch from the product edge of the seal with no discernible resistance to the gentle lifting, it shall be considered evidence of delamination.

5/ The effective closure seal is defined as any uncontaminated, fusion bonded, continuous path, minimum 1/8 inch wide from side seal to side seal that produces a hermetically sealed pouch.

6/ Applicable to unit packed pouches only.

4.5.4 Pouch vacuum examination. Not less than 96 hours after filling and sealing, the pouches shall be visually examined for conformance to the vacuum requirements in 5.1.1.1.2 and 5.1.1.2.2. The sealed pouch shall continue to exhibit tight adherence to the surface contours of the contents when a pulling force is applied at the center of each side seal. This force shall be applied by holding each side seal between thumb and forefinger of each hand, simultaneously exerting a slight pull with both hands. Any evidence of loss of vacuum shall be classified as a major defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

4.5.5 Net-weight examination of product when unit packed in pouches as specified in 5.1.1.1. The net weight of the filled and sealed pouches shall be determined by weighing each sample unit on a suitable scale tared with a representative empty pouch. Any individual net weight of less than 36 grams or greater than 44 grams shall be classified as a minor defect. The lot size shall be expressed in pouches. The results shall be reported to the nearest gram. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.5.6 Product examination when unit packed as specified in 5.1.1.1. The finished product shall be examined for the defects listed in table II. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects (unit packs) 1/ 2/

Category		Defect
Major	Minor	
101		Presence of forming streaks or stains
102		Dimensions of bars not as specified
103		Color of bars not as specified
104		Shape of bars is distorted, (concave, convex or cupped) or not as specified
	201	Broken or crumbled bar (more than three pieces) 3/

1/ The presence of any foreign material (for example, glass, dirt, insects, insect parts, hair, wood, metal), foreign odor or flavor (for example, burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by a USDA agent).

3/ A broken or crumbled bar is a bar which either:

a. has been broken into more than three pieces, the smallest of which is larger than 1/2 cubic inch in volume; or

b. has more than 1/8th of the volume of the bar crushed.

4.5.7 Product testing when unit packs are held over 30 days (see 5.1.1.1). When unit packed bars are held over 30 days before final assembly, the storage container shall be tested for conformance to the oxygen content or vacuum requirements of 5.1.1.1. Testing shall be as specified in 4.5.7.1 or 4.5.7.2. The lot size shall be expressed in number of storage containers. The sample unit shall be one sealed container. The inspection level shall be S-2. Any storage container failing to meet the oxygen content or vacuum requirements shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

4.5.7.1 Oxygen content testing. The analysis to determine the percentage of oxygen in the nitrogen atmosphere shall be in accordance with any accepted USDA method, using appropriate methods to adapt to the bulk container in which the bars are stored.

4.5.7.2 Vacuum testing. The vacuum level shall be determined by testing in accordance with any accepted USDA method, using appropriate methods to adapt to the bulk container in which the bars are stored.

4.5.8 Examination for weight of product when bulk packed in pouches as specified in 5.1.1.2. The weight of the bread crisp bars shall be determined by individually weighing two bars randomly selected from each sample unit. Any individual bar weight of less than 36 grams or greater than 44 grams shall be classified as a minor defect. The lot size shall be expressed in bulk packed pouches. The results shall be reported to the nearest gram. The sample unit shall be one bulk packed pouch. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.5.9 Product examination when bulk packed as specified in 5.1.1.2. The finished product shall be examined for defects listed in table III. The lot size shall be expressed in bulk packed pouches. The sample unit shall be two bars selected at random from the bulk packed pouch. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for minor defects.

TABLE III. Products defects (bulk pack) 1/ 2/

Category		Defect
Major	Minor	
101		Presence of forming streaks or stains
102		Dimensions of bars not as specified
103		Color of bars not as specified
104		Shape of bars is distorted (concave, convex or cupped) or not as specified
105		Number of bars not as specified 3/
	201	Broken or crumbled bar (more than three pieces) 4/

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

1/ The presence of any foreign material (for example, dirt, insects, insect parts, paper, hair, wood, metal), foreign odor or flavor (for example, burnt, scorched, moldy, rancid, sour, stale), foreign color, shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by a USDA agent.)

3/ The sample unit shall be the selected bulk packed pouch.

4/ A broken or crumbled bar is a bar which either:

a. has been broken into more than three pieces, the smallest of which is larger than 1/2 cubic inch in volume, or

b. has more than 1/8th of the volume of the bar crushed.

4.5.10 Pouch closure seal strength testing. The filled and sealed pouches shall be tested for closure seal strength in accordance with ASTM F 88, except that the testing speed shall be 10 or 12 inches per minute. Machines that apply the tensile load to the test specimen by movement of the upper or lower clamp may be used. Test specimens shall be cut 1/2 inch in width and to a length suitable for proper mounting. Three adjacent specimens shall be cut from the closure seal of each pouch in the sample. The average seal strength of the closure seal shall be calculated by averaging the test results of the three test specimens cut from the seal. The results shall be reported to the nearest 0.1 pound per inch of width. Any test specimen or average seal strength failing to meet the requirements of 5.1.1.1.2 or 5.1.1.2.2 shall be classified as a major defect and shall be cause for rejection of the lot. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-1.

4.5.11 Moisture content testing. The finished product shall be tested for moisture content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Cereal Foods: Section: Total Solids (Moisture, Indirect Method): Method: Vacuum Oven except that the drying cycle shall be 16 hours at 70°C under a pressure of not more than 100 mm Hg. The test results shall be reported to the nearest 0.1 percent. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed unit packed pouch or two bars selected at random from bulk packed pouches. The inspection level shall be S-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

4.5.12 Microbiological testing. Five filled and sealed unit packed pouches or two bars selected from each of five filled and sealed bulk packed pouches shall be selected at random from the lot regardless of lot size. The pouches or two bar units shall be individually tested for microbiological levels in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Microbiological Methods; Section: Frozen, Chilled, Precooked, or Prepared Foods - Official First Action. The diluent shall be added to each bar and allowed to stand for 15 minutes before blending the sample. Continue with the procedure as directed in the Official First Action. Any result not conforming to the microbiological requirements in 3.6j and 3.6k shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.13 Mineral content testing. The finished product shall be prepared and tested for mineral content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Cereal Foods Section using appropriate methods to remove interferences from coatings or carriers. The test results shall be reported to the nearest 0.1 gram. Any test failure shall be classified as a major defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed unit packed pouch or two bars selected at random from bulk packed pouches. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.5.14 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major:	National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible. Cushioning material missing or not as specified.
Minor:	Other required markings missing, incorrect, or illegible. Number of bars not as specified. Pouches not packed flat in layers.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A. The product shall be unit packed in accordance with 5.1.1.1 or bulk packed in accordance with 5.1.1.2.

5.1.1.1 Unit packs. When specified (see 6.1), one bread crisp bar shall be unit packed in a preformed pouch as specified in 5.1.1.1.1. The unit packed bars shall be stored in a closed container. If bars are held for more than 30 days from date of pack to ration assembly, they shall be protected from oxygen by either holding under a nitrogen atmosphere with 2.0 percent or less

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

oxygen or holding under a vacuum of at least 27 inches of mercury during the period exceeding 30 days. In no case shall the bars be held for more than 90 days from date of pack to ration assembly.

5.1.1.1.1 Preformed pouch for unit pack. The preformed pouch shall be fabricated from inside to outside 0.004 inch thick (± 0.001 inch) polyolefin film laminated to 0.0005 inch thick (± 0.0001 inch) polyester. The material shall be suitably formulated for food packaging and shall not impart an odor or flavor to the product being packed. The material shall show no evidence of delamination, degradation, or foreign odor when heat sealed or fabricated into pouches. The preformed pouch shall be a flat style pouch having inside dimensions of 3.0 inches wide by 4-7/8 inches long (± 1/16 inch), with the 3.0 inch dimension being the opening of the pouch. The pouch shall be made by heat sealing three edges with 1/4 inch (± 1/16 inch) wide seals. The heat seals shall be made in a manner that will ensure hermetic seals. The pouch shall maintain its integrity and air tightness of the side and bottom seals when tested as specified in 4.5.1.3.2. The side and bottom seals shall have an average seal strength of not less than 10 pounds per inch and no individual specimen shall have a seal strength of less than 9 pounds per inch when tested as specified in 4.5.1.3.1. A tear notch at least 1/32 inch deep, located 1 to 1-1/4 inches from the top edge of the pouch, shall be made in one or both side seals. The distance between the inside edge of the tear notch and the inside edge of the seal shall be at least 3/16 inch. One side of the open end of the pouch shall be provided with an extended lip, extending 1/8 inch (± 1/16 inch) to facilitate opening and filling. Tear notch location shall be measured from the top of the pouch, excluding the extended lip.

5.1.1.1.2 Filling and sealing of unit pack pouches. One bar shall be placed into a preformed pouch as specified in 5.1.1.1.1. The filled pouch shall then be hermetically sealed, by evacuating the air within a sealing chamber under a vacuum of not less than 25 inches of mercury, and applying a continuous heat seal of not less than 1/8 inch wide. The closure seal shall be free of foldover wrinkles, delamination, occluded matter, and entrapped moisture or grease. The closure seal shall be located no less than 1/8 inch above tear notch. The average closure seal strength shall be not less than 10 pounds per inch and no individual test specimen shall be less than 9 pounds per inch when tested as specified in 4.5.10. The filled and sealed pouch shall show no loss of vacuum when examined as specified in 4.5.4.

5.1.1.2 Bulk pack. When specified (see 6.1), fifteen bread crisp bars of one type shall be bulk packed in a pouch as specified in 5.1.1.2.1. The bulk packed bars shall be held for not more than 180 days from date of pack to ration assembly.

5.1.1.2.1 Preformed pouch for bulk pack. The preformed pouch shall be fabricated from a hot fill type, minimum 0.006 inch thick, 3-ply laminate from inside to outside, of polyolefin/aluminum foil/polyester material. The material shall be suitably formulated for food packaging and shall not impart an odor or flavor to the product being packed. The material shall show no evidence of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

delamination, degradation, or foreign odor when heat sealed or fabricated into pouches. The preformed pouch shall be a flat style pouch having outside dimensions of 12 inches wide by 15 inches long (± 1/8 inch), with the 12 inch dimension being the opening of the pouch. The pouch shall be made by heat sealing three edges with 3/8 inch (± 1/8 inch) wide seals. The heat seals shall be made in a manner that will ensure hermetic seals. The pouch shall maintain its integrity and air tightness of the side and bottom seals when tested as specified in 4.5.1.3.2. The side and bottom seals shall have an average seal strength of not less than 10 pounds per inch and no individual specimen shall have a seal strength of less than 9 pounds per inch when tested as specified in 4.5.1.3.1.

5.1.1.2.2 Filling and sealing of bulk pack pouches. Fifteen bread crisp bars of one type shall be single tier packed into the bulk pack pouch. The filled pouch shall then be hermetically sealed, by evacuating the air within a sealing chamber under a vacuum of not less than 25 inches of mercury, and applying a continuous heat seal of not less then 1/8 inch wide. The closure seal shall be free of foldover wrinkles, delamination, occluded matter, and entrapped moisture or grease. The average closure seal strength shall be not less than 10 pounds per inch and no individual test specimen shall be less than 9 pounds per inch when tested as specified in 4.5.10. The filled and sealed pouch shall show no loss of vacuum when examined as specified in 4.5.4.

5.2 Packing for shipment to ration assembler. Two hundred and forty bread crisp bars, preserved as specified in 5.1, shall be packed flat in layers in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF, variety SW, grade 275, class domestic of PPP-B-636. Cushioning material not less than 1/8 inch thick, conforming to type II, class B of PPP-C-843 or cushioning material not less than 1/16 inch thick conforming to type I of PPP-C-1797 or cushioning material conforming to type VII, class 1 of PPP-C-1752 shall be placed between each of the layers and at the bottom and top of the box to minimize movement of the individual packs.

5.3 Labeling and marking.

5.3.1 Unit pack pouches. Unit pack pouches shall be labeled in a permanent, contrasting color directly on the packaging material in a manner that does not damage the pouches, with a food compatible ink which is free of carcinogenic elements or ingredients. No marking shall be closer than 1/16 inch to any seal. Pressure-sensitive labels may be used instead of marking directly on the packaging material. Labels shall be of a water resistant grade of paper or film, flat-back, coated on one side with pressure-sensitive adhesive. The texture of the material shall permit flexibility. Labels shall be suitable for printing or writing on with ink without feathering or spreading. The adhesive shall be of a pressure-sensitive permanent type. The adhesive shall be water insoluble, homogenous, and shall be coated in a smooth layer on one side of the label. The adhesive shall require no solvent, heat, or other preparation prior to application. Adhesive shall be of a type that will adhere to the pouch surface under high or low temperatures. Dimensions of the label shall not be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

larger than the dimensions of the surface of the product where the label is applied on the package. Ink and adhesive used must be suitable for use with food products and shall be free of carcinogenic elements or ingredients. Letter size shall be not less than 1/16 inch high. The following information must be included:

Item Name
Date of production/Lot number (Julian date) 1/
Name of contractor

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1987 would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code.

5.3.1.1 Each unit pack shall contain item name (one of the below listed item names) as applicable:

CHEESE BREAD CRISP	ORANGE-NUT BREAD CRISP
CHEESE-BACON BREAD CRISP	PIZZA BREAD CRISP
COCONUT BREAD CRISP	TAMALE BREAD CRISP

5.3.2 Bulk pack pouches. Bulk pack pouches shall be marked as specified in 5.3.1 except that the labels shall include the following information:

Number of bars
Contract number
Name, address, and zip code of contractor

5.3.3 Marking of shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Type (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.4, and 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

e. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
f. Whether unit pack or bulk pack is required (see 5.1.1.1 and 5.1.1.2).

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.4 Technical information.

6.4.1 Bits, formulated, cheddar cheese based or wheat-germ formulated, bacon or orange flavored. Satisfactory products have been produced by using these components produced by Anacon Foods Co., Roseville, MN. Other products may provide equivalent results.

6.4.2 Mineral pre-mix. Encapsulated ferrous sulfate 60 percent No. 83008, zinc sulfate 60 percent No. 83034, cupric sulfate 50 percent, No. 83027 and magnesium oxide, heavy granulated No. 63023 from Desmo Chemical Company, St. Louis, MO have worked satisfactorily in preparing mineral pre-mixes. Minerals from other suppliers may provide equivalent results. A combined encapsulated iron, zinc, and cupric sulfate may be substituted for the individual sulfate components provided that there is at least a 40 percent edible coating of mono and diglycerides.

6.4.3 Pectin, extra slow set. Mexpectin XSS100 produced by Grinstead Products, Inc., Industrial Airport, Kansas, has worked satisfactorily. Other slow-set pectins may perform as well.

6.4.4 Nuts, formulated, wheat-based. Satisfactory products have been produced by using wheat germ based nuts produced by Anacon Foods Co., Roseville, MN. Other flavor nuts may provide equivalent results.

6.5 Subject term (key word) listing.

Bar, dehydrated
Operational ration

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

Custodian:

Army - GL

Review Activities:

Army - MD, QM
Navy - MC, SA
Air Force - 50
DP - SS

Preparing activity:

Army - GL

(Project 8920-A528)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-44388(GL)	Bread Crisp Bars, Ration Lightweight, 30-Day

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T01:53Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:53Z
Check the source to verify that this is the current version before use.