INCH-POUND

MIL-C-44383
7 November 1989

MILITARY SPECIFICATION

CRADLE, MILITARY FUEL CAN, FIVE GALLON / TWENTY LITER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a cradle for a 5-gallon/20-liter fuel can (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

UU-T-81	-	Tags, Shipping And Stock
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-35078 - Loads Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, And Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes
MIL-STD-129 - Marking For Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members For Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-5868 - Stand, Assembly, Fuel Can
5-4-6931 - Tag, Stand Assembly, Fuel Can

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS Natick, MA 01760-5014.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:52Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 580 - Anodic Oxide Coatings On Aluminum
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. The materials and components used shall conform to the applicable referenced specifications, standards, and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice provided the completed items comply with all provisions of this specification. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Design and construction. The design and construction of the cradle shall be as specified herein, and as shown on Drawing 5-4-5868 and all subsidiary drawings and parts lists.

3.3.1 Stitches and stitching. All stitches and stitching shall conform to FED-STD-751. The number of stitches per inch shall be as specified on the referenced drawings. Allowances shall be maintained with stitching so that no run-offs, twists, pleats, puckers or open seams occur.

3.3.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2-inch minimum except when caught in other stitching. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of the materials sewn.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When the thread breaks or the bobbin runs out during sewing, the stitching shall be repaired by starting the stitching a minimum of 1-inch back of the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item shall be repaired by overstitching. The stitching shall start a minimum of 1-inch in back of the defective area (1/2-inch on box, box-x, and W-W stitching) and continue a minimum of 1-inch beyond the defective area on to the existing stitching. Reinforcements shall be overstitched not less than 1/4-inch. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner. When damaged thread has been removed, needle holes do not constitute damage to the material. 1/

1/ When making the above repairs, the ends of the stitching are not required to be back stitched.

3.3.1.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met, and at least three or more tying, overlapping, or backstitches are used to secure the ends of the stitching.

3.3.1.3 Thread ends. Thread ends that are visible on the finished item shall be trimmed to a length of not more than 1/4-inch.

3.4 Instruction tag. The instruction tag shall conform to size No. 8, type A, grade 2 or 3 of UU-T-81. Color of the tag shall be either white or yellow. Stringing shall be galvanized wire. The instruction tag shall be securely wired to the leg mount. The instructions and illustrations shown on Drawing 5-4-6931 shall be reproduced legibly, and neatly on each instruction tag. The reproduction shall be as large as practicable, keeping the border around the tag to a minimum.

3.5 Anodizing. The cradle shall be anodized per ASTM B 580, type C after a thorough cleaning, but before final assembly.

3.6 Workmanship. The cradle shall be free from fractures, splits, punctures, tears, dents, creases, deteriorations or malformations. There shall be no sharp edges, burrs, or slivers. The finish shall be free from chipped areas or areas of no anodization. Threaded fasteners shall not be broken, stripped, fractured or loose. The surface of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be sound, continuous, smooth and free of porosity, cracks, incomplete fusion and deformation of material. All scale and flux deposit shall be removed from the finished welds. The cradle shall conform to the quality of product established by this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3 and tested as specified in 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:52Z
Check the source to verify that this is the current version before use.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of 5-gallon/20-liter fuel can cradles. The sample unit shall be one 5-gallon/20-liter fuel can cradle. The inspection level shall be II (see 6.4).

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Design, construction and workmanship	Any component or part missing or not of specified type or size	101	
	Fractured, split, punctured, torn, dented, creased, deteriorated or malformed	102	
	Component loose		201
	Sharp burr, edge or sliver		202
	Rivet broken, loose or not attached	103	
	Strap frayed, torn or loose stitching	104	
	Over tightening of locknuts, preventing movement of braces and legs		203
Finish (on entire unit except straps and fasteners)	Any component not anodized	105	
	Anodic film not continuous	106	
	Scratches, breaks, or abrasions		204
Stitching:			
Open Seams	One half inch or less		205
	More than 1/2-inch	107	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur.		
Runoffs	(See "Open Seams")		
Stitch type	Stitch type not as specified	108	
Stitch tension	Loose, resulting in loose bobbin or top thread		206
	Excessively tight, resulting in puckering of material or cutting of material between needle holes		207

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Stitches per inch	One stitch less than minimum specified		208
	Two or more stitches less than minimum specified	109	
	One or more stitches in excess of maximum specified		209
Stitching ends	Ends of stitching not secured as specified (except when caught in stitching		210
Thread breaks, skipped stitches or runoffs	Overstitched less than 1/2-inch in each direction beyond the defective stitching area		211
NOTE:	Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Rows of stitching	Any row omitted	110	
Instruction Tag	Missing, incomplete, illegible	111	
Welding	Missing, incomplete fusion, burn holes, cracked, fractured, not fused, burrs, scale or flux deposits not remove	112	

4.4.3 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of 5-gallon/20-liter cradles. The sample unit shall be one 5-gallon/20-liter cradle. The inspection level shall be S-2 (see 6.4).

4.4.4 End item testing. The end items shall be assembled in accordance with the instruction tag (see 3.4). The inspection level shall be S-1 (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:52Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 (see 6.4).

Examine	Defect
Markings, (exterior and interior)	Omitted, incorrect, incomplete, illegible; of improper size, location, sequence or method of application
Material	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Other than specified

4.4.6 Palletization examination . The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 (see 6.4).

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A preservation. Each cradle shall be folded to its smallest dimensions and secured with the hold down straps.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:52Z
Check the source to verify that this is the currentversion before use.

5.1.2 Commercial preservation. The cradle shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing. Each cradle, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. Either end-loading or top-loading boxes are acceptable. The inside of each box shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Inside dimensions of each shipping container shall approximate 47 inches in length, 3-1/2 inches in width, and 3-1/2 inches in depth. Each shipping container shall be closed, waterproofed, and reinforced, with strapping or tape banding in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Each cradle, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Either end-loading or top-loading boxes are acceptable. The inside of each box shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade 275 of PPP-B-636. Inside dimensions of each shipping container shall approximate 47 inches in length, 3-1/2 inches in width, and 3-1/2 inches in depth. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing. Cradles preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), cradles, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or bonding means F or G. Pallet pattern shall be number 123 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cradle is intended for holding a 5-gallon/20-liter fuel can. The cradle's primary use shall be with the following heaters:

MIL-H-12340 - Heater, Space (Yukon, M-1950, with Accessories)
MIL-H-13514 - Heaters, Space, Radiant Type, Portable 45,000 Btu/Hr

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).
h. Acceptance criteria required (see 6.4).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Acceptance criteria. The acceptance criteria below is recommended for use. The acceptance criteria as specified in the contract or purchase order shall be binding. Unless otherwise specified, the following acceptance criteria are in accordance with MIL-STD-105.

6.4.1 For end item visual examination. An acceptable quality level (AQL), expressed in terms of defects per hundred units, of 2.5 for major defects and 6.5 for total (major and minor combined) defects is recommended.

6.4.2 For end item dimensional examination. An AQL, expressed in terms of defects per hundred units, of 4.0 is recommended.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:52Z
Check the source to verify that this is the current version before use.

6.4.3 For end item testing. An AQL, expressed in terms of defects per hundred units, of 1.0 is recommended.

6.4.4 For packaging examination. An AQL, expressed in terms of defects per hundred units, of 2.5 is recommended.

6.4.5 For palletization examination. An AQL, expressed in terms of defects per hundred units, of 6.5 is recommended.

6.5 Subject term (key word) listing.

Framework
Holder
Stand
Support
Tripod

Custodians:
Army - GL
Navy - YD
Air Force - 99

Review activities:
Army - MD, ME
Navy - MS
Air Force - 84
DLA-CS

User activity:
Navy - MC

Preparing activity:
Army - GL

(Project 7240-0249)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-44383	CRADLE, MILITARY FUEL CAN, FIVE GALLON / TWENTY LITER

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* — Optional

b. WORK TELEPHONE NUMBER *(Include Area Code)* — Optional

c. MAILING ADDRESS *(Street, City, State, ZIP Code)* — Optional

8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 202610-22T0[illegible]:52Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil - Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.