INCH-POUND

MIL-DTL-44400A
7 April, 2000

SUPERSEDING
MIL-T-44400(GL)
11 April, 1990

DETAILED SPECIFICATION

TENT, FABRIC ASSEMBLIES, STANDARDIZED INTEGRATED COMMAND POST SYSTEM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the fabric components of a frame-supported tent equipped, which can stand-alone or be complexed with other tents or vehicles.

1.2 Classification. (see 6.2)

Class I - Camouflage Green 483
Class II - Desert Tan 459

2. APPLICABLE DOCUMENTS

*2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions, clarifications) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center Philadelphia, Clothing and Textiles Directorate, Attn: DSCP-CNR, 700 Robbins Ave., Philadelphia, PA 19111-5096 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

*2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

DDD-L-20 - Label; For Clothing, Equipage and Tentage (General Use)

STANDARDS

FEDERAL

FED-STD-601 - Rubber: Sampling and Testing

(Unless otherwise indicated. copies of federal and military specifications, standards, and handbooks are available from the Defense Automated Printing Service, Bldg. 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

*2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF THE ARMY FIELD MANUAL

FM 10-16 – General Repair of Tents, Canvas and Webbing

(Applications for copies should be addressed to the Superintendent of Documents, US Government printing office, Washington, DC 20402)

DRAWINGS

U.S. ARMY BIOLOGICAL AND CHEMICAL COMMAND

5-4-6341 - Fabric Assemblies Overview
5-4-7676 - Instruction Label, Five Soldier Crew Tent
5-4-7678 - FSCT Pegs, Bag & Contents

(Copies of drawings are available from the U. S. Army Biological Chemical Command, ATTN: AMSSB-REO-S(N), NATICK, MA 01760-5017.)

*2.3 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-6193 - Standard Practice for Stitches and Seams

(Applications for copies of referenced documents should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19426-2959.)

*2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

*3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.2 and 6.2).

3.2 Materials and components. The materials and components used shall conform to the applicable referenced specifications, standards and requirements specified herein. Where materials are not definitely specified, they shall be of the quality normally used by the manufacturer in his standard commercial practice provided the completed items comply with all provisions of this specification.

3.2.1 Alternate components. Components offered as equivalent to components specified hereinafter and on the referenced drawings as s specific manufacturer's part or model number or equal, shall be functionally equal to the manufacturer's model number identified and of equal or better quality. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component and shall not reduce ease of maintenance to it or any other components unless such modification or change is approved by the contracting officer. Prior to the manufacture of the first article, or if none is required, prior to commencing production the contractor shall submit for the contracting officer's approval, a list identifying each component, together with proof that each listed component complies with the requirements of this document. The contracting officer may require a sample of the proposed substitution. Approval of the submitted listing, together with the necessary supporting data, authorizes commencement of manufacture but does not relieve the contractor of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

*3.3 Design and construction. The design and construction of the class 1 tent shall conform to Drawing 5-4-6341-1 and all subsidiary drawings and parts lists and as specified herein. The design and construction of the class 2 tent shall conform to Drawing 5-4-6341-2 and all subsidiary drawings and parts lists and as specified herein.

3.3.1 Fusing of ends of synthetic cord, webbing and tape. All ends of synthetic cord, webbing and tape shall be fused. The apparatus used to fuse the cord, webbing and tape ends shall be capable of providing sufficient heat to provide a smooth edge with the cut ends of the cord, webbing and tape yarns all fused together. Fusing of the cord, webbing and tape shall be accomplished prior to being assembled for stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

3.3.2 Stitching, machine.

*3.3.2.1 Types. All stitch types, except bartacking, shall conform to ASTM-D-6193 as follows:

a. For all stitching except zig-zag stitching and stitching indicated by "Z" on drawings – type 301, 5 to 7 stitches per inch.

b. For zig-zag stitching - type 304, 12 to 16 stitches per inch.

c. For stitching indicated by "Z" on drawings fasteners – type 401, 5 to 7 stitches per inch.

d. Bartacking. Bartack length shall be as specified on drawings, 1/8 inch in width (bight) and shall be free of thread breaks and loose stitching.

3.3.2.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch at each break on stitch type 301, not less than ¾ inch at each break on stitch type 304 and not less than 1 ½ inches at each break on stitch type 401. Thread breaks in type 401 stitching may be overstitched with stitch type 301. Thread breaks noted during inspection shall be repaired by overstitching the existing stitching starting from a distance of 1 inch beyond the break, across the defective area, to a distance of 1 inch beyond the break. The ends of repair stitching are not required to be backstitched.

3.3.2.3 Stitching ends. The ends of 301 stitching shall be overstitched not less than 1 inch except where ends are turned under in a hem or held down by other stitching. Where 301 stitching is performed automatically on stitch patterns such as box, box with cross-stitch, "W" stitching or straight line tacking, not less than three tying, overlapping , or back stitches shall be used to secure the ends of stitching. The ends of type 304 stitching shall be firmly secured by backstitching or overstitching or by increasing the number of stitches per inch at the ends for a minimum of ¼ inch.

3.3.2.4 Skipped stitches. Two or more consecutively skipped stitches occurring in type 301 or 304 stitching shall be overstitched not less than 1 inch. Any skipped stitches in type 401 stitching shall be overstitched not less than 1 ½ inches. Skipped stitches in 401 stitching may be overstitched with type 301 stitching. Skipped stitches noted during inspection shall be repaired as specified for thread breaks (see 3.3.2.2).

3.3.2.5 Thread lubricant. The addition of any lubricant to the polyester sewing thread prior to or during the sewing operation is prohibited.

3.3.2.6 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch and size and type of thread are met and at least three or more tying, overlapping or back stitches are used to secure the ends of stitching.

3.3.2.7 Thread ends. All thread ends shall be trimmed to a length of not more than ¼ inch.

3.3.2.8 Stitching margins. Unless otherwise specified, all stitch margins shall be 1/8, + 1/16 – 0 inch.

3.3.3 Splicing of cloth. There shall be no splicing of roof, wall, liner or floor panels. The number of panel seams shall not exceed requirements specified on the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

3.3.4 Setting of grommets. Holes punched to receive grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. Grommets shall be securely clinched without cutting the materials. Roll of the clinched grommet shall not contain more than three scores (splits).

3.3.5 Wicking of sewing thread. There shall be no wicking of water through the stitching on the wall assemblies when the tent is tested as specified in 4.4.1. The cup test is intended to insure that non-wicking thread has been utilized and that no lubrication has been added to the thread prior to or during the sewing operation. Repairs required as a result of failure of the cup test and when authorized by the contracting officer shall be performed by treating exposed stitching on the wall assembly with seam sealant specified in 3.3.6.

*3.3.6 Leakage of sealed seams. All exposed stitching on the exterior of the roof cap assemblies and rain gutter shall be treated with Kenyon Consumer Products K-Kote seam sealer-J (clear) #83-234C or equal (see 6.5 and 6.7). The requirements for infrared reflection shall not apply. The fabric surface shall be cleaned so that it is free of dirt and moisture prior to application of seam sealant. Sealant shall be applied with a brush or roller and shall evenly cover an area ½ inch wide on each side and on top of all stitching. There shall be no leakage of water through seams when the tent is tested as specified in 4.4.2.

3.3.7 Seam strength. The strength of the seams shall be 80% of the fabric strength when tested as specified in 4.4.3.

3.3.8 Repairs to liner assembly fabric. All necessary repairs shall be effected in accordance with the Department of The Army Field Manual FM 10-16 except that hand sewn patches, other than specified herein, will not be acceptable. Patches on holes, cuts or tears not more than 1 inch in diameter or length shall be permitted. A maximum of one patch per liner assembly shall be allowed without prior authorization from the contracting officer. Each patch shall be large enough to overlap the damaged area with a margin of at least ¾ inch on all sides. Patches shall be placed on the outside of the liner assemblies and shall not be permitted over the seams or in hardware areas. All other repairs shall require authorization by the contracting officer.

3.3.9 Repairs to the roof cap, walls, rain gutter and transport covers. No more than one repair to holes, cuts, tears or burn throughs resulting from the heat sealing operation shall be allowed. Repairs on holes, cuts, tears or bur throughs not more than one inch in diameter or length shall be performed as follows:

a. Repairs shall be accomplished by the application of cemented patches. Cemented patches shall be large enough to overlap the damaged area with a margin of at least ¾ inch on all sides, using cement per Minnesota Mining and Manufacturing 847 or equal (see 6.6 & 6.7).

b. For repairs of burn-throughs on panel lap seams, the width of the patch shall be such that the overlap on each side of the burn-through shall be equal to the width of the seam.

c. Patches shall be applied to the top side of the assemblies and the patched area shall be smooth, i.e., with the torn or cut edge securely and completely sealed and corners shall have a radius.

3.4 Marking. All markings and labels shall conform to DDD-L-20.

3.4.1 Special markings. The letters "US" and the item nomenclature on the roof cap assemblies and transport covers shall conform to type IV, class 9 of DDD-L-20, in the size

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

characters and in the locations shown on the drawings. Class 9 markings shall be clearly legible after subjection to accelerated weathering.

3.4.2 Identification label. Identification labels shall conform to type IV, class 6 of DDD-L-20 and shall be 3 ½ inches by 5 ½ inches minimum and a blank space of at least 1 ¼ inches shall be provided on the bottom of the label for the Department of Defense inspector's stamp. Identification labels shall be stitched to the tent components in the locations shown on the drawings.

*3.5 Color. The color of the class I and class II tents shall be as specified in 1.2. The webbings, tapes, slide fastener tapes, fastener tapes, pulls and thread shall be a good approximation to Camouflage Green 483 for the class I tents and Desert Tan 459 for the class II tents.

3.6 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched material.

3.7 Workmanship. Cloth components shall be clean and free of holes, cuts, tears, or cloth defects such as multiple floats, broken or missing yarns, or areas untreated with compound. Webbing and tapes shall not have frayed or scalloped edges and rope components shall be free of cuts or breaks Where there is sewing, thread tension shall be maintained with seams properly sewed so that no runoffs, twists, pleats or open seams shall result. Care shall be taken in sewing to see that no needle chews occur. All thread ends shall be trimmed to ½ inch or less. Metal components shall be free of burrs, sharp edges and corroded areas and shall not be broken or malformed. Heat sealed seams shall be free of wrinkles, pleats and folds. A heat sealed seam, regardless of its length, shall not have more than a total of two wrinkles, pleats or folds.

*3.8 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

4. VERIFICATION

4.1 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all dimensions specified in the component specifications have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. When a first article is required (see 6.2) it shall be examined for the defects listed in 4.3.3 and 4.3.4 and tested as specified in 4.3.5. Any nonconformance or failure of any test shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

4.3 Conformance inspection. Sampling for inspection shall be as specified in the contract or purchase order.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

*4.3.2 In-process inspection. Inspection shall be made of the following fabrication operations to establish conformance with specified requirements. The government reserves the right to exclude from consideration for acceptance , any material or service for which in-process inspection shall has indicated nonconformance.

a. There shall be no lubrication of polyester thread prior to or during sewing operations for compliance with 3.3.2.5.

b. Holes punched to receive grommets are in compliance with 3.3.4.

c. Heat sealing operations shall be monitored. A sample seam specimen of sufficient size to conduct testing in accordance with 3.3.7 shall be produced each time the heat sealing equipment is started and every 300 linear feet of sealed seam thereafter.

Whenever nonconformance is noted, correction shall be made to the items affected and the process. When correction cannot be made the item affected shall be removed from the process.

*4.3.3 End item visual examination. The end item units of roof cap, walls, rain gutters, floor assemblies, liners, transport covers and pin container shall be examined for the defects listed in Table I. The lot size shall be expressed in units of end items. The sample unit shall be one end item. The inspection level shall be II.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Screening	Cut or tear:			
	- ¼ inch or less in length			301
	- More than ¼ inch in length but not more than 2 inches in length		201	
	- More than 2 inches in length	101		
Webbing and tape	Any cut, tear or hole			302
	Edge frayed or scalloped, not firmly or tightly woven			303
Cloth for Roof, wall & Gutter	Cut, tear or hole (including exposed drill holes) greater than 1/8 inch in length or diameter:			
	- On roof, wall or gutter assemblies	102		
	Cut, tear or hole (including exposed drill holes) 1/8 inch or less in length or diameter:			
	More than four:			
	- On roof or gutter assemblies	103		
	More than five but less than ten			
	- On wall assemblies		202	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
	More than ten - On wall assemblies	104		
Cloth for liner	Cut, tear or hole (including exposed drill holes) greater than 1/8 inch in length or diameter:		203	
	Cut, tear or hole (including exposed drill holes) Less than 1/8 inch in length or diameter:			
	- More than ten		204	
	- More than five but less than ten			304
Cloth for transport covers or tent pin container	Cut, tear or hole (including exposed drill holes) greater than 1/8 inch in length or diameter		205	
	Cut, tear or hole (including exposed drill holes) less than 1/8 inch in length or diameter			
	- More than ten		206	
	- More than five but less than ten			305
Cloth for floor	Cut, tear or hole (including exposed drill holes) greater than 1/8 inch in length or diameter	105		
	Cut, tear or hole (including exposed drill holes) less than 1/8 inch in length or diameter:			
	- More than ten	106		
	- More than five but less than ten		207	
Hardware & metal components	Broken	107		
	Malformed:			
	- fails to perform intended function	108		
	- but will perform intended function		208	
	Corroded area			306
	Burr or sharp edge that may cause injury in handling or damage to fabric	109		
	Not specified type or size		209	
Grommets	Improperly set, two or more teeth exposed (except where a grommet is set as specified but is in an area of uneven thickness which prevents uniform clinching)			307
	Clinched loosely, allowing grommet to rotate around hole			308
	Clinched excessively tight (i.e., cutting cloth)	110		
	Insecurely clinched (i.e., grommets or washers become disengaged)	111		
	Grommet set with barrel inserted from top of webbing instead of bottom			309
	Roll of a grommet contains more than three scores (splits)			310

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Rope components tent lines & cord components	Any cut or break: - On eve guy line		210	
	Eye splice omitted		211	
	Eye splice not as specified			311
	Free ends not finished as specified			312
Seams & stitching	Open seams on stitch type 301; - more than ¼ inch but not more than 1 inch			313
	- more than 1 inch		212	
	Burn through	112		
	Note: A seam shall be classified as open when one or more stitches joining a seam are broken, or when one or more skipped or run-off stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.			
	Raw edges caught in stitching: - more than 1 inch but not more than 3 inches			314
	- more than 3 inches		213	
	Note: Raw edge not securely caught in stitching shall be classified as an open seam			
	Thread breaks: - overstitched less than 1 ½ inches on stitch type 401			315
	- overstitched less than 1 inch on stitch type 301			316
	Note: Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as an open seam			
	Needle chews resulting in cut, tear or hole (see cut, tear or hole)			
	Skipped stitches: - Overstitched less than 1 ½ inches on stitch type 401		214	
	- Overstitched less than 1 inch on stitch type 301 (when 2 or more skipped stitches occur consecutively)		215	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
	NOTE: Skipped stitches not overstitched shall be classified as open seams			
	One or more required rows of stitching omitted (except on boxstitching)	113		
Heat sealed seams	Pleated, puckered, burned through, wrinkled or folded	114		
Boxstitching	Incomplete:			
	- one row of stitching omitted			317
	- two or more rows of stitching omitted		216	
	More or less than specified length by more than 1/8 inch			318
Bartacking	One or more bartacks omitted	115		
	Any bartack not as specified or not in specified location			319
	Loose stitching incomplete or broken			320
	Less than specified length by more than 1/8 inch			321
	Width less than 1/8 inch		217	
Stitching ends	Overstitched less than 1 inch on stitch type 301 (except where ends are held down by other stitching or turned under in a hem or where stitching is performed automatically)		218	
	Secured with less than ¼ inch of back stitching, Overstitching, or an increased number of stitches per inch at the end of stitch type 304			322
Seams	Pleated:			
	- on all wall, liner or floor assemblies		219	
	- on transport covers			323
Seam type	Wrong seam type	116		
Stitch type	Wrong stitch type	117		
Stitch tension	Loose, resulting in exposed bobbin or top thread for more than 6 inches		220	
	Tight, as evidenced by puckering on fabric for more than 6 inches		221	
Stitches per inch	Less than minimum specified (except on panel joining seams)			
	- one stitch			324
	- two or more stitches		222	
	Less than minimum specified on panel joining seams		223	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
	More than the maximum specified:			
	- one stitch			325
	- two or more stitches		224	
	Note: Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams or in turning corners shall be classified as follows:			
	a. Within the minor "B" defect classification no defect			
	b. Within the minor "A" defect classification minor "B" defect			
Stitching gage	Not as specified		225	
Stitching margin	Larger or smaller than specified (including tolerance):			
	- for more than 2 inches but not more than 4 inches in length			326
	- for more than 4 inches in length		226	
Mends, darns or patches	Repairs not in accordance with Department of The Army Field Manual FM 10-16 or not authorized by the contracting officer (see 3.3.8)	118		
Components & assembly	Any operation omitted or not performed in accordance with specification or drawing unless classified herein	119		
Reinforce-ments,	Improperly applied, causing excessive fullness on reinforcements or reinforced parts	120		
Marking & labels	Omitted, incorrect, illegible, or misplaced:			327
Cleanness	Grease or oil stains			
	Thread ends not trimmed to ½ inch or less			328

4.3.4 End item dimensional examination. The end item shall be examined for the defects listed in Table II. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. The lot size shall be expressed in units of tents. covers or frame carrying covers, as applicable. The sample unit shall be one end item. The inspection level shall be S-3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects

Examine	Defect	Classification Major	Minor A	Minor B
Overall dimensions of roof cap, window wall entranceway wall, plain wall liners, floors or rain gutters	Smaller than specified dimensions less applicable minus tolerances indicated on drawings	101		
	Larger than specified dimensions and applicable plus tolerance indicated on drawings			301
Overall dimensions of transport bag-frame, transport bag fabric tent pin container or support straps	Smaller than specified dimensions less applicable minus tolerances indicated on drawings but not smaller than specified dimensions less twice applicable minus tolerance			302
	Smaller than specified dimensions less twice the applicable minus tolerance indicated on drawing		201	
	Larger than specified dimensions and applicable plus tolerance indicated on drawing			303
Location Dimensions (unless otherwise specified)	Not within specified tolerance: - Not exceeding twice the applicable tolerance			304
	- Exceeding twice the applicable tolerance		202	
Webbing (tie-tapes)	Finished length less than specified by more than 1 inch			305
Grommets	Set beyond specified location by more than ½ inch		203	
Rope components, tent lines	Eye on footstop or line less than specified by more than ½ inch			306
	Finished length of guy line less than specified: - by not more than 4 inches			307
	- by more than 4 inches but non more than 12 inches		204	
	- by more than 12 inches	102		
Hems	Required to finish less than ¾ inch or less in width, less than specified		205	
Reinforcements	Finished dimensions less than specified by more than ½ inch		206	
Ventilator Opening	Misplaced by more than ½ inch		207	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

4.3.5 End item testing. Tents shall be tested as specified in 4.4. The lot size shall be expressed in units of end items. The sample unit shall be one tent. The inspection level shall be S-2. Any test failure shall be cause for rejection of the lot.

*4.3.6 Packaging examination. The fully packaged end items shall be examined for marking, materials, workmanship and content defects.

4.4 Methods of inspection.

4.4.1 Wicking of sewing thread (cup test). The end item unit shall be tested once on a wall assembly panel feld seam (see 3.3.5).

4.4.1.1 Procedure. Suspend the seamed section of the test fabric in the center of a 6 ± 1/8 inch diameter hoop and form a depression with the seamed fabric in the hoop to a depth of 1 ± ¼ inch. Slowly pour 500 ml of water at 77° ± 4°F into the cupped area (depression) and observe the under surface of the fabric for water penetration. Any wicking of water along the sewing thread, identified by a discoloration or darkening of the thread within 5 minutes after water is poured shall constitute a test failure. Water leakage through the needle holes or between the plies of the lapped seam fabric shall not be considered a failure.

4.4.2 Seam leakage test. The end item unit shall be tested on one roof cap assembly, one rain gutter assembly and one floor assembly for seam leakage on an area of stitching that has been treated with seam sealant (see 3.3.6). The end item unit shall be laid over a 6 1/8 inch diameter hoop and form a depression with the seamed fabric in the hoop to a depth of 1 ± ¼ inch with the seam to be tested running through the center of the depression. Slowly pour 500 ml of water at 77° ± 4°F into the cupped area (depression) and observe the under surface of the fabric for water penetration. Any wicking of water along the sewing thread, identified by a discoloration or darkening of the thread within 5 minutes after water is poured shall constitute a test failure. Water leakage through the needle holes or between the plies of the lapped seam fabric shall not be considered a failure.

4.4.3 Seam strength test. The end item unit seams shall be tested in accordance with Method 8311 of FED-STD-601. Any break in the seam that indicates the seam strength is less than 80% of the fabric strength shall be considered a test failure (see 3.3.7).

5. PACKAGING

*5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

*(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

*6.1 Intended use. The tent is intended for the standardized integrated command post system (SICPS). The class 1 tent is to be used in all theaters except the desert. The class 2 tent is to be used in the desert.

*6.2 Acquisition requirements. Acquisition documents must specify the following:
a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When first article is required (see 3.1, 4.2 and 6.4).
d. Levels of preservation and packing (see 5.1).
e. Class required (see 1.2).

6.3 Sample. For access to standard sample, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it will be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

*6.5 Seam sealer supply source. A source of supply for seam sealer used in 3.3.6 is Kenyon Consumer Products, P.O. Box 3715 1425 Kingstown Road, Peace Dale, Rhode Island 02883.

*6.6 Commercial adhesive. A source of supply for the commercial adhesive specified in 3.3.9 is the Minnesota Mining & Mfg. Co., 3M Center, St. Paul, Minnesota 55144.

*6.7 Equal item. Prior to the use of an “or equal” item, the supplier will submit the item, with supporting data to the contracting officer for subsequent approval or disapproval by the responsible military agency.

6.8 Subject term (key word) listing.
Liner
Shelter
SICPS

*6.9 Changes from previous issue. The margins of this document have been marked with an asterisk(*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - GL

Preparing activity
DLA-CT

Review activities:
Army – MD

Project No: 8340-0583

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7 and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-44400A	**2. DOCUMENT DATE** ***(YYYYMMDD)*** 2000 APR 7

3. DOCUMENT TITLE

TENT, FABRIC ASSEMBLIES, STANDARDIZED INTEGRATED COMMAND POST SYSTEM

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME DEFENSE SUPPLY CENTER PHILADELPHIA DSCP-CNRP	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN (215) 737-3290 444-3290
c. ADDRESS *(Include Zip Code)* 700 Robbins Ave. (Bldg 6, C&T) PHILADELPHIA, PA 19111-5092	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888

DD Form 1426, FEB 1999 (EG) PREVIOUS EDITION IS OBSOLETE
WHS/DIOR, Feb 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.