INCH-POUND
MIL-F-44397(GL)
10 January 1990

MILITARY SPECIFICATION

FRAME, TENT (SICPS)

This specification is approved for use by the Natick Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a frame for a command post tent.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

DDD-L-20	-	Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-704 - Treatment and Painting of Material
MIL-C-5541 - Chemical Conversion Coatings on Aluminum and Aluminum Alloys

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-6946 - Frame Assembly, End Wall
5-4-6947 - Frame Assembly, Tent
5-4-6967 - Frame Assembly, Center
5-4-6980 - Pole Assembly, Telescopic, SICPS
6-1-9374 - Finish Requirements, CARC Paint

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the documents cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 633 - Electrodeposited Coating of Zinc on Iron and Steel
D 3951 - Standard Practice for Commercial Packaging

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Material and components shall be as specified on Drawing 5-4-6947 and on all drawings and parts lists pertaining thereto, and as specified herein. Materials not definitely specified shall be of the quality normally used by the contractor provided that the completed item complies with all provisions of this specification. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Treatment and painting. Treatment and painting of material shall conform to MIL-STD-704 and Drawing 6-1-9374.

3.3 Design and construction. The design and construction of the frame shall be as specified herein and conform to Drawing 5-4-6947 and all subsidiary drawings and parts lists. The frame sections shall be capable of being erected by hand without the use of a tool for force.

3.3.1 Castings. Castings shall be clean and free from pits, blow holes and scale.

3.3.2 Rivets. All rivets shall be securely set.

3.3.3 Welds. All welds shall be smooth, uniform, and free from burn through areas, pits, slag inclusion, porosity, cracks, fractures, flash and excess flux deposits.

3.4 Finish. Interior surfaces of tubes, where slotted or diagonally cut at the end and the shank of rivets do not need to be primed or painted.

3.4.1 Cleaning and treatment. Prior to assembly, all completely fabricated metal components shall be thoroughly clean and exterior surfaces of all aluminum shall be cleaned and treated in accordance with class 1A treatment of MIL-C-5541.

3.4.2 Frame components. The frame components shall be coated as specified on the drawings and 3.2.1. The finish coating shall be continuous and uniform, e.g., free of sag, run, pinhole, blister, wrinkle, area of thin or no film,

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:54Z
Check the source to verify that this is the current version before use.

scratch or scruff, foreign matter imbedded in finish, and wet or tacky paint. Areas of finish damaged during flexing of movable joints shall be touched up.

3.4.2.1 Elastic cord. The elastic cord on Drawings 5-4-6946, 5-4-6947, and 5-4-6967 shall be crimped tightly to prevent slippage.

3.5 Marking. All markings and labels shall conform to DDD-L-20.

3.5.1 Frame identification. One outer leg member of the frame shall be permanently and distinctly stamped or marked for identification in accordance with MIL-STD-130, with the letters "US" in 1/4-inch high characters, and the manufacturer's name, number and date of the contract in 1/8-inch characters.

3.6 Workmanship. The frame shall conform to the quality of product established by this specification. All components of the frame shall not be bent out of shape and shall be free from split, puncture, fracture, twist, malformation, sharp edge, and burr. Castings shall be clean and free from pits, blow holes and scale. Rivets and rollpins shall be free from more than one split.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3, 4.4.4 and tested for the characteristics specified in 4.4.5.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made of the operations listed in table I to establish that no deviation is made from the indicated requirements. Whenever a nonconformance is noted, corrections shall be made to the affected items, the lot in progress and to the operation. Parts which cannot be corrected shall be removed from production.

TABLE I. In-process inspection

Operation	Requirement paragraph
Castings are clean and free from pits, blow holes and scale	3.3.1
Welds are sound, smooth, uniform, and free from burn through areas, pits, slag inclusion, porosity, crack, fracture, flash and excess flux deposit	3.3.3
All completely fabricated metal components are clean and exterior surfaces of metal are treated prior to assembly	3.4.2

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table II. The lot size shall be expressed in units of tent frame assemblies. The sample unit shall be one tent frame assembly. The inspection level shall be II. The acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 15.0 for major defects and 40.0 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Color not as specified		201
	Detent body assembly and clamps coated		202
	Not continuous and not uniform, e.g., sag, pinhole, blister, wrinkle, foreign matter imbedded in finish and wet or tacky		203
	Any run exceeding 3 inches in length	101	
	Area of no film:		
	-more than 3-square inches of bare metal	102	
	-3-square inches or less of bare metal		204
Note:	Areas of no film on interior surfaces of the tent frame tubes, where slotted or diagonally cut at the end, and the shank of rivets, holes are allowed.		
	Area of thin film:		
	-primer shows through in an area of 9-square inches or more	103	
	-primer shows through in an area less than 9-square inches		205
	Scratch or scruff exposing bare metal:		
	-12 inches or more in longest dimensions	104	
	-less than 12 inches in longest dimensions		206
Note:	Defects in finish attributable to flexing of movable joints during examination will not be scored as a defect. However, areas damaged during flexing of movable parts shall be touched up.		
Hardware	Broken	105	
	Malformed:		
	-fails to perform intended function	106	
	-but will perform intended function		207
	Corroded area		208
	Burr or sharp edge which may cause injury in handling or damage to fabric	107	
	Elastic cord fasteners not crimped tightly	108	
Construction and Workmanship	Any part or component not fabricated of applicable referenced materials	109	
	Any component missing	110	
	Any component not fabricated as specified	111	
	Any component split, punctured, twisted, fractured, malformed or bent out of shape	112	
	Any sharp edge or burr	113	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Castings	Clean and free from pits, blow holes and scale	114	
	Burn through area, pits, discoloration, porosity, crack, fracture, flash, or nonuniform surface		209
Riveting	Loose rivet		210
	Roll of a rivet has more than one split		211
Rollpins	Loose rollpins	115	
	Rollpins contain more than one split	116	
Cables	Cable swages not crimped properly	117	
Threaded components	Any bolt, nut or screw missing	118	
	Not specified size or type	119	
	Threads damaged or stripped	120	
Markings and Labels	Omitted, illegible, incorrect, of improper size or type, or not in location specified		212

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerances shall be classified as a defect. The lot size shall be expressed in units of tent frames. The sample unit shall be one tent frame. The inspection level shall be I. The AQL, expressed in terms of defects per hundred units, shall be 15.0.

4.4.5 Examination of frame for defects during erection. The completely fabricated frame shall be examined during erection and striking for the defects listed in table III. Each sample frame specified for erection inspection shall be fully erected and struck ten times. The frames selected for the visual or dimensional examination shall not be used for this examination until after the visual examination has been conducted, and the sample item has passed inspection. The lot size shall be expressed in tent frames. The sample unit shall be one tent frame or as specified in the procurement document. The inspection level shall be S-1. The AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

CHANGE 0 CHANGE 0 CHANGE 0 CHANGE 0

TABLE III. End item tests

Examine	Defect
Assembly	Any component or assembly that cannot be connected or joined with companion assembly, i.e., assembling requires realignment of parts, drilling, enlargement of holes, or use of drift pin or other mechanical means Assembly hole missing or misplaced Special tool is required to aid assembly Buckled, bent out of shape, or otherwise damaged Any components missing (check all bolts, self-locking nuts, pin detent assemblies and locking cam assemblies Component does not fit with mating components Component is out of alignment Cam locking joints that do not lock or unlock (open or close) when handle is locked or unlocked Cables are too loose or not taut when the frame is fully erected Cables which are too tight, not allowing the legs to be vertical when the frame is erected
Note:	Areas of finish damaged during erection and disassembly of the frame sections shall be touched up.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2. The AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

5.1.1 Level A preservation. The frame shall be completely folded, and secured with the binding strap provided. The ends of the folded assembly shall be wrapped or cushioned to prevent damage to the finish. The end connections of each purlin and header shall be wrapped. All pins shall be secured with tape and wrapped or cushioned to prevent damage to the finish.

5.1.2 Commercial preservation. Components of each frame shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

5.2.1 Level A packing. One complete frame, preserved as specified in 5.1, shall be packed in a close fitting shipping container conforming to overseas type, style A, type 3 load of PPP-B-601. Inside dimensions of the box shall approximate 70 inches in length, 20 inches in width, and 13 inches in depth. Each box shall be provided with skids fabricated in accordance with the requirements of the box specification. Cushioning shall be used, as necessary, to prevent movement or damage during shipment. Each box shall be closed and reinforced with strapping in accordance with the appendix of PPP-B-601.

5.2.2 Level B packing. One complete frame, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except that the box shall conform to class 2, style A, NO. 1 or 2 end of PPP-B-640.

5.2.3 Commercial packing. Frame sections or individual components when procured separately, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipment shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The frame shall provide support for a tent 11 feet long, 11 feet wide and 9-1/2 feet high. The tent is designed for use as a command post tent.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Brace
Shelter
Structure
Support
Tent

Custodian:

Army - GL

Preparing activity:

Army - GL

(Project 8340-A532)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-44397 (GL)	FRAME, TENT (SICPS)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.

The inspections set forth ... The Government reserves the right to perform any of

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick RD&E Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:54Z
Check the source to verify that this is the current version before use.