INCH-POUND

MIL-P-44407(GL)
26 February 1991

MILITARY SPECIFICATION

PACKETS FOR VEST, AIRCREW, SURVIVAL

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers packets which will be included in the survival vest worn by aircrew personnel. The packets are part of an aircrew survival system. This is a special purpose Life Support Clothing and Equipment (LSC&E) item. All Government administrative and surveillance procedures applicable to LSC&E items shall be invoked in accordance with the contract or purchase order (see 6.2).

1.2 Classification. The survival packets shall be of the following types:

Type I - Basic

Type II - Medical

Type III - First aid dressing and water storage bag

Type IV - Combat casualty blanket

2. APPLICABLE DOCUMENTS

2.1 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5019 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

A-A-48	-	Soap, Toilet (Milled Cake)
A-A-20175	-	Chewing Gum
A-A-20177	-	Candy and Chocolate Confections
A-A-30074	-	Adhesive Tape, Surgical
A-A-53850	-	Aspirin Tablets, USP
A-A-53866	-	Bacitracin Ointment, USP
L-P-378	-	Plastic, Sheet and Strip, Thin Gauge, Polyolefin
U-P-560	-	Bacitracin Zinc, Neomycin Sulfate and Polymyxin B Sulfate Opthalmic Ointment
EE-M-101	-	Matches, Safety and Matches, Nonsafety (Strike Anywhere)
FF-P-416	-	Pin, Safety
DDD-B-35	-	Bandage, Absorbent, Adhesive
FFF-F-486	-	Floss, Dental
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-W-283	-	Water Purification Tablet, Iodine
MIL-S-9964	-	Saw, Hand, Finger Grip, Survival, Type MB-2
MIL-F-10805	-	Fuel, Compressed, Trioxane, Ration Heating
MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-R-36540	-	Razor, Surgical Preparation (For Field Use)
MIL-B-36842	-	Bandage, Gauze, Elastic, 2 Ply, 3 Inches by 5 Yards
MIL-B-36964	-	Blanket, Combat, Casualty, Lightweight, Waterproof, Aluminized Plastic

STANDARDS

FEDERAL

FED-STD-101	-	Test Procedures for Packaging Materials

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and miltary specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

F 88 - Test Method for Seal Strength of Flexible Barrier Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Guide samples. Guide samples, when furnished, are solely for guidance and information to the contractor (see 6.6). Variations from this specification may appear in the sample, in which case this specification shall govern.

3.3 Material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Component bags. The bags for individual components shall be fabricated from 0.003-inch thick polyethylene tubing conforming to type I, class 1 of L-P-378. The bottom seam of each bag shall be heat sealed. Each bag shall be of appropriate length and width to accommodate the applicable component. The component bags shall be clear and transparent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

3.3.2 Packet bags. The packet bags shall be fabricated from multilayer film consisting of a nominal 0.001-inch thick layer of nylon 6, a nominal 0.0002-inch thick layer of polyvinylidene dichloride, and a nominal 0.0025-inch thick layer of polyethylene (LD copolymer EVA) (see 6.4). The bag shall be heat sealed on three sides and shall have a tear notch on the top edge. The empty bag dimensions shall be 4-3/4 by 8 inches ± 1/8 inch. The packet bags shall be clear and transparent.

3.3.3 Component identification labels. Each component shall have affixed to it a clearly visible identification label. Each label shall be fabricated from white bond paper of appropriate size and shall have a black letter legend containing the applicable component nomenclature specified in tables I through IV. The legends shall be printed by a lithograph, photo-offset, or silk screen process. The printing shall be sharply defined and legible. The label shall be affixed to the components prior to inserting them into the component bag.

3.3.4 Packet content and instruction sheets. Each packet shall contain a list of contents and related information printed with black waterproof ink on a white waterproof paper sheet. The printed sheet shall be folded to be approximately 4-1/2 inches wide by 3 inches long. The list legend shall contain the type of packet and the applicable information specified in 3.5. The list shall not show any deleterious effects when tested for immersion as specified in 4.4.1.3.

3.4 Packet contents, requirements and packaging. Each of the components to be included in the packets shall conform to the applicable requirements specified in tables I through IV. Components shall be of the specified quantity and may be configured in any way as long as no components are damaged. Each component shall be inserted, along with the related component identification label specified in 3.3.3, into the individual component bag specified in 3.3.1 prior to sealing. The label shall be placed between the component and the component bag with the legend to the outside for easy identification. Excess air in the component bag shall be removed by physical compression. The closure shall be heat sealed. The heat seal shall be uniform and smooth (without wrinkles or foreign matter) and shall have a seam strength of not less than 7 pounds per inch of width when tested in accordance with 4.5.2. Excess tubing beyond the seals shall be cut off. The filled and sealed component bags shall not leak when tested as specified in 4.4.5.3.

TABLE I. Contents for the type I basic packet

Item No.	Component nomenclature	NSN	Quantity	Requirements
1	Fuel, compressed, trioxane, ration heating	9110-00-263-9865	3 bars	MIL-F-10805, type II 1/

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:55Z
Check the source to verify that this is the current version before use

TABLE I. Contents for the type I basic packet (cont'd)

Item No.	Component nomenclature	NSN	Quantity	Requirements
2	Matches, strike anywhere	9920-00-985-6891	1 box (30 matches)	EE-M-101, type III, class I, size 2
3	Whistle, ball, plastic	2/	1 each	---
4	Fire starter, aviation, survival, magnesium	1680-01-160-5618	1 each	---
5	Headnet and mitten set	3/	1 each	---
6	Sunscreen and insect repellent	6505-01-288-2188	1 each	---
7	Saw, hand, finger grip, survival	5110-00-570-6896	1 each	MIL-S-9964, type MB-2 4/
8	Moleskin, 2 inches by 10 inches	6510-00-203-6010	2 each	5/
9	Chewing gum	---	3 packets (6 tablets)	A-A-20175 6/ type I, any flavor
10	Candy	---	10 each	A-A-20177 7/
11	List of contents and instructions	---	1 each	(See 3.3.4 and 3.5.1)

1/ Trioxane shall be preserved in foil packet as specified in MIL-F-10805, then packaged in a component bag.

2/ Source: Seron Mfg. Co., 254 Republic Ave., Joilet, IL 60535. Part No. P-38 or equal (see 6.5).

3/ Source: Absentee Shawnee Bandage Group, P.O. Box 98, Tecumseh, OK 74873 or equal (see 6.5).

4/ It is recommended that the saw be reconfigured to reduce bulk, then packaged in a component bag.

5/ Moleskin shall be cut under sanitary conditions to proper dimensions, then packaged in a component bag.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:55Z
Check the source to verify that this is the current version before use.

6/ Gum tablets shall be in a cellophane wrapper, then packaged in a component bag.

7/ Type IV - Hard candy fruit tablets.

TABLE II. Contents for the type II medical packet

Item No.	Component nomenclature	NSN	Quantity	Requirements
1	Aspirin tablets, 0.324 gram, indiviually sealed 100s	6505-00-118-1948	10 each	A-A-53850 1/
2	Bandage, adhesive, 3/4 inch by 3 inches	6510-00-913-7909	6 each	DDD-B-35
3	Bandage, gauze, elastic, 2 ply, 2 inches by 5 yards	6510-00-913-7906	1 each	MIL-B-36842
4	Bacitracin ointment, USP 1 oz. tube	6505-00-582-4191	2 each	A-A-53866
5	Bacitracin opthalmic eye ointment, USP 1/8 oz tube	6505-00-582-4190	1 each	U-P-560
6	Floss, unwaxed, dental, 100 yards	6520-00-935-1007	1 each	FFF-F-486
7	Imodium capsules, anti-diarrhea	6505-01-066-6568	6 each	1/
8	Pin, safety	8315-00-787-8000	4 each	FF-P-416
9	Razor, surgical, preparation	6515-00-926-2089	1 each	MIL-R-36540 2/
10	Tape, adhesive, surgical, 1/2 inch, woven	6510-00-926-8881	1 each	A-A-30074
11	Discs, transderm, scopoline	6505-01-138-5692	4 each	2/
12	Needle, sewing, 18 gage	---	2 each	Commercial 3/
13	Penrose tubing, 3/8 inch by 12 inches	6515-00-926-8954	1 each	---

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:55Z
Check the source to verify that this is the current version before use.

TABLE II. Contents for the type II medical packet (cont'd)

Item No.	Component nomenclature	NSN	Quantity	Requirements
14	Water purification tablets, iodine, 8 mg.	6850-00-985-7166	1 bottle (50 tablets)	MIL-W-283
15	Soap, toilet, nonfloating 1/2 oz. with bacterial capability	8520-00-551-0375	1 each	A-A-48
16	List of contents and instructions	---	1 each	(See 3.3.4 and 3.5.2)

1/ Ten aspirins or six imodium capsules shall be separated from bulk sheet, maintained in blister pack, then packaged in a component bag.

2/ One razor or four scopoline discs shall be maintained in original wrapping, then packaged in a component bag.

3/ Needles shall be round eyed for general hand sewing. The length of the size 2 needle shall be 2 inch nominal and have a diameter of 0.034 inch. One needle shall be straight and one needle shall be bowed.

TABLE III. Contents for the type III first aid dressing and water storage bag packet

Item No.	Component nomenclature	NSN	Quantity	Requirements
1	Dressing, first aid, field	6510-00-159-4883	1 each	1/
2	Water storage bag	2/	1 each	---
3	List of contents and instructions	---	1 each	(See 3.3.4 and 3.5.3)

1/ Dressing shall be maintained in original wrapping, then packaged in a component bag.

2/ Source: Absentee Shawnee Bandage Group, P.O. Box 98, Tecumseh, OK 74873 or equal (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:55Z
Check the source to verify that this is the current version before use.

TABLE IV. Contents for the type IV combat casualty blanket packet

Item No.	Component nomenclature	NSN	Quantity	Requirements
1	Blanket, combat casualty	7210-00-935-6667	1 each	MIL-B-36964, type III
2	List of contents and instructions	---	1 each	(See 3.3.4 and 3.5.4)

3.5 Legends for packet content and instruction sheets (see 3.3.4).

3.5.1 Legend for sheet for type I basic packet.

TYPE I - BASIC PACKET

ITEM IDENTIFICATION	QUANTITY	COMMENTS
Fuel, compressed, trioxane ration heating (MIL-F-10805)	3 bars	Heating food/water
Matches, strike anywhere, type III, class I, size 2 (EE-M-101)	1 box (30 matches)	For use as required
Whistle, ball, plastic (commercial)	1 each	Signaling/communication
Fire starter, aviation, survival, magnesium (1680-01-160-5618)	1 each	Instant fire starting
Headnet and mitten set (commercial)	1 each	Protection against insects, apply insect repellent before using
Sunscreen and insect repellent (6505-01-288-2188)	1 each	Protection against insects and sunburn
Saw, hand, finger grip, survival, type MB-2 (5150-00-570-6896)	1 each	For use as required
Moleskin, 2 inches by 10 inches (6510-00-203-6010)	2 each	Foot injuries and blisters

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:55Z
Check the source to verify that this is the current version before use.

TYPE I - BASIC PACKET (cont'd)

ITEM IDENTIFICATION	QUANTITY	COMMENTS
Chewing gum (A-A-20175)	6 each	Quick energy
Candy (A-A-20177)	10 each	Quick energy

3.5.2 Legend for sheet for type II medical packet.

TYPE II - MEDICAL PACKET

ITEM IDENTIFICATION	QUANTITY	USE	COMMENTS
Aspirin tablets (6505-00-118-1948)	10 each	Headache and acute pain	1 or 2 tablets every 4 hours, up to four times a day
Bandage, adhesive, 3/4 inch by 3 inches (6510-00-913-7909)	6 each	Minor cuts and skin breaks	As required
Bandage, gauze, elastic, 2 ply, 2 inches by 5 yards (6510-00-913-7906)	1 each	Bandaging injuries	Cut lengths as required
Bacitracin ointment, USP, 1 oz. tube (6505-00-582-4191)	2 each	Cuts, scratches, bites, fungus infections	Apply to skin, rub in
Bacitracin opthalmic eye ointment, USP 1/8 oz. tube (6505-00-582-4190)	1 each	Eye injuries, irritations	Apply small amount to inside lower eye lid, do not rub eyes
Floss, unwaxed, dental, 100 yards (6520-00-935-1007)	1 each	Cleaning teeth	Cut length as required
Imodium capsules, anti-diarrhea (6505-01-066-6568)	6 each	Diarrhea	Take 2 tablets 3 or 4 times daily
Pin, safety (8315-00-787-8000)	4 each	Pin bandages, slings, clothing	For use as required

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:55Z
Check the source to verify that this is the current version before use.

TYPE II - MEDICAL PACKET (cont'd)

ITEM IDENTIFICATION	QUANTITY	USE	COMMENTS
Razor, surgical, preparation (6515-00-926-2089)	1 each	Shaving hair, opening wounds	For use as required
Tape, adhesive, surgical, 1/2 inch woven (6510-00-926-8881)	1 each	Closing wounds	Cut length as required
Disc, transderm, scopoline (6505-01-138-5692)	4 each	Motion sickness	1 disc behind ear up to 3 days
Needle, sewing, 18 gage (commercial)	2 each	Mending clothing, webbing	For use as required
Penrose tubing, 3/8 inch by 12 inches (6515-00-926-8953)	1 each	Tourniquet to control blood circulation	For use as required
Water purification tablet, iodine, 8 mg. (6850-00-985-7166)	1 each	Purifying water	2 tablets per quart of water, shake well, wait 20 minutes
Soap, toilet, non-floating, 1/2 oz. with bacterial capability (8520-00-551-0375)	1 each	Cleansing wounds	For use as required

3.5.3 Legend for sheet for type III first aid dressing and water storage bag packet.

TYPE III - FIRST AID DRESSING AND WATER STORAGE BAG

ITEM IDENTIFICATION	QUANTITY	USE
Dressing, first aid, field, type III (6510-11-159-4883)	1 each	Protect wounds, compress to stop bleeding
Water storage bag	1 each	Storing and carrying water

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

3.5.4 Legend for sheet for type IV combat casualty blanket packet.

TYPE IV - COMBAT CASUALTY BLANKET

ITEM IDENTIFICATION	QUANTITY	USE FOR
Blanket, combat casualty, type III (7210-00-935-6667)	1 each	Protection from cold

3.6 Potency expiration items. The contractor shall determine from the marked expiration date(s) that at least 12 months potency remains beyond his assembly date.

3.7 Packet assembly. The components, individually packaged as specified in 3.4, of each type packet specified in tables I through IV, shall be assembled in the packet bag specified in 3.3.2. The folded list of contents and related information shall be inserted into the packet bag prior to sealing the bag. In type I packets, the matches shall be placed at one end of the bag and the fuel, trioxane and fire starter at the other end. Each filled bag shall be vacuum packaged under minimum 28 inches of mercury and the closure heat sealed. The heat seal closure shall be 3/16 to 1/2 inch in width, uniform and smooth (without wrinkles or foreign matter) and shall have a seam strength of not less than 7 pounds per inch of width when tested as specified in 4.5.2. The finished dimensions of type I and type II packets shall not exceed 5-1/2 by 4 by 2 inches. The finished depth of type III and type IV packets shall not exceed 3/4 inch. Each vacuum packaged packet shall be hard and compact and show no loss of vacuum.

3.8 Workmanship. The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels. Utmost care shall be taken during fabrication to ensure quality workmanship and safety of the service person using the item.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. Any nonconformance shall be cause for the rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the packet bag film conforms to the requirements specified in 3.3.2.

4.4.1.2 Unfilled packet bag visual examination. The bags shall be examined for the defects listed in table V. The lot size shall be expressed in units of packet bags. The sample unit shall be one unfilled packet bag.

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:55Z
Check the source to verify that this is the current version before use.

The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0 for major defects and 4.0 for total (major and minor combined) defects.

TABLE V. Unfilled packet bag visual defects

Examine	Defect	Classification Major	Minor
Material	Any tear, hole, or split	101	
	Not fabricated as specified	102	
	Creases, sharp wrinkles or surface imperfections in packet which impair the use of the packet	103	
	Plastic not clear and transparent	104	
Heat sealing	Not heat sealed as specified	105	
	Not heat sealed on three sides	106	
Tear notch	Omitted		201
General	Any finished packet dimension not as specified	107	

4.4.1.3 Immersion test (list of contents and instructions sheet). The lists shall be tested for conformance to the immersion requirement in 3.3.4. Two copies of the list shall be fully immersed in tap water for 24 hours. There shall be no deleterious effects such as running ink or shredded paper. Any test failure shall be cause for rejection of the lot.

4.4.2 In-process inspection. Inspection of filled and sealed component bags shall be made to ascertain that they conform to the hot water immersion requirements in 3.4 when tested for leaks in accordance with the hot water technique of Method 5009 of FED-STD-101. Bubbles which may appear on the surface of the bag but are not released are not to be construed as an indication of failure. A steady stream or recurring succession of bubbles from any surface or seam shall be considered a failure. Upon completion of the test the bags shall be thoroughly dried. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.3 Filled and sealed packet examination. The filled and sealed packets shall be examined for the defects listed in table VI. The lot size shall be expressed in units of packets. The sample unit shall be one filled and sealed packet. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0 for major defects and 4.0 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

TABLE VI. Packet contents visual defects

Examine	Defect	Classification Major	Minor
Material	Any tear, hole or split in component bag	101	
	Component bags not fabricated as specified	102	
	Creases, sharp wrinkles or surface imperfections in component bag which impair the use of the bag	103	
Components	Any component missing	104	
	Any component not as specified	105	
	Component quantity not as specified	106	
	Any component leaking, torn or broken	107	
Heat sealing	Component bag not properly sealed	108	
	Component heat seal caught in packet heat seal	109	
	Packet heat seal closure width not as specified		201
	Packet heat seal closure not uniform and smooth	110	
Visibility	Plastic not clear and transparent as specified	111	
General	Packet shows loss of vacuum	112	
	Any packet dimension not as specified	113	
	Excessive air trapped in component bag	114	
Contents and instruction list	Omitted, incorrect or illegible	115	
Identification labels	Omitted, incorrect, or illegible	116	
	Not positioned as specified		202

4.4.4 Seam strength testing. The closure seams of the packets shall be tested as specified in ASTM F 88 for conformance to the seam strength requirements in 3.7. The lot size shall be expressed in packets. The sample unit shall be one packet. The inspection level shall be S-2. Any test failure shall cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling. Bulged or distorted container.
Content	Number of packets per container is more or less than required.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. The packaging of the individual components must meet the current regulations for the domestic and international transportation of hazardous goods.

5.2 Packing. Packing shall be level A or B, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Forty type I or II packets or 80 type III or IV packets, of one type only, assembled as specified in 3.7, shall be packed in a shipping container conforming to style RSC-L, grade V2s of PPP-B-636. Inside dimensions of the shipping container shall approximate 21 inches in length, 13-1/2 inches in width and 8-1/2 inches in depth. Each shipping container shall be closed, waterproofed and reinforced in acordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Forty type I or II packets or 80 type III or IV packets, of one type only, assembled as specified in 3.7, shall be packed in a shipping container conformimg to style RSC-L, grade V3c of PPP-B-636. Inside dimensions of the shipping container shall approximate 21 inches in length, 13-1/2 inches in width, and 8-1/2 inches in depth. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.3 Palletization. When specified (see 6.2), packets packed as specified in 5.2.2 shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4 way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 91 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The survival packets are intended for use by aircrew personnel in emergency survival situations.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Special provisions for verification inspection of Life Support Clothing and Equipment (see 1.1).
c. Type required (see 1.2).
d. Issue of DODISS to be cited in the solicitation, and if required the specific issue of individual documents referenced (see 2.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

e. When a first article is required (see 3.1, 4.3 and 6.3).
f. Levels of packing (see 5.2).
g. Type and class of unit load (see 5.2.1).
h. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Packet film material. The film manufactured by Curwood, Inc. (Oshkosh, WI), as Curlon, Grade 550, has been tested and found to meet the requirements of 3.3.2.

6.5 Equal item. Prior to the use of an "or equal" item, the supplier shall submit the item with supporting data to the contracting officer for subsequent approval or disapproval by the responsible military agency.

6.6 Samples. For access to samples address the contracting activity issuing the invitation for bids or request for proposal.

6.7 Subject term (key word) listing.

Emergency
Kit
Life Support Clothing and Equipment
LSC&E
SARVIP system

Custodian:

Army - GL

Review activities:

Army - MD
DLA - CT

Preparing activity:

Army - GL

(Project 8465-0039)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:55Z
Check the source to verify that this is the current version before use.

class 3 and class 4 SARVIS lenses shall be tested for compliance with [illegible] tion or discoloration and the c

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-44407(GL)	1991 February 26

3. DOCUMENT TITLE
PACKETS FOR VEST, AIRCREW, SURVIVAL

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. Army Natick RD&E Center	(1) Commercial 508-651-4532	(2) AUTOVON 256-4532
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-IRT Natick, MA 01760-5019	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP, APR 90 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T01:55Z
Check the source to verify that this is the current version before use.