INCH-POUND
MIL-T-44382(GL)
22 January 1990

MILITARY SPECIFICATION

TABLE, FIELD, FOLDING LEGS, METAL

This specification is approved for use by the Natick Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a field table with folding legs.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-W-572	-	Wood Preservative; Water-Repellent
PPP-B-601	-	Boxes, Wood, Cleated Plywood
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7195

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-13-4661 - Field Table, Assembly

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-EMSS, Natick, MA 01760-5014.)

2.2 Non-Government publications. The following document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the documents cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Materials and components shall be as specified herein and on the applicable drawings and parts lists. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.2.1 Wood frame. The table top panels shall have a peripheral close-out of kiln dried hardwood. Hardwood type is optional, but the type chosen shall meet or exceed typical properties of commonly available birch. Corner joinery is optional and no gaps exceeding 0.001 inch shall be acceptable. The thickness of the material shall be such that the overall panel thickness is 0.5 inch. The width of the wood shall be 1.5 inches.

3.3 Design.

3.3.1 Load. Deflection of the table top shall not exceed 0.1 inch after removal of the test weight when tested as specified in 4.5.3. The table shall not collapse, exhibit instability, or permanent deformation and the leg locking devices shall not release when tested as specified in 4.5.4.

3.3.2 Low temperature. The components of the table shall show no permanent deformation, corrosion, delamination, cracks or loosening, and the legs and braces shall open and close by applying a force not to exceed ten pounds, after exposure to the conditions specified in 4.5.5.

3.3.3 High temperature. The components of the table shall show no permanent deformation, corrosion, delamination, cracks or loosening, and the legs and braces shall open and close by applying a force not to exceed ten pounds, after exposure to the conditions specified in 4.5.6.

3.3.4 High temperature/high humidity. The components of the table shall show no permanent deformation, corrosion, delamination, cracks or loosening, and the legs and braces shall open and close by applying a force not to exceed ten pounds, after exposure to the conditions specified in 4.5.7.

3.3.5 Impact resistance. The table panels shall not show signs of delamination beyond 1.5 inches from the center of impact after being tested as specified in 4.5.8.

3.3.6 Smoothness of table top. The table top shall not show signs of delamination or dimpling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

3.4 Construction. The table shall be constructed in accordance with the designs, details, and dimensions as shown on the drawings and as specified herein.

3.4.1 Panel flatness. Panel surfaces shall not be cupped or bowed in excess of 0.125 inch when measured with a 48-inch long straight edge as specified in 4.4.5.2.

3.5 Preparation of surfaces.

3.5.1 Skins. The decorative side of the skins shall be solvent wiped with methyl ethyl ketone (MEK), or a similar solvent. This wipe is to remove any minute adhesive particles which would deter from the aesthetic quality of the panels.

3.5.2 Wood. Prior to assembly, the wood shall be treated with wood tone, oil based wood sealer or according to TT-W-572.

3.6 Marking. The table shall be marked in accordance with MIL-STD-130 for identification and in accordance with MIL-STD-129 for shipment and storage.

3.7 Workmanship. The table shall conform to the quality of product established by this specification. All surfaces of the table shall be free from burrs, slivers, and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for defects specified in 4.4.3 and 4.4.4 and tested for the characteristics specified in 4.4.5.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection.

4.4.2.1 Impact test. Whenever the production process is changed, one representative panel (24-inches by 24-inches) shall be fabricated and tested as specified in the impact test. Any nonconformance shall constitute a test failure and shall be cause for the contractor to test a new sample.

4.4.2.2 Skin wipe. The decorative side of the skin shall be wiped prior to bonding as specified in 3.5.1.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of field tables. The sample unit shall be one field table. The inspection level shall be II. The acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 4.0 for total (major and minor combined) defects.

Table I. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Color not as specified	101	
	Not smooth or uniform, or foreign matter embedded in finish	102	
	Bare spots or areas of visible thin coating		201

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2. The AQL, expressed in terms of defects per hundred units, shall be 2.5

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.5 Methods of inspection.

4.5.1 Tap test.

4.5.1.1 Test number 1. The panel shall be tapped at approximately 6 inch intervals completely around the panel at 1 +1/2 inches from the panel edge. Any change in sound along the wood edges shall be cause for the panel to be further evaluated per 4.5.2.

4.5.1.2 Test number 2. The panel shall be tapped at approximately 6 inch intervals completely around the panel at 2-1/2 +1 inch from the panel edge. Any change in sound shall be cause for the panel to be further evaluated per 4.5.2.

4.5.1.3 Test number 3. The area of the panel that has not been tested shall be tapped at least 25 times, evenly distributed over each side. Any change in sound shall be cause for the panel to be further evaluated per 4.5.2.

4.5.2 Re-evaluation test. Panels indicating a change in sound in 4.5.1 shall be re-evaluated.

4.5.2.1 Re-evaluation number 1. Each area indicating a dull sound shall be marked with a wax or grease pencil (no permanent markings). Any panel containing dull sounding areas composing more than 25% of the total area per side shall constitute a failure and rejection of the panel.

4.5.2.2 Re-evaluation number 2. Panels containing a single dull sounding area greater than 30 square inches within one inch of the wood edges or 15 square inches in the remaining area per side shall constitute failure and rejection of the panel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

4.5.2.3 Re-evaluation number 3. Panels indicating a change in sound but within the limits of 4.5.2.1 and 4.5.2.2 shall be tested as specified in 4.5.2.3.1 and 4.5.2.3.2.

4.5.2.3.1 Panel flatness evaluation. Verify panel flatness in accordance with 4.4.5.2.

4.5.2.3.2 Visual evaluation.

4.5.2.3.2.1 Surface. Visually examine the panel for any rises (bubble) in the surface laminate. Any rise in the surface laminate shall be pressed downward by hand, and any displacement of the surface laminate shall constitute a failure and rejection of the panel.

4.5.2.3.2.2 Edges. Visually examine the outer edge of the panel. Any separation or delamination greater than 1/16 inch deep shall constitute a failure and rejection of the panel.

4.5.3 Static load test. With the table erected and with the legs locked in the unfolded position, a dead weight of 350 pounds. shall be applied at the center of the table top over an area not to exceed one square foot. The table shall remain loaded for one hour.

4.5.4 Horizontal force test. With the table loaded as specified in 4.5.3, an additional 50 pound horizontal force shall be applied to a corner at a direction perpendicular to the long edge of the table. Repeat test with force perpendicular to short edge.

4.5.5 Low temperature. The table shall be exposed to a temperature of -25 degrees F with a relative humidity of 0-10% for 24 hours. The table shall be in a folded position. Immediately after the end of the 24 hour period the force needed to open the legs shall be measured. Also, the table shall be static loaded as specified in 4.5.3 and 4.5.4 for one additional hour at the test conditions. After the table returns to standard temperature, it shall be examined for compliance with the requirements specified in 3.3.1 and 3.3.2, and any inability to comply with these requirements shall be cause for rejection of the table.

4.5.6 High temperature. The table shall be exposed to a temperature of 160 degrees F with a relative humidity of 0-10% for 24 hours. The table shall be in a folded position. Immediately after the end of the 24 hour period the force needed to open the legs shall be measured. Also, the table shall be static loaded as specified in 4.5.3 and 4.5.4 for one additional hour at the test conditions. After the table returns to standard temperature, it shall be examined for compliance with the requirements specified in 3.3.1 and 3.3.3, and any inability to comply with these requirements shall be cause for rejection of the table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

4.5.7 High temperature/high relative humidity. The table shall be exposed to a temperature of 100 degrees F with a relative humidity of 95% for 24 hours. The table shall be in a folded position. Immediately after the end of the 24 hour period the force needed to open the legs shall be measured. Also, the table shall be static loaded as specified in 4.5.3 and 4.5.4 for one additional hour at the test conditions. After the table returns to standard temperature, it shall be examined for compliance with the requirements specified in 3.3.1 and 3.3.4, and any inability to comply with these requirements shall be cause for rejection of the table.

4.5.8 Impact test (panel only). A 24-inch by 24-inch panel shall be impact resistant tested. It shall receive a blow from a 3 pound rigid metal cylinder dropped from a height of 15 inches. The specimen shall contain only one continuous piece of core material (without structural members or core splices) bonded with the same adhesive as used in the map board panel. The specimen shall be supported along its four edges by a wood framework backed by concrete. The framework shall be rigidly bolted together to form a square 24 inches per side (outside dimensions) and 4 inches high. The frame shall rest on the 24 inch wide face. The specimen shall be impacted with a cylinder of 2-1/2 inches in diameter and hemispherical at one end. The cylinder shall be positioned and dropped vertically so that the center of the hemispherical end of the cylinder strikes the center of the specimen on a horizontal plane. The cylinder shall not be permitted to be re-impact the specimen after the first impact. The test specimen shall be cross-sectioned through the impact area and visually examined for conformance to the requirements specified in 3.3.5.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial.

5.1.1 Level A preservation. Each table shall be collapsed and placed within a close-fitting fiberboard box conforming to style OPF, type CF, grade 200 of PPP-B-636. The inside dimensions of the box shall be 60-1/2 inches in length, 24-1/2 inches in width 1-3/8 inches in depth. Dimensions are furnished as a guide only. Each box shall be closed in accordance with PPP-B-636.

5.1.2 Commercial preservation. Each table shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial.

5.2.1 Level A packing. Twenty tables preserved as specified in 5.1.1, shall be packed in a close-fitting cleated-plywood shipping container conforming to overseas type, style optional PPP-B-601. The inside dimensions of the shipping container shall approximate 61 inches in length, 35 inches in width, and 25 inches in depth. Approximate dimensions are furnished as a guide only. The shipping container shall be skidded, closed, and strapped in accordance with PPP-B-601.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Twenty tables preserved as specified in 5.1.1, shall be packed in a cleated-plywood container conforming to domestic type, style optional PPP-B-601. The inside dimensions of the container shall approximate 61 inches in length, 35 inches in width, and 25 inches in depth. Approximate dimensions are furnished as a guide only. The shipping container shall be skidded, closed, and strapped in accordance with PPP-B-601.

5.2.3 Commercial packing. Tables preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special markings required by the contract or purchase order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The field table is intended to be used with the Standard Integrated Command Post System (SICPS) tent.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Drawing
Furniture
SICPS
Tent

Custodian:
Army - GL

Preparing activity:
Army - GL

(Project 7195-A106)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-44382 (GL)	Table, Field, Folding, Legs, Metal

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

NAME OF SUBMITTER (Last, First, MI) – Optional	b. WORK TELEPHONE NUMBER (Include Area Code) – Optional

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U S Army Natick Research, Development
and Engineering Center
ATTN STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:52Z
Check the source to verify that this is the current version before use.