FED. SUP CLASS 5305

METAL THICKNESS	.050	.060	.083	.109	.125	.140	.187	.250	.312	.375	.500
SCREW SIZE	SHEET STEEL										
2-56	.073	.073	.073	.073	.076	.076					
4-40	.089	.089	.094	.096	.098	.098	.102				
6-32	.110	.113	.116	.116	.116	.120	.125	.125			
8-32	.136	.140	.140	.144	.144	.147	.150	.150	.150		
10-24	.152	.154	.161	.161	.166	.170	.173	.173	.173	.173	
10-32	.159	.166	.166	.170	.170	.170	.177	.177	.177	.177	
1/4-20			.213	.219	.221	.221	.228	.228	.228	.228	.228
1/4-28			.221	.228	.228	.234	.234	.234	.234	.234	.234
5/16-18 (B)				.277	.277	.281	.290	.290	.290	.290	.290
3/8-16					.339	.339	.348	.358	.358	.358	.358
	SHEET ALUMINUM										
2-56	.070	.073	.073	.073	.073	.073					
4-40	.089	.089	.089	.094	.094	.094	.098				
6-32	.109	.109	.111	.113	.116	.116	.120	.125			
8-32	.136	.136	.136	.140	.140	.144	.147	.150	.150		
10-24	.150	.152	.154	.157	.159	.161	.166	.172	.173	.173	
10-32	.161	.161	.161	.166	.166	.166	.172	.177	.177	.177	
1/4-20			.206	.209	.213	.213	.221	.228	.228	.228	.228
	CAST IRON										
2-56	.076	.076	.076	.078	.078	.078					
4-40	.100	.100	.102	.102	.102	.102	.104				
6-32	.120	.120	.125	.125	.125	.125	.128	.128			
8-32	.147	.150	.150	.150	.150	.150	.154	.154	.154		
10-24	.170	.170	.172	.173	.173	.173	.177	.177	.177	.177	
10-32	.173	.173	.177	.177	.177	.177	.180	.180	.180	.180	
1/4-20			.228	.228	.228	.228	.234	.234	.234	.234	.234
	DIE CAST ZINC AND ALUMINUM										
2-56	.073	.073	.076	.076	.076	.076					
4-40	.096	.096	.096	.096	.100	.100	.100				
6-32	.116	.120	.120	.120	.120	.120	.120	.120			
8-32	.144	.144	.144	.144	.147	.147	.147	.150	.150		
10-24	.161	.166	.166	.166	.166	.166	.170	.170	.172	.172	
10-32	.170	.170	.172	.172	.172	.172	.172	.173	.173	.177	
1/4-20			.219	.219	.221	.221	.221	.228	.228	.228	.228

PLASTIC

SCREW SIZE	PHENOL FORMALDEHYDE				CELLULOSE ACETATE, CELLULOSE NITRATE, ACRYLIC RESIN, STYRENE RESIN			
	HOLE DIA	DRILL SIZE	DEPTH OF PENETRATION		HOLE DIA	DRILL SIZE	DEPTH OF PENETRATION	
			MIN	MAX			MIN	MAX
2-56	.078	5/64	.219	.375	.076	48	.219	.375
4-40	.098	40	.250	.312	.093	42	.250	.312
6-32	.116	32	.250	.312	.116	32	.250	.312
8-32	.144	27	.312	.500	.144	27	.312	.500
10-24	.161	20	.375	.500	.161	20	.375	.500
10-32	.166	19	.375	.500	.166	19	.375	.500
1/4-20	.228	1	.375	.625	.228	1	.375	1.000

NOTES:

1. Because conditions differ widely, it may be necessary to vary the hole size to suit a particular application.
2. (B) All dimensions are in inches. Hole diameters are standard drill sizes rounded to the nearest .001 inch.
3. For aeronautical applications, more definitive hole dimensions are contained in AND10326.
4. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
5. Referenced documents shall be of the issue in effect on date of invitations for bid.

(B) THIS IS A DESIGN STANDARD AND SHALL NOT BE USED AS A PART NUMBER

REVIEWER: AT, AV, EL, IS, MI, MU, NSA, 85 GL, ME, OS, SH
USER: AS,

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 5 OCT 59 REVISED (A) 7 JUN 61 (B) 8 NOV 68

P.A. WC
Other Cust S2

TITLE: SCREW, TAPPING, THREAD CUTTING - TYPES D, F, G AND T, APPROXIMATE HOLE SIZES FOR

MILITARY STANDARD
MS24634
SHEET 1 OF 1

PROCUREMENT SPECIFICATION NONE

SUPERSEDES:

DD FORM SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-341-513/A-2814

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:58Z
Check the source to verify that this is the current version before use.