

FED. SUP. CLASS
4730





DASH NUMBER		TUBE O.D.	B STRAIGHT THREAD	D DIA	G_1 DIA +.002 -.003	I_2	K +.015 -.005	K_1	M_3	M_4
ASSY	*BODY	NOM	CLASS 2A	DRILL		±.02		±.020	±.03	±.03
1	2	1/8	5/16-24UNF	0.093	0.250	0.83	.188	.094	0.80	1.33
3	4	3/16	3/8 -24UNF	0.125	0.313	0.88	.234	.094	0.92	1.41
5	6	1/4	7/16-20UNF	0.203	0.364	0.94	.234	.094	0.95	1.52
7	8	5/16	1/2 -20UNF	0.234	0.427	0.94	.250	.094	1.05	1.55
9	10	3/8	9/16-18UNF	0.281	0.482	0.95	.250	.094	1.08	1.70
11	12	1/2	3/4 -16UNF	0.422	0.660	1.12	.305	.125	1.33	1.97
13	14	5/8	7/8 -14UNF	0.500	0.773	1.27	.350	.125	1.52	2.27
15	16	3/4	1-1/16-12UN	0.656	0.945	1.38	.350	.125	1.64	2.48
17	18	7/8	1-3/16-12UN	0.718	1.070	1.38	.350	.125	1.70	2.55
19	20	1	1-5/16-12UN	0.875	1.195	1.38	.415	.125	1.73	2.61
21	22	1-1/4	1-5/8 -12UN	1.093	1.507	1.38	.415	.125	2.02	2.89
23	24	1-1/2	1-7/8 -12UN	1.344	1.756	1.38	.485	.125	2.20	3.17
25	26	2	2-1/2 -12UN	1.813	2.381	1.58	.485	.125	2.39	3.77

NOTES:
1. MATERIAL: Steel, carbon in accordance with procurement specification.
   Steel, corrosion-resisting in accordance with procurement specification.
2. PROTECTIVE COATING: Cadmium plated in accordance with procurement specification.
   Zinc plated in accordance with procurement specification.
   Phosphate coating in accordance with procurement specification.
   Passivation treatment in accordance with procurement specification.
3. DIMENSIONS AND TOLERANCES: Dimensions and tolerances not shown shall be in accordance with SAE Standard for Flareless Tube Fittings (SAE J514).
4. THREADS: Threads shall be in accordance with Screw-Thread Standards for Federal Services, FED-STD-H28.
5. PART NUMBER: The MS part number consists of the MS number, plus the dash number and (for complete assembly) the applicable MS51825 sleeve style designator.
   A. For complete assembly (with nuts and sleeves), cadmium plated, use the MS number, plus the assembly dash number and the sleeve style designator. Example: MS51855-1A or MS51855-1B.
   B. For body only, cadmium plated, use the MS number and the body dash number. Example: MS51855-2.
   C. For zinc coating add "Z" and (for complete assembly) the sleeve style designator to the dash number. Example: MS51855-1ZA or MS51855-1ZB or MS51855-2Z.
   D. For phosphate coating add "P" and (for complete assembly) the sleeve style designator to the dash number. Example: MS51855-1PA or MS51855-1PB or MS51855-2P.
   E. For corrosion-resisting steel add "SS" and (for complete assembly) the sleeve style designator to the dash number. Example: MS51855-1SSA or MS51855-1SSB or MS51855-2SS.
6. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
7. Reference documents shall be of the issue in effect on date of invitations for bid.
8. The illustration is for identification and is not intended to restrict designs or shapes not dimensioned.
* 9. After 22 NOV 1974 , bodies will be used for production only and SHALL NOT be stocked for maintenance. Existing stock of bodies should be used until depleted.

© Denotes change

APPROVED 16 DEC 1966 REVISED 30 DEC 1970 22 NOV 1974 © 30 July 1987

P.A. AR	TITLE	MILITARY STANDARD
Other Coast 99	ELBOW, TUBE, 90°, BULKHEAD, FLARELESS TYPE, HYDRAULIC	MS51855
PROCUREMENT SPECIFICATION MIL-F-18866	SUPERSEDES	SHEET 1 OF 1

DD FORM 672-1 (Coordinated) ☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-603-113/3486

4730-0898

© User Activities: Army - AT, AV, EL, AR Navy - OS, MC
© Review Activities: Army - GL, ME Air Force - 82 DLA - CS
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited. This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:11Z
Check the source to verify that this is the current version before use.