MIL-B-3628 / 37C
10 February 1988
SUPERSEDING
MIL-B-3628 / 37B
31 October 1969

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, LAUCHHEIMER TROPHY, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.



DASH NOS:
-1: GOLD
-2: SILVER
-3: BRONZE

MATERIAL:
-1: 1/10 10 KARAT GOLD FILLED (1/20 OBVERSE, 1/20 REVERSE OVER COMM'L BRASS ALLOY)
-2: 1/10 SILVER FILLED (1/20 OBVERSE AND 1/20 REVERSE OVER COMM'L BRASS ALLOY)
-3: GILDING METAL

DIMENSIONS (INCHES):
HEIGHT:
ASSEMBLED: 1-7/8 (REF)
PENDANT: 1-1/2 (REF)
SUSPENSION BAR: 11/32 (REF)

WIDTH (OVERALL):
PENDANT: 1-1/32 (REF)
SUSPENSION BAR: 1-15/32 (REF)

THICKNESS (AT RIM):
PENDANT: .055 ± .005
SUSPENSION BAR: .075 ± .005

FINISH:
OBVERSE:
PENDANT AND SUSPENSION BAR:
-1: GOLD PLATED, SMUDGED, HIGHLIGHTS POLISHED
-2: SILVER PLATED, LIGHTLY OXIDIZED, RELIEVED, HIGHLIGHTS POLISHED
-3: LIGHTLY OXIDIZED, RELIEVED, HIGHLIGHTS POLISHED

REVERSE: MIRROR-LIKE POLISHED

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:01Z
Check the source to verify that this is the current version before use.

NOTES:

1. THE LUGS FOR THE PENDANT, FORMED FROM .050 ± .002 INCH DIAMETER WIRE, SHALL BE 5/32 ± 1/64 INCH IN OUTSIDE DIAMETER. THE LUGS SHALL BE LOCATED 1/8, +1/32, -0 INCH BELOW THE TOP OF THE PENDANT AND 21/32 ± 1/32 INCH ON CENTERS. THE LUGS SHALL BE SOLDERED IN PLACE USING GOLD SOLDER FOR DASH NOS. 1 AND 3 AND SILVER SOLDER FOR DASH NO. 2. AT OPTION OF THE MANUFACTURER, THE LUGS ON THE PENDANT MAY BE MADE AN INTEGRAL TYPE, PROVIDED THE FINISHED DIMENSIONS ARE THE SAME AS THOSE SPECIFIED FOR THE SOLDERED TYPE.

2. THE CONNECTING LINKS, FORMED FROM .040 ± .002 INCH DIAMETER WIRE, SHALL BE OBLONG IN SHAPE, 5/16 ± 1/64 INCH IN LENGTH BY 1/8 ± 1/64 INCH IN WIDTH.

3. THE ATTACHING DEVICE SHALL BE PRONG AND FLAT BALL TYPE CLUTCH CONFORMING TO FIGURE 2. WHITE METAL FLAT BALL CLUTCHES SHALL BE USED FOR DASH NO. 2 AND RED BRASS FLAT BALL CLUTCHES SHALL BE USED FOR DASH NOS. 1 AND 3. THE PRONGS SHALL BE CENTERED ON AND SOLDERED TO THE BACK OF THE SUSPENSION BAR. THE PRONGS SHALL BE LOCATED 1-3/32 ± 1/32 INCHES ON CENTERS EQUIDISTANT FROM EACH END.

Custodian:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0268)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:01Z
Check the source to verify that this is the current version before use.