MILITARY SPECIFICATION SHEET

SUPERSEDING
MIL-B-3628/38A
30 June 1967

BADGE, QUALIFICATION, MARINE CORPS RIFLE CHAMPIONSHIP (McDOUGAL TROPHY)

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.



MATERIAL: 14 KARAT GOLD

DIMENSIONS (INCHES):
- HEIGHT:
  - ASSEMBLED: 1-31/32 (REF)
  - PENDANT (EXCLUDING LUGS): 1-1/2 (REF)
  - SUSPENSION BAR(EXCLUDING LUGS): 9/32 (REF)
- WIDTH (OVERALL):
  - PENDANT: 1-7/16 (REF)
  - SUSPENSION BAR (INCLUDING BALLS): 1-17/32 (REF)
- THICKNESS:
  - PENDANT (AT THICKEST POINT): .110 (REF)
  - SUSPENSION BAR (AT RIM): .085 (REF)

WEIGHT (ASSEMBLED) 540 GRAINS (MIN)

FINISH:
- PENDANT:
  - OBVERSE: SMUDGED, HIGHLIGHTS POLISHED
  - REVERSE AND EDGES: MIRROR-LIKE POLISHED
- SUSPENSION BAR:
  - OBVERSE: SMUDGED, HIGHLIGHTS POLISHED
  - REVERSE: MIRROR-LIKE POLISHED

NOTES:
1. THICKNESS GIVEN FOR INFORMATION PURPOSES ONLY. WEIGHT GOVERNS.

2. THE LINKS SHALL BE OBLONG SHAPED, 7/32 ± 1/32 INCH LONG BY 5/32 ± 1/32 INCH WIDE, SHALL BE FORMED FROM .040 ± .002 INCH DIAMETER WIRE. THE LUGS SHALL BE AN INTEGRAL PART OF BOTH THE PENDANT AND THE SUSPENSION BAR.

3. THE ATTACHING DEVICE SHALL BE PIN AND CATCH TYPE. THE DEVICE SHALL BE CENTERED ON AND SOLDERED TO THE BACK OF THE SUSPENSION BAR. THE HINGE AND CATCH SHALL BE 1-1/32 ± 1/32 INCH ON CENTERS AND THE PIN SHALL BE 1-3/16 ± 1/32 INCH IN LENGTH.

CUSTODIAN:
NAVY - PE
REVIEW ACTIVITIES:
NAVY - PE, MC
OTHER - DP
USER ACTIVITY:
NAVY - MC

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY, UNITED STATES ARMY

Project No. 8455-0131

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:01Z
Check the source to verify that this is the current version before use.