
MIL-B-3628 / 38C
10 February 1988
SUPERSEDING
MIL-B-3628 / 38B
31 October 1969

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, MARINE CORPS RIFLE CHAMPIONSHIP (McDOUGAL TROPHY)

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.



MATERIAL: 1/10 10 KARAT GOLD FILLED (1/20 OBVERSE, 1/20 REVERSE OVER COMM'L BRASS ALLOY)

DIMENSIONS (INCHES):
- HEIGHT:
  - ASSEMBLED: 1-31/32 (REF)
  - PENDANT (EXCLUDING LUGS): 1-1/2 (REF)
  - SUSPENSION BAR (EXCLUDING LUGS): 9/32 (REF)
- WIDTH (OVERALL):
  - PENDANT: 1-7/16 (REF)
  - SUSPENSION BAR (INCLUDING BALLS): 1-17/32 (REF)
- THICKNESS:
  - PENDANT (AT THICKEST POINT): .110 (REF)
  - SUSPENSION BAR (AT RIM): .085 (REF)

FINISH:
- PENDANT AND SUSPENSION BAR:
  - OBVERSE: GOLD PLATED, SMUDGED, HIGHLIGHTS POLISHED
  - REVERSE AND EDGES: MIRROR-LIKE POLISHED

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:01Z
Check the source to verify that this is the current version before use.

NOTES:

1. THE LINKS SHALL BE OBLONG SHAPED, 7/32 ± 1/32 INCH LONG BY 5/32 ± 1/32 INCH WIDE, SHALL BE FORMED FROM .040 ± .002 INCH DIAMETER WIRE. THE LUGS SHALL BE AN INTEGRAL PART OF BOTH THE PENDANT AND THE SUSPENSION BAR.

2. THE ATTACHING DEVICE SHALL BE PRONG AND FLAT BALL TYPE CLUTCH. THE PRONGS SHALL BE 1-1/32 ± 1/32 INCH ON CENTERS EQUIDISTANT FROM EACH END.

Custodian:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0268)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:01Z
Check the source to verify that this is the current version before use.