NOT MEASUREMENT SENSITIVE

MIL-B-3628/39E
30 July 1993
SUPERSEDING
MIL-B-3628/39D
10 February 1988

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, MARINE CORPS PISTOL CHAMPIONSHIP (WALSH TROPHY)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL: Red Brass

FINISH (Pendant and Suspension Bar):
OBVERSE: Gold Plated, Rose Gold Plated, Relieved, Letters and Rim (Top and Sides only) Polished Highlights.
REVERSE: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:02Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (Overall):

ASSEMBLED: 2 inches (5.08 cm) (REF)

PENDANT (Excluding Lugs): 1-15/32 inches (3.73 cm) (REF)

SUSPENSION BAR (Excluding Lugs): 9/32 inch (0.71 cm) (REF)

WIDTH (Overall):

PENDANT: 1-15/64 inches (3.14 cm) (REF)

SUSPENSION BAR (Including Balls): 1-17/32 inches (3.89 cm) (REF)

THICKNESS:

PENDANT (At Thickest Point): 0.115 inch ± .005 inch (0.292 cm ± 0.012 cm)

SUSPENSION BAR (At Rim): 0.070 inch ± .005 inch (0.178 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The links shall be oblong shaped, 7/32 inch ± 1/32 long by 5/32 inch ± 1/32 inch wide (0.56 cm ± 0.08 cm long by 0.40 cm ± 0.08 cm wide) and shall be formed from 0.040 inch ± 0.002 inch (0.102 cm ± 0.005 cm) diameter wire.

4. The lugs are an integral part of both the pendant and the suspension bar.

3. The attaching device shall be prong and flat ball clutch type. The prongs shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 1-1/32 inch ± 1/32 inch (2.62 cm ± 0.08 cm) apart.

Custodian:
Army - IH
Navy - NU

Preparing activities:
Army - IH

Review activities:
Navy - MC

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:02Z
Check the source to verify that this is the current version before use.