MILITARY SPECIFICATION SHEET

MIL-B-3628 / 43B
31 October 1969

SUPERSEDING
MIL-B-3628/43A
30 June 1967

Badge, Qualification, MARINE CORPS, DIVISION PISTOL COMPETITION

This specification is mandatory for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.





DASH NO.	AWARD
-1:	GOLD
-2:	SILVER
-3:	BRONZE



BLACK ENAMEL

WHITE ENAMEL

MATERIAL:
- -1: 14 KARAT GOLD
- -2: STERLING SILVER
- -3: GILDING METAL

DIMENSIONS (INCHES):
- HEIGHT:
  - ASSEMBLED: 1-3/4 (REF)
  - PENDANT: 1-9/32 (REF)
  - SUSPENSION BAR: 3/8 (REF)
- WIDTH (OVERALL):
  - PENDANT: 1-9/32 (REF)
  - SUSPENSION BAR: 1-15/32 (REF)
- THICKNESS (AT RIM):
  - PENDANT: .085 ± .005
  - SUSPENSION BAR: .065 ± .005

WEIGHT (ASSEMBLED):
- -1: 470 GRAINS (MIN)
- -2: 380 GRAINS (MIN)
- -3: N/A

FINISH:
- OBVERSE:
  - -1:
    - PENDANT: ENAMELED, SMUDGED, HIGHLIGHTS LIGHTLY POLISHED
    - SUSPENSION BAR: SMUDGED, HIGHLIGHTS POLISHED
  - -2 & -3:
    - PENDANT: ENAMELED, OXIDIZED, RELIEVED, HIGHLIGHTS LIGHTLY POLISHED
    - SUSPENSION BAR: OXIDIZED, HIGHLIGHTS POLISHED
- REVERSE: BRIGHTLY POLISHED

NOTES:

1. THE THICKNESS IS GIVEN FOR DASH NO. 1 AND DASH NO. 2 FOR INFORMATION PURPOSES ONLY. WEIGHT GOVERN.

2. THE LUGS FOR THE SUSPENSION BAR SHALL BE AN INTEGRAL PART OF THE BAR. THE LUGS ON THE PENDANT, FORMED FROM .044 ± .002 INCH DIAMETER WIRE, SHALL BE 5/32 ± 1/64 INCH IN OUTSIDE DIAMETER. THE LUGS SHALL BE LOCATED 3/32 ± 1/64 INCH BELOW THE TOP EDGE OF THE PENDANT AND 11/16 ± 1/64 INCH ON CENTERS. THE LUGS SHALL BE SOLDERED IN PLACE WITH GOLD SOLDER FOR DASH NO. 1 AND DASH NO. 3 AND SILVER SOLDER FOR DASH NO. 2.

3. THE CONNECTING LINKS, FORMED FROM .040 ± .002 INCH DIAMETER WIRE, SHALL BE OBLONG SHAPED, 3/16 ± 1/64 INCH LONG BY 1/8 ± 1/64 INCH WIDE.

4. THE ATTACHING DEVICE SHALL BE THE PIN AND CATCH TYPE. THE DEVICE SHALL BE CENTERED ON AND SOLDERED TO THE BACK OF THE SUSPENSION BAR. THE HINGE AND CATCH SHALL BE LOCATED 1 ± 1/32 INCH ON CENTERS. THE PIN SHALL BE 1-5/32 ± 1/32 INCHES IN LENGTH.

5. ENAMELED AREAS SHALL BE AS INDICATED. THE ENAMEL SHALL MATCH THE ENAMEL ON THE STANDARD OR APPROVED SAMPLE AND SHALL CONFORM TO THE TIOH COLOR CHIP NUMBERS LISTED BELOW:

Color	Chip No.
WHITE	28
BLACK	26

CUSTODIAN:
NAVY - PE
REVIEW ACTIVITIES:
NAVY - PE, MC
OTHER - DP
USER ACTIVITY:
NAVY - MC
Project No. 8455-0131

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY,
UNITED STATES ARMY

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:04Z
Check the source to verify that this is the current version before use.