MIL-B-3628 / 44B
31 October 1969
SUPERSEDING
MIL-B-3628/44A
30 June 1967

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, ANNUAL RIFLE SQUARD COMBAT PRACTICE COMPETITION, MARINE CORPS

This specification is mandatory for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.



DASH NO.	AWARD
-1:	GOLD
-2:	SILVER
-3:	BRONZE

MATERIAL:
-1: 14 KARAT GOLD
-2: STERLING SILVER
-3: BRONZE (90-10)

DIMENSIONS (INCHES):
HEIGHT:
ASSEMBLED: 1-15/16 (REF)
PENDANT (EXCLUDING LUGS): 1-15/32 (REF)
SUSPENSION BAR (EXCLUDING LUGS): 1/4 (REF)
WIDTH (OVERALL):
PENDANT: 1-3/16 (REF)
SUSPENSION BAR: 1-29/32 (REF)
THICKNESS (AT RIM):
PENDANT: .075 ± .005
SUSPENSION BAR: .060 ± .005

WEIGHT (ASSEMBLED):
-1: 380 GRAINS (MIN)
-2: 320 GRAINS (MIN)
-3: N/A

FINISH:
OBVERSE:
-1:
PENDANT: LIGHTLY SMUDGED, RELIEVED POLISHED HIGHLIGHTS
SUSPENSION BAR: SMUDGED, HIGHLIGHTS POLISHED
-2 & -3:
PENDANT: LIGHTLY OXIDIZED, RELIEVED, HIGHLIGHTS POLISHED
SUSPENSION BAR: OXIDIZED, HIGHLIGHTS POLISHED
REVERSE: MIRROR-LIKE POLISHED

NOTES:
1. THICKNESS FOR DASH NO. 1 AND DASH NO. 2 IS GIVEN FOR INFORMATION PURPOSES ONLY. WEIGHT GOVERNS.

2. THE LUGS SHALL BE AN INTERGRAL PART OF BOTH THE PENDANT AND SUSPENSION BAR. THE CONNECTING LINKS, FORMED FROM .042 ± .002 INCH DIAMETER WIRE, SHALL HAVE AN OUTSIDE DIAMETER OF 3/16 ± 1/32 INCH.

3. THE ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. THE PRONGS SHALL BE SOLDERED ON THE HORIZONTAL CENTERLINE OF THE BACK OF THE SUSPENSION BAR EQUIDISTANT FROM EACH END AND 1-7/16 ± 1/16 INCHES ON CENTERS.

CUSTODIAN:
NAVY - PE
REVIEW ACTIVITIES:
NAVY - PE, MC
OTHER - DP
USER ACTIVITY:
NAVY - MC

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY, UNITED STATES ARMY

Project No. 8455-0131

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:05Z
Check the source to verify that this is the current version before use.