NOT MEASUREMENT SENSITIVE

MIL-B-3628/44D
24 June 1993
SUPERSEDING
MIL-B-3628/44C
10 February 1988

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, ANNUAL RIFLE SQUAD COMBAT PRACTICE COMPETITION, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



DASH NO.
-1: Gold
-2: Silver
-3: Bronze

MATERIAL:
-1, -2: Red Brass
-3: Gilding Metal

FINISH:
OBVERSE:
-1: Gold Plated, Rose Gold Plated, Polished Highlights
-2: Silver Plated, Lightly Oxidized, Relieved, Polished Highlights and shall match TIOH Metal Finish Chip Number 15.
-3: Lightly Oxidized, Relieved, Polished Highlights
REVERSE:
-1: Gold Plated, Rose Gold Plated, Mirror-like Polished
-2: Silver Plated, Mirror-like Polished
-3: Mirror-like Polished

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T19:04Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (Overall):

ASSEMBLED: 1-15/16 inches (4.92 cm) (REF)
PENDANT (Excluding Lugs): 1-15/32 inches (3.73 cm) (REF)
SUSPENSION BAR (Excluding Lugs): 1/4 inch (0.64 cm) (REF)

WIDTH (Overall):

PENDANT: 1-3/16 inches (3.02 cm) (REF)
SUSPENSION BAR: 1-29/32 inches (4.84 cm) (REF)

THICKNESS (At Rim):

PENDANT: 0.075 inch ± .005 inch (0.191 cm ± 0.012 cm)
SUSPENSION BAR: 0.060 inch ± .005 inch (0.152 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lugs are an integral part of both the pendant and suspension bar.

3. The connecting links shall be formed from 0.042 inch ± 0.002 inch (0.107 cm ± 0.005 cm) diameter wire and shall have an outside diameter of 3/16 inch ± 1/64 inch (0.48 cm ± 0.04 cm).

3. The attaching device shall be prong and clutch type. Nickel plated flat ball clutches shall be used for Dash No. -2 and red brass flat ball clutches shall be used for Dash No. -1 and -3. The prongs shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 1-7/16 inch ± 1/16 inch (3.68 cm ± 0.16 cm) apart.

Custodian:
Army - IH
Navy - NU

Preparing activities:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:04Z
Check the source to verify that this is the current version before use.