INCH-POUND

MIL-DTL-3628/44F
15 August 2009
SUPERSEDING
MIL-DTL-3628/44E
15 November 1996

DETAIL SPECIFICATION SHEET

# BADGE, QUALIFICATION, ANNUAL RIFLE SQUAD COMBAT PRACTICE COMPETITION, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.




DASH NO.1
-1: Gold
-2: Silver
-3: Bronze

MATERIAL:
-1, -2: Red Brass
-3: Gilding Metal



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:04Z
Check the source to verify that this is the current version before use.

FINISH:
OBVERSE:
-1: Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
-2: Silver Plated, Lightly Oxidized, Relieved, Polished Highlights and shall match TIOH Metal Finish Chip Number 15.
-3: Lightly Oxidized, Relieved, Polished Highlights.
REVERSE:
-1: Gold Plated, Mirror-like Polished
-2: Silver Plated, Mirror-like Polished
-3: Mirror-like Polished

DIMENSIONS:
HEIGHT (overall):
ASSEMBLED: 1-15/16 inches (REF)
PENDANT (excluding lugs): 1-15/32 inches (REF)
SUSPENSION BAR (excluding lugs): 1/4 inch (REF)

WIDTH (overall):
PENDANT: 1-3/16 inches (REF)
SUSPENSION BAR: 1-29/32 inches (REF)

THICKNESS (at rim):
PENDANT: 0.075 inch $\pm$ .005 inch
SUSPENSION BAR: 0.060 inch $\pm$ .005 inch

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lugs are an integral part of both the pendant and suspension bar.

3. The connecting links shall be formed from 0.042 inch $\pm$ 0.002 inch diameter wire and shall have an outside diameter of 3/16 inch $\pm$ 1/64 inch.

4. The attaching device shall be prong and clutch type. Nickel plated flat ball clutches shall be used for Dash No. -2 and red brass flat ball clutches shall be used for Dash No. -1 and -3. The prongs shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 1-7/16 inch $\pm$ 1/16 inch apart.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:04Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH
Navy - MC

Preparing activity:
Army - IH
(Project No. 8455-2009-100)

Review activities:
DLA - CT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:04Z
Check the source to verify that this is the current version before use.