INCH-POUND

MIL-B-8906C
AMENDMENT 2
5 FEBRUARY 1998

MILITARY SPECIFICATION

BOLT, ALLOY STEEL, SHEAR AND TENSILE (132 KSI MIN FSU AND 220 KSI MIN FTU), 450°F, SPLINE DRIVE

This amendment forms a part of MIL-B-8906C, dated 18 APRIL 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* Delete paragraph 3.2

Rewrite paragraph 3.2 to read: "3.2 This paragraph left intentionally blank."

PAGE 11

Paragraph 3.10.3: Delete "average" and substitute "minimum," i.e. average fatigue life of 65,000 cycles should be minimum fatigue life of 65,000 cycles.

PAGE 13

* Delete paragraph 4.2

Rewrite paragraph 4.2 to read: "4.2 Classification of inspections. The examination and testing of bolts shall be classified as quality conformance inspection (see 4.4)."

- Delete paragraph 4.3 and Table VI.
-

PAGE 14

* Delete paragraph 4.3.1, 4.3.2 and 4.3.3

AMSC N/A FSC 5306
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:41Z
Check the source to verify that this is the current version before use.

* Delete paragraph 6.3 and 6.3.1 and replace with the following:

"6.3 This paragraph left intentionally blank."

"6.3.1 This paragraph left intentionally blank."

Custodians:
Army - AV
Navy - AS
Air Force - 99

Review activity:
Army - AR, MI
Air Force - 82

Preparing Activity:
DLA-IS

(Project 5306-2019)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:41Z
Check the source to verify that this is the current version before use.