MIL-V-8883B

10 JUNE 1965

Superseding
MIL-V-008883A(Wep)
3 December 1962
MIL-V-8883(ASG)
7 June 1960

MILITARY SPECIFICATION

VALVES, INLET, LIFE RAFT

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers the requirements for two types of life raft inlet valves.

1.2 Classification.- Valves covered by this specification are classified as follows (see 6.2):

Type I - Valve, check, inlet, one-man life raft - MS29599

Type II - Valve (with or without check), inlet, 20-man life raft - MS29600

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

BB-C-101	Carbon Dioxide (CO_2); Technical and U.S.P.
QQ-B-626	Brass, Leaded and Non-Leaded; Rods, Shapes, Forgings and Flat Products with Finished Edges (Bars, Flat Wire and Strip)
QQ-W-423	Wire, Steel, Corrosion-Resisting

Military

MIL-A-5539	Adhesive, Natural Rubber or Synthetic Natural Rubber
MIL-R-6855	Rubber; Synthetic, Sheet, Molded, and Extruded
MIL-L-9131	Life Rafts, Inflatable, Twenty Man
MIL-V-25492	Valve, Inflation, One-Man Life Raft

FSC 4220

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED. TEST METHOD STD. NO. 151	Metals; Test Methods
FED. TEST METHOD STD. NO. 601	Rubber; Sampling and Testing

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification Marking of US Military Property
MS26545	Cylinders - Compressed Gas, Nonshatterable
MS29599	Valve, Check, Inlet, One-Man, Life Raft, Type I
MS29600	Valve, Inlet, 20 Man, Life Raft, Type II

DRAWINGS

Bureau of Naval Weapons

63A120H1	Inflation Equipment, Carbon Dioxide, for Multiplace Life Rafts

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Qualification.- The valve furnished under this specification shall be a product which has been subjected to and which has passed the qualification tests specified herein, and which has been listed on or approved for listing on the applicable Qualified Products List. Each type of valve shall be qualified separately.

3.2 Materials.- Materials shall conform to applicable specifications as specified herein. Materials which are not covered by applicable specifications or which are not specifically described herein shall be of the best quality and suitable for the purpose intended. Unless otherwise specified, the elastomeric materials used in the construction of the valve shall have been manufactured not more than 12 months prior to the date of delivery of the valves to the Government or a life raft manufacturer.

3.2.1 Rubber.-

3.2.1.1 Patch.- The rubber patch shall be natural rubber having a Shore durometer hardness of 55 ±5. The composition shall be such that it shall have good cementability properties when used with the adhesive conforming to class 1 or 2 of MIL-A-5539.

3.2.1.2 Valve check.- The rubber used in conjunction with the valve check shall be synthetic conforming to MIL-R-6855, class 2, grade 60.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

3.2.2 Metal.-

3.2.2.1 Valve stem, valve check, and swivel nut.- The valve stem, valve check, and swivel nut shall be fabricated from brass conforming to QQ-B-626, composition 22, half hard.

3.2.2.2 Swivel nut retaining ring (type II).- The swivel nut retaining ring for type II valve shall be fabricated from brass conforming to QQ-B-626 composition 22, half hard.

3.2.2.3 Spring.- The spring shall be fabricated from corrosion-resistant steel conforming to QQ-W-423, composition 302, condition B. The diameter of the wire shall be of a suitable thickness so that the valve shall function properly in service and shall conform to the performance requirements of this specification.

3.3 Design.-

3.3.1 Type I.- The type I valve assembly shall be designed in accordance with MS29599 and shall consist of a spring-loaded check contained in the valve stem.

3.3.2 Type II.- The type II valve assembly shall be designed in accordance with MS29600, with or without a spring-loaded check in accordance with the specified MS dash number. The type II valve shall contain a free-swiveling coupling nut attached to the stem.

3.4 Construction.-

3.4.1 Metal components.- All the exposed edges of the valve metal components shall be smoothly rounded so that all sharp edges or burrs are removed.

3.4.2 Rubber patch.- A patch fabricated from the rubber (3.2.1.1) shall be securely molded to the valve stem. The bonding material shall not affect the rubber patch or metal and shall not exude or become stiff or brittle. The side of the patch facing the threaded portion of the stem shall be flat for cementing to the innerside of the raft tube.

3.4.3 Inlet diffuser.- The valve shall be of the nonrecoiling type with four discharge holes. The inlet diffuser shall be completely covered, except for the discharge holes, with a heavy layer of the same material as the patch in order to prevent chafing of the raft tube cloth.

3.4.4 Replacement.- Replacement of any expendable parts shall be possible from the inlet end of the valve stem which is attached to the cylinder valve, without removing the valve from the raft after installation.

3.5 Interchangeability.- All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

3.6 Performance.-

3.6.1 Patch adhesion.-

3.6.1.1 As received.- The molded rubber patch shall not strip away from the valve in any instance, and the rubber patch shall not fail below 75 pounds, when inspected as specified in 4.6.2.2.

3.6.1.2 After aging.- The molded rubber patch shall not strip away from the valve in any instance nor shall the rubber patch fail below 65 pounds when inspected as specified in 4.6.2.3.

3.6.2 Valve check seating force.- The valve check shall become unseated and permit the flow of gas at a pressure not less than 10 or greater than 15 pounds per square inch gage (psig), when tested as specified in 4.6.2.4.

3.6.3 Gas flow.-

3.6.3.1 Type I.- The type I valve shall discharge in not more than 5 seconds at the specified temperature, the percentage of carbon dioxide listed below, when inspected as specified in 4.6.2.5.1 or 4.6.2.5.2, as applicable. The gas shall pass through all the discharge holes.

Temperature	Minimum percent discharge
70° ±2° F	90
-20° ±2° F	50

3.6.3.2 Type II.- The type II valve shall discharge at least 90 percent of the carbon dioxide in the time and temperature listed below, when inspected as specified in 4.6.2.6.1 or 4.6.2.6.2, as applicable. The gas shall pass through all the discharge holes.

Temperature	Discharge time, maximum
70° ±2° F	17 seconds
-40° ±2° F	40 seconds

3.6.4 Back pressure leakage.- The valves shall not leak when tested as specified in 4.6.2.7.

3.6.5 Vibration.- After being vibrated as specified in 4.6.2.8.1 or 4.6.2.8.2, as applicable, the valve shall be inspected and conform to the requirements for gas flow at 70° F, 3.6.3.1, or 3.6.3.2, as applicable, valve check seating force, 3.6.2, and back pressure leakage 3.6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

3.6.6 Salt spray.- After being exposed to salt spray as specified in 4.6.2.9, there shall be no evidence of corrosion or damage which will adversely affect the operation. The swivel nut (type II) shall operate freely and not become frozen. The valve shall then be inspected and conform to the requirements for gas flow, at 70° F, 3.6.3.1 or 3.6.3.2, as applicable, valve check seating force, 3.6.2, and back pressure leakage, 3.6.4.

3.7 Identification of product.- The valves shall be identified by marking as shown on the applicable MS in accordance with MIL-STD-130.

3.8 Workmanship.- The valves shall be uniform in quality and shall be free from irregularities or defects which could adversely affect performance, reliability, or durability. Because of the emergency use of this equipment, the importance of providing a product of uniform excellent quality cannot be overemphasized.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are needed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections.- The examinations and tests to be performed on the valves are classified as:

(a) Qualification inspection (4.3)
(b) Quality conformance inspection (4.4)

4.3 Qualification inspection.- Qualification inspection shall consist of performing all the examinations and tests of this specification.

4.3.1 Qualification samples.- The qualification samples shall consist of:

Five valves of each type for which qualification is desired. The type II valves shall contain the checks.

The qualification samples shall be forwarded to the Supply Officer, Naval Air Engineering Center, Philadelphia, Pa., 19112, Attention: Director, Aerospace Crew Equipment Laboratory. The samples shall be plainly identified by securely attached durable tags marked with the following information:

Samples for qualification testing
VALVE, INLET, LIFE RAFT
Type for which qualification is desired
Manufacturer's designation or number
Name of manufacturer
Submitted by (name) (date) for qualification testing in accordance with MIL-V-8883B under authorization (reference authorizing letter and number)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.- Quality conformance inspection shall consist of performing the examinations and tests specified in table I.

4.4.1 Inspection lot.-

4.4.1.1 Valves.- An inspection lot size shall be expressed in units of one valve of one type made essentially under the same conditions and from the same components and materials. The sample unit shall be one valve of one type.

4.4.1.2 Preparation for delivery.- An inspection lot size shall be expressed in units of one fully prepared shipping container, containing valves of one type, fully prepared for delivery from essentially the same materials and components. The sample unit shall be one shipping container, containing valves of one type, fully prepared for delivery with the exception that it need not be sealed.

4.4.2 Sampling.- Sample size and acceptance criteria shall be as specified in table I. Sampling shall be in accordance with MIL-STD-105.

4.5 Test conditions.-

4.5.1 Temperature and pressure.- Unless otherwise specified, inspections shall be conducted at local ambient temperature and barometric pressure. Corrections shall be made to provide agreement with the temperature and pressure calibration of the instruments. Inspection data provided by any instrument not calibrated to normal temperature and pressure (NTP) conditions shall be corrected to determine NTP requirements. NTP conditions are 29.92 inches of mercury and 70° F.

4.6 Inspection methods.-

4.6.1 Examinations.-

4.6.1.1 Valves.- Each valve shall be examined visually for critical defects to determine conformance to this specification. Each valve, selected as a sample unit from the lot, shall be thoroughly checked dimensionally and examined visually for minor defects to determine conformance to this specification. The classification and list of defects,tables II and III, shall be used to classify and enumerate the defects.

4.6.1.2 Preparation for delivery.- Sample shipping containers shall be examined to determine that the packaging, packing, and marking conform to the applicable level specified in the contract or order. Each instance of nonconformance shall be enumerated as a defect.

4.6.2 Tests.-

4.6.2.1 Shore durometer hardness.- The Shore durometer hardness of the elastomeric material used in the patch shall be determined in accordance with Method 3021 of Fed. Test Method Std. No. 601.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

TABLE I. Quality conformance examinations, tests, sample size, and acceptance criteria

Inspection	Type of inspection	Paragraph		Sample size	Acceptance criteria
		Requirement	Test method		
Examination of valve (see table II)	Critical Minor	---	4.6.1.1	Every valve Inspection level II	Critical defects: Reject all defective units Minor defects: AQL of 2.5 defects per 100 units
Examination of dimensions	Critical	MS29599 MS29600	4.6.1.1	Inspection level S-2 1/	Acceptance number - zero Rejection number - one
Examination of preparation for delivery	Major	---	4.6.1.2	Inspection level S-2	Total AQL of 4.0 defects per 100 units
Patch adhesion, as received	Critical	3.6.1.1	4.6.2.2	Inspection level S-1 1/	Acceptance number - zero Rejection number - one
Valve check seating force 3/	Critical	3.6.2	4.6.2.4	Every valve	Reject all defective valves
Gas flow, type I, at 70° F	Critical	3.6.3.1	4.6.2.5.1	Inspection level S-1 1/	Acceptance number - zero Rejection number - one
Gas flow, type I, at -20° F	Critical	3.6.3.1	4.6.2.5.2	Inspection level S-1 1/	Acceptance number - zero Rejection number - one
Gas flow, type II, at 70° F	Critical	3.6.3.2	4.6.2.6.1	Inspection level S-1 1/,2/	Acceptance number - zero Rejection number - one
Gas flow, type II, at -40° F	Critical	3.6.3.2	4.6.2.6.2	Inspection level S-1 1/,2/	Acceptance number - zero Rejection number - one
Back pressure leakage 3/	Critical	3.6.4	4.6.2.7	Inspection level S-1 1/	Acceptance number - zero Rejection number - one
Weight	Major	MS29599 MS29600	4.6.2.10	Inspection level S-1 1/	Acceptance number - zero Rejection number - one

1/ The sample size shall be based only on the applicable sample size code letter corresponding to the specified inspection level of MIL-STD-105.
2/ The sample size shall be doubled since two valves are required to be tested simultaneously.
3/ These inspections are not applicable when the type II valve is procured without the valve check.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for visual examination of the inlet valves

Critical	Minor
1. Material imperfections - foreign matter embedded. 2. Number of discharge holes not as specified (see 3.4.3). 3. Any discharge hole blocked. 4. Surface - unclean, rough, misaligned, or containing cracks, nicks, sharp edges, or other flaws. 5. Any component missing, malformed, fractured, or otherwise damaged. 6. Any component loose, detached, or otherwise not securely retained. 7. Incorrect assembly or improper positioning of the components. 8. Any functioning part that works with difficulty. 9. Faulty workmanship or other irregularities. 10. Replacement of any expendable part not possible from the inlet end of the valve. 11. Finish of any component not as specified. 12. Threads stripped, torn, broken, or otherwise damaged.	201. Marking - missing, insufficient, incorrect, illegible, not permanent or misplaced.

TABLE III. List of defects for the finished dimensions of the inlet valve

Finished dimensions	Defect
Measure the valve stem, threads, rubber patch, and swivel nut, as applicable.	Any measurement deviating from the dimensions and tolerances as specified in MS29599 and MS29600, as applicable, shall be enumerated as a dimensional defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

4.6.2.2 Patch adhesion as received.- The rubber patch of the valve assembly shall be cut into six equal segments, along the radius lines, completely through to the valve stem. Two diametrically opposite segments shall be clamped in the jaws of a suitable testing apparatus with movable jaws that operate under no load at a rate of 2 ±1/8 inches per minute. The jaws shall be separated until failure occurs (see 3.6.1.1). The test shall be repeated for each remaining two diametrically opposite segments.

4.6.2.3 After aging.- The inlet valve assembly shall be exposed at 170° ±2° F for 168 ±1/4 hours. The valve shall then be exposed to a temperature of 75° ±5° F and after a minimum of 16 hours and not more than 96 hours, the patch adhesion after aging shall be determined as specified in 4.6.2.2.

4.6.2.4 Valve check seating force.- A source of oil-free and water-free air shall be connected to the inlet side of the valve. The valve shall be submerged in water to provide at least 1 inch of water above all parts of the valve. The gas pressure shall be increased until a flow of gas through the valve is produced. The pressure required to produce a flow through the valve shall be not less than 10 nor more than 15 psig.

4.6.2.5 Gas flow, type I.-

4.6.2.5.1 At 70° ±2° F.- The type I inlet valve shall be assembled to a cylinder valve conforming to MIL-V-25492 and to a MS26545B1C0020 or MS26545B3C0020 cylinder charged with 0.50 ±0.01 pounds of carbon dioxide conforming to BB-C-101, type I, grade B. The assembled inflation equipment shall be exposed at 70° ±2° F for 24 ±1/4 hours and shall then be weighed on a scale or balance capable of weighing to the nearest 0.05 of an ounce. The carbon dioxide filled cylinder shall be held in a horizontal position and activated. At the end of 5 seconds, the time being measured from the instant the carbon dioxide filled cylinder is activated, the cylinder valve shall be returned to the closed position and the assembly reweighed. The inlet valve shall also be observed to determine if the carbon dioxide passes through all the discharge holes.

4.6.2.5.2 At minus 20° ±2° F.- The type I inlet valve shall be assembled and inspected as specified in 4.6.2.5.1, except that the assembled inflation equipment shall be exposed and inspected at -20° ±2° F and the carbon dioxide filled cylinder shall be held in a vertical position with the cylinder valve end down.

4.6.2.6 Gas flow, type II.-

4.6.2.6.1 At 70° ±2° F.- Two type II inlet valves shall be attached to the non-vented "Y" manifold, remote pull cable, and cylinder valve specified on drawing 63A120H1. A MS26545B1C0415 or MS26545B3C0415 cylinder charged with 9.20 ±0.6 pounds of carbon dioxide conforming to BB-C-101, type I, grade B, shall be attached to the cylinder valve. The assembled inflation equipment shall be exposed at a temperature of 70° ±2° F for 24 ±1/4 hours and then weighed on a scale or balance capable of weighing to the nearest 0.05 of an ounce. The carbon dioxide filled cylinder shall be held in a horizontal position and activated. At the end of the time specified in 3.6.3.2, the time being measured from the instant the carbon dioxide filled cylinder is activated, the cylinder valve shall be returned to the closed position and the assembly reweighed. The inlet valves shall also be observed to determine if the carbon dioxide passes through all the discharge holes of each inlet valve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

4.6.2.6.2 At minus 40 ±2° F.- Two type II inlet valves shall be assembled and inspected as specified in 4.6.2.6.1, except that the assembled inflation equipment shall be exposed and inspected at -40° ±2° F and the carbon dioxide filled cylinder shall be held in a vertical position with the cylinder valve end down.

4.6.2.7 Back pressure leakage.- A source of oil-free and water-free air shall be connected to the outlet side of the valve. The valve shall be submerged in water so that all parts of the valve are at least 1 inch below the surface. A pressure of 1.5 psig ±0.1 shall be applied to the outlet side for 30 seconds. Under these conditions, there shall be no evidence of leakage.

4.6.2.8 Vibration.-

4.6.2.8.1 Type I.- The type I valve shall be connected to the inflation equipment specified in 4.6.2.5.1 and vibrated at a double amplitude of 0.031 to 0.062 inch and a frequency of 3,200 to 3,500 cycles per minute for at least 24 hours. After completion of the vibration period, the valve shall be subjected to and pass the test specified in 4.6.2.4, 4.6.2.5.1, and 4.6.2.7.

4.6.2.8.2 Type II.- The type II valve shall be connected to the inflation equipment specified in 4.6.2.6.1 and vibrated at a double amplitude of 0.031 to 0.062 inch and a frequency of 3,200 to 3,500 cycles per minute for at least 24 hours. After completion of the vibration period, the valve shall be subjected to and pass the test specified in 4.6.2.4, 4.6.2.6.1, and 4.6.2.7.

4.6.2.9 Salt spray.- The valve shall be subjected to salt spray in accordance with Method 811 of Fed. Test Method Std. No. 151 for 100 hours. The inlet and discharge holes shall be plugged to prevent entry of the salt spray during this exposure. After completing the salt spray exposure, the valve shall be examined for corrosion and other damage that could affect the operation of the valve, and for free movement of the swivel nut (type II) by hand operation. The valve shall then be subjected to and pass the tests specified in 4.6.2.5.1 or 4.6.2.6.1, as applicable for the type of valve, 4.6.2.4, and 4.6.2.7.

4.6.2.10 Weight.- The weight of the valves shall be determined on any scale or balance capable of weighing to the nearest 0.05 of an ounce.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Intended use.- The inlet valves are intended for use as a component of the mechanical inflation system for the one-man and 20-man life rafts conforming to MIL-L-8664 and MIL-L-9131, respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- Procurement documents should specify:

(a) Title, number, and date of this specification.

(b) Type of valve (see 1.2). If type II is specified, whether the valve check is required (see MS29600 for part number).

(c) Applicable levels of packaging, packing, and marking required (see 5.1).

6.3 Qualification.- With respect to products requiring qualification, awards will be made only for such products as have, prior to the bid opening date, been tested and approved for inclusion in the applicable Qualified Products List, whether or not such products have actually been so listed by that date. The attention of suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the qualified products list is the Chief, Bureau of Naval Weapons, Department of the Navy, Washington, D. C. 20360; however, authorization for qualification of products shall be obtained from the Commanding Officer, Naval Air Engineering Center, Philadelphia, Pennsylvania 19112, Attention: Director, Aerospace Crew Equipment Laboratory. Prior to submission of the samples for qualification inspection, the manufacturer shall submit a request to the Aerospace Crew Equipment Laboratory indicating a date on which the samples can be forwarded and also request an authorization number to accompany the samples.

6.4 Data.- For the information of contractors and contracting officers, any of the data specified in applicable documents listed in Section 2 of this specification, or referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List), which will be attached to and made a part of the contract or order. NavWeps Form 4200/15 (Drawings, Lists, and Specifications Required) will be attached where applicable.

Custodians:
Army - MO
Navy - WP
Air Force - (11)

Preparing activity:
Navy - WP

Project No. 4220-0063

Reviewer activities:
Army - MO
Navy - WP
Air Force - (11), (84)

User activities:
Army -
Navy -
Air Force -

Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DoD Standardization Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

MIL-V-8883B VALVES, INLET, LIFE RAFT

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ Direct Government Contract ☐ Subcontract

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)

SUBMITTED BY (Printed or typed name and activity) DATE

DD Form 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:39Z
Check the source to verify that this is the current version before use.