MILITARY SPECIFICATION

REFILL KIT, M58A1 PERSONAL DECONTAMINATION KIT TRAINING AID

This amendment forms a part of MIL-R-51472A(EA), dated 9 October 1986, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.3: Delete paragraph in its entirety.

3.4: Delete paragraph in its entirety.

PAGE 4

3.12: Delete paragraph in its entirety.

3.13: Delete "Ampoule screen" and substitute "Tube glass screen".

3.15: Add new paragraph as follows:

"3.15 Decon 2 packet solution content. The pad in the decon 2 packet shall contain 3.6 to 5.2 g of a solution consisting of 12 ± 2 percent by weight 2-propanol conforming to TT-I-735, with the remainder water conforming to Drawing 5-77-2267 when tested as specified in 4.4.4.9."

PAGE 5

4.3.2.2, under "TABLE I. Preproduction inspection":

Delete requirements for "Ampoule leakage", "Ampoule fill" and "Ampoule tip" in their entirety.

AMSC N/A FSC 6910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

Add new requirement as follows:

Requirement: "Decon 2 packet solution content (3.15)"
Sample size: "10"
Accept/reject criteria: "acc 0, rej 1"
Test paragraph: "4.4.4.9"

Delete requirement title "Ampoule screen" and substitute "Tube glass screen".

Delete "***Same sample packets used for ampoule leakage test may be used."

PAGE 7

4.4.3.1, under "TABLE II. Quality conformance inspection":

Delete requirements "Ampoule leakage", "Ampoule fill" and "Ampoule tip" in their entirety.

Delete requirement title "Ampoule screen" and substitute "Tube glass screen".

Add new requirement as follows:

Requirement: "Decon 2 packet solution content (3.15)"
Sample size: "15, prior to assembly in refill kits"
Accept/reject criteria: "acc 1, rej 2"
Test paragraph: "4.4.4.9"

Delete "***Same sample packets used for ampoule leakage test may be used."

PAGE 8

4.4.4.1: Delete paragraph in its entirety.

4.4.4.2: Delete paragraph in its entirety.

PAGE 9

4.4.4.3: Delete "Submerge the packet for at least 60 seconds in water heated to 58.8° ± 1.5°C." and substitute "Submerge the packet for at least 30 seconds in ambient temperature water in a transparent vacuum tank under a vacuum of 7 ± 1 pounds per square inch."

4.4.4.6: Delete paragraph in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

4.4.4.7: Delete "Ampoule screen" and substitute "Tube glass screen".

4.4.4.9: Add new paragraph as follows:

"4.4.4.9 Decon 2 packet solution content. Weigh the packet to the nearest 0.01 g. Open the packet and remove the towelette (pad) and nylon mesh with glass tubes enclosed. Place the pad, nylon mesh with glass tubes and opened packet in an air circulating oven and dry at 105 ± 2°C for 60 ± 5 minutes. Weigh the entire packet, nylon mesh with glass tubes and pad to the nearest 0.01 g. Calculate the weight of the solution on the pad as follows:

$$\text{Weight of solution} = A-B$$

Where: A = Weight of packet 2 (pad, nylon mesh with glass tubes and packet) before drying, in grams and
B = Weight of packet 2 (pad, nylon mesh with glass tubes and packet) after drying, in grams."

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 6910-A005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.