INCH-POUND
MIL-B-18/206D
W/AMENDMENT 1
18 February 2022
SUPERSEDING
MIL-B-18/206D
22 November 2010

MILITARY SPECIFICATION SHEET

BATTERY, DRY, BA-331/U

INACTIVE FOR NEW DESIGN AFTER
10 AUGUST 1998 AND IS NO LONGER USED,
EXCEPT FOR REPLACEMENT PURPOSES.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-B-18.




FIGURE 1. Battery dimensions.

AMSC N/A FSC 6135
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:53Z
Check the source to verify that this is the current version before use.

Ltr	INCHES	INCHES	MM	MM
	Min	Max	Min	Max
A	.313	---	7.62	---
B	.188	---	4.78	---
C	.266	.328	6.76	8.33
D	.563	.625	14.30	15.88
E	.078	.110	1.98	2.79
F	.469	.531	11.91	13.46
G	.937	1.063	23.80	27.00
H	.078	.110	1.98	2.79
J	.219	.281	5.56	7.14
K	.063	.125	1.60	3.17
L	1.312	1.469	33.32	37.31
M	.063	.125	1.60	3.18

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.031 inch (0.794 mm).
4. Square or round corners are optional.
5. Alternate terminal construction as shown is allowable but dimensions in the top view, other than those shown on the alternate view, shall apply.
6. Positive and negative terminals are alike.
7. Marking to be in accordance with MIL-B-18.

FIGURE 1. Battery dimensions - Continued.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Nominal voltage: 15 volts.

Usual number and type of cells: 10 “FL-2” cells.

Usual cell connection: Series.

Terminals: Flat surface.

Weight (maximum): 1.0 ounces.

Capacity tests: When the battery is tested in accordance with the methods of examination and test of this specification, the minimum capacity-test requirements shall be not less than the minimum time specified for SLD or SLT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:53Z
Check the source to verify that this is the current version before use.

First article inspection in accordance with MIL-B-18:

Visual and mechanical (external).
Battery voltage.
Vibration test.
Mechanical-shock test in accordance with MIL-STD-202-213, test condition I.
Insulation resistance test in accordance with MIL-STD-202-302, test condition B, tolerance ±20 volts.
Capacity, D (without storage).
Jacket integrity test.

Conformance inspection in accordance with MIL-B-18:

Visual and mechanical (external).
Battery voltage.
Insulation resistance test in accordance with MIL-STD-202-302, test condition B, tolerance ±20 volts.
Vibration test.
Mechanical-shock test in accordance with MIL-STD-202-213, test condition I.
Jacket integrity test.
Electrode leakage.
Capacity, D and T.

Method of examination and test:

Capacity tests: See requirements for capacity specified herein.

Storage:

Test	Period
D	9 months
T	90 days

Discharge: The battery shall be discharged through 15,000 ohms for 12 hours per day, 5 days per week. This cycle shall be repeated 5 days per week continuously to a test-end voltage of 11.3 volts.

Closed circuit voltage: Use TS-183 ( )/U test per special marking or, with minimum permissible voltage as specified for TS-183 ( )/U, use a load resistance value of 18,750 ohms.

Special marking on each unit package:

TO TEST THIS BATTERY WITH TS-183 ( )/U:

USE JACK NO.	MINIMUM PERMISSIBLE VOLTAGE
19	13.3

Unless expressly authorized, this test information shall apply to Army and Air Force applications only.

Part or Identifying Number (PIN): BA-331/U, see 1.2 of MIL-B-18.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:53Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-B-18, this document references the following:

MIL-STD-202-213 MIL-STD-202-302

Custodians:
Navy - SH
DLA - CC

Preparing activity:
DLA - CC

(Project 6135-2021-016)

Review activities:
Navy - MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:53Z
Check the source to verify that this is the current version before use.