FEDERAL SPECIFICATION

LADDERS, STRAIGHT, EXTENSION, AND TRESTLE

This amendment, which forms a part of Federal Specification RR-L-91D, dated October 27, 1970, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

Add a new paragraph under paragraph 3.1.4 as follows:

3.1.4.3 Shape. Unless otherwise specified (see 6.2), rungs shall be round or D shaped in cross section at the manufacturers option. Width of the flat on D shaped rungs shall be 7/8 inch or greater.

Paragraph 3.1.8, add the following to end of paragraph:

Flat pads and shoes shall be an insulating material, rubber, or rubber-like plastic material.

PAGE 4

Paragraph 3.2.5, add the following to end of paragraph:

Rope shall be not less than 1/4 inch in diameter.

PAGE 5

Add a new paragraph under paragraph 3.3 as follows:

3.3.6 Extension locking device. The extension device shall be designed to withstand all ladder load tests.

PAGE 6

Add a new paragraph under paragraph 3.4.2 as follows:

3.4.2.4 Rope. Rope used with pulley shall have a minimum breaking strength of 560 pounds (see 4.4.2.5).

PAGE 10

Add a new paragraph as follows:

4.4.2.5 Pulley rope. Specimen shall be any convenient length. Apply a static load to one end of the rope with the opposite end secured, or apply the load in a tensile testing machine using a low rate of travel between cross-heads (see 3.4.2.4).

PAGE 12

Paragraph 6.2, add a new subparagraph as follows:

(1) Cross-sectional shape of rungs for straight and extension ladder, when required (see 3.1.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:08Z
Check the source to verify that this is the current version before use.

Add a new paragraph under paragraph 6.5 as follows:

6.5.7 S1 flat pad swivel safety shoes. When using ladders on hard dry surfaces such as concrete or asphalt, position the safety shoe with the flat pad bearing on the dry surface. When using ladders on grass lawns or soft ground rotate the flat pad to an up position parallel to the side rails, then push with foot at one end then the other end of the bottom rung to imbed the side rails in the ground, or position the flat pads of the safety shoes on a 2 by 6 inch wood board approximately 6 inches wider than the overall ladder width.

MILITARY INTERESTS:

DOD has waived coordination or revisions and amendments to this Federal Specification until further notice.

Preparing activities:

GSA-FSS

Civil Agency Coordinating Activities:

COMMERCE - NBS
GSA - FSS
TVA - TVA

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:08Z
Check the source to verify that this is the current version before use.