FEDERAL SPECIFICATION

MATTRESSES, BED, INNERSPRING

This amendment, which forms a part of Federal Specification V-M-96G, dated April 11, 1975, was approved by the Commissioner, Federal Supply Service, General Services Administration for the use of all Federal agencies.

PAGE 4

3.3.5.2, line 5: Delete "18.0 percent" and substitute "34.0 percent".

PAGE 6

Add the following new paragraph:

"3.3.15.1 Alternate ventilators. As an alternate, ventilators may be supplied with the following requirements:

a. One or two piece construction.
b. Ventilator cap made from 0.010 ± 0.003 inch thick brass.
c. Ventilator shanks (tube) made from 0.012 ± 0.003 inch thick brass.
d. Outside diameter of cap 1.000 ± 0.003 inch.
e. Outside diameter of shank 0.758 ± 0.002 inch (hole size 0.728 + 0, -0.002 inch before finishing).
f. Length of shank shall be of sufficient length of effect a secure clinch of the border without cutting the surrounding ticking.
g. A minimum of 50 percent of the face of ventilator shall be perforated with not less than 61 holes of 0.055 ± 0.003 inch diameter.
h. Bottom of shanks (tube) made with 13 equally spaced scores (see 4.4.1.2)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

PAGE 17

Table III, "Weight pounds (min)" column: Add "3/".

PAGE 18

Table IV, "Weight pounds (min)" column: Add "3/".

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD
Navy - SA, MC
DSA - DM
DPSC - CT

User activity:

Navy - SH

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS

Project No. 7210-0209

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.