MIL-C-20/18C
25 May 1973
SUPERSEDING
MIL-C-0020/18B(USAF)
14 August 1972, and
MIL-C-20/18A
2 June 1961


MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (TEMPERATURE COMPENSATING) (INSULATED), NON-ESTABLISHED RELIABILITY, STYLE CC52

INACTIVE FOR NEW DESIGN AFTER DATE OF THIS SPECIFICATION. SEE MIL-C-20/45 FOR ITEMS PREVIOUSLY COVERED IN MIL-C-0020/18B(USAF).

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the capacitors described herein shall consist of this document and the latest issue of Specification MIL-C-20.



INCHES	MM
.040	1.02
.050	1.52
.120	3.05
.125	3.18
.375	9.53
.550	13.97
1.250	31.75

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Leads shall be of tinned wire of .025±.002(.64±.05 mm) diameter.
4. This dimension shall be measured at the point of emergence of the leads from the body of the capacitor.

FIGURE 1. Style CC52 capacitors (insulated).

REQUIREMENTS:

Design and construction:
Dimensions and configuration: See figure 1.
Lead type: Radial.
DC rated voltage: 500 volts.
Operating temperature range: -55° to +125°C.
Characteristic: See table I.

Capacitance: Within tolerance specified (see table I).

Quality factor (Q): In accordance with MIL-C-20.

Dielectric withstanding voltage: In accordance with MIL-C-20.
Body insulation - Test II.

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:05Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.


Type designation [1]	Capacitance (pF)	Capacitance tolerance	Temperature coefficient shown as column head and tolerance envelope for temperature coefficient shown in column							
			C	H	L	P	R	S	T	U
CC52—H330-	33	FGJK	H	H						
CC52-H360-	36	FGJ	H	H						
CC52-H390-	39	FGJK	H	H						
CC52-H430-	43	FGJ	H	H	H					
CC52-H470-	47	FGJK	H	H	H	H	H			
CC52-H510-	51	FGJ	H	H	H	H	H			
CC52-H560-	56	FGJK			H	H	H	H		
CC52—620-	62	FGJ			G	G	H	H		
CC52—680-	68	FGJK				G	H	H	H	
CC52-H750-	75	FGJ					H	H	H	
CC52-H820-	82	FGJK						H	H	
CC52—910-	91	FGJ						H	H	J
CC52-101-	100	FGJK							H	J
CC52—111-	110	FGJ							H	J
CC52UJ121-	120	FGJK								J
CC52UJ131-	130	FGJ								J
CC52UJ151-	150	FGJK								J

[1] Complete type designation will include letter symbols to indicate capacitance tolerance, and where applicable, temperature coefficient, and tolerance envelope for temperature coefficient.

Life: In accordance with MIL-C-20, operating condition 1.

Marking:
Method I - In accordance with MIL-C-20, except for "JAN" brand.
Method II - In accordance with MIL-C-20 and as shown on figure 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:05Z
Check the source to verify that this is the current version before use.



1. The characteristic, capacitance, and capacitance tolerance shall be indicated on the capacitor by five spots of color. The color spots shall be applied so that the designation may be read clockwise. The diameter of the characteristic spot shall be at least twice that of any other spot, or the space between the first and last spots shall be at least three times the space between adjacent spots.

2. The MIL identifier (black spot) shall be applied to the capacitor body approximately in the center and on the reverse side of the capacitor body to which the color code is applied.

FIGURE 2. Color-code marking.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army -
Navy - OS
Air Force - 80
DSA - ES8

User activities:
Army -
Navy - AS, SH, MC
Air Force -

Preparing activity:
Air Force - 11

Agent:
DSA - ES

(Project 5910-1064-18)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:05Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

4950/TZS
Wright-Patterson AFB, Ohio 45433

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS L[illegible] E.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]-15T17:05Z
Check the source to verify that this is the current version before use.