INCH-POUND

MIL-PRF-20/28C
21 June 2001
SUPERSEDING
MIL-PRF-20/28B
9 May 1989

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (TEMPERATURE COMPENSATING), ESTABLISHED AND NON-ESTABLISHED RELIABILITY, STYLES CCR76 AND CC76

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the capacitors described herein shall consist of this specification and the latest issue of MIL-PRF-20.



CIRCUIT DIAGRAM

Inches	mm
.001	0.03
.005	0.13
.010	0.25
.016	0.41
.090	2.29
.160	4.06
1.250	31.75

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Lead diameter shall be .015 (0.38 mm) to .027 (0.69 mm).
4. Lead length may be a minimum of 1.00 inch (25.4 mm) long for use in tape and reel packaging, when specified in the ordering data.

FIGURE 1. Styles CCR76 and CC76 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:06Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Lead type: Axial.

Case type: Tubular, molded.

DC rated voltage: See table I.

Operating temperature range: -55°C to +125°C.

Characteristic: CG.

Failure rate level (CCR76 only): M (1.0 percent), P (0.1 percent), R (.01 percent) or S (.001 percent).

Thermal shock and voltage conditioning (CCR76 only): In accordance with MIL-PRF-20.

Capacitance: Within tolerance specified (see table I).

Dissipation factor: In accordance with MIL-PRF-20.

TABLE I. Capacitor characteristics.

Type designation 1/ 2/	Rated voltage (volts, dc)	Nominal capacitance (pF)	Capacitance tolerance	Type designation 1/ 2/	Rated voltage (volts, dc)	Nominal capacitance (pF)	Capacitance tolerance
CC-76CG820--	200	82	FGJ	CC-76CG431--	100	430	FGJ
CC-76CG910--	200	91	FGJ	CC-76CG471--	100	470	FGJ
CC-76CG101--	200	100	FGJ	CC-76CG511--	100	510	FGJ
CC-76CG111--	200	110	FGJ	CC-76CG561--	100	560	FGJ
CC-76CG121--	200	120	FGJ	CC-76CG621--	100	620	FGJ
CC-76CG131--	200	130	FGJ	CC-76CG681--	100	680	FGJ
CC-76CG271--	100	270	FGJ	CC-76CG751--	50	750	FGJ
CC-76CG301--	100	300	FGJ	CC-76CG821--	50	820	FGJ
CC-76CG331--	100	330	FGJ	CC-76CG911--	50	910	FGJ
CC-76CG361--	100	360	FGJ	CC-76CG102--	50	1000	FGJ
CC-76CG391--	100	390	FGJ				

1/ Complete type designation will include the following:
1st dash - Symbol “R” (for style CCR76) or dash will be deleted (for style CC76).
2nd dash - Applicable capacitance tolerance symbol.
3rd dash - Applicable failure rate level symbol (CCR76 only) or dash will be deleted (for style CC76).

2/ Capacitors deleted since previous revisions shall be replaced by selecting a capacitor with the nearest parameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:06Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage: In accordance with MIL-PRF-20.

Body insulation: Test II.

Solderability: In accordance with MIL-PRF-20.

Resistance to soldering heat: In accordance with MIL-PRF-20.

Life: In accordance with MIL-PRF-20, operating condition 2.

Marking: Method I of MIL-STD-1285, as shown in the following example:

JCG - "J" brand (ER only) (J); and characteristic (CG).

820 - Capacitance value.

GM1 - Capacitance tolerance (G); FR level, CCR76 only (M); and year code (1 for 2001).

ATM - Lot code (A); and trademark (TM).

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AV, MI
Navy - AS, MC, OS

Preparing activity:
DLA - CC

(Project 5910-2116-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:06Z
Check the source to verify that this is the current version before use.