NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-20/31A
AMENDMENT 1
23 October 1978

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (TEMPERATURE COMPENSATING), ESTABLISHED AND NON-ESTABLISHED RELIABILITY, STYLES CCR79 AND CC79

This amendment forms a part of Military Specification Sheet MIL-PRF-20/31A, dated 26 August 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Under requirements, delete: Failure rate level (CCR79 only) in its entirety and substitute:

"Failure rate level (CCR79 only): M(1.0%), P(0.1%), R(0.01%) or S(0.001%)."

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army -
Navy - OS
Air Force - 85
DLA - ES

User activities:
Army -
Navy - AS, SH, MC
Air Force -

Preparing activity:
Air Force - 11

Agent:
DLA - ES

(Project 5910-1284-2)

☆U.S. GOVERNMENT PRINTING OFFICE: 1978-603-022/5183

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:06Z
Check the source to verify that this is the current version before use.