NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-20/36E
AMENDMENT 1
21 April 1993

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (TEMPERATURE COMPENSATING), ESTABLISHED AND NON-ESTABLISHED RELIABILITY, STYLES CCR06 AND CC06

This amendment forms a part of MIL-C-20/36E, dated 6 May 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Solderability, delete in its entirety and substitute: "Solderability: The leads shall be solderable up to .020 inch (0.51 mm) from the body egress."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - OS
Air Force - 99
DLA - ES

User activities:
Navy - AS, MC, SH

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5910-1835-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:07Z
Check the source to verify that this is the current version before use.