MIL-B-49041(EL)
AMENDMENT 1
26 April 1977

MILITARY SPECIFICATION

BATTERY, DRY BA-1579/U

This amendment forms a part of Military Specification MIL-B-49041(EL), dated 31 May 1974.

PAGE 1

2.1, under the heading MILITARY for specifications change the title of MIL-B-55521 to "Batteries, Dry and Thermal, Packaging Of."

PAGE 3

3.5.3.3, following this paragraph add new subparagraph as follows:

"3.5.3.4 Open circuit voltage with deadweight load. - The battery shall have an open circuit voltage of 7.3 ± 0.5 volts when measured with a dead-weight load of 4.0 ± 0.1 pounds applied and at a temperature of 70°± 10°F (21.1° ± 5.6°C) (See 4.7.3.3)."

PAGE 9

4.2, under subparagraphs 4.2a, line 2, and 4.2c for items (1) and (2) delete "preparation for delivery" and substitute "packaging".

4.3, at the end of the paragraph add the word "humidity".

PAGE 10

TABLE II, under Groups I and II directly below the line for "Visual-mechanical examination" add the following line under appropriate headings:

(Examination & Test)	(Req. Para.)	(Method of Test Para.)
"Open circuit voltage with deadweight load	3.5.3.4	4.7.3.3"

PAGE 11

4.6.1, line 1: Delete "preparation for delivery" and substitute "packaging".

FSC 6135

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:45Z
Check the source to verify that this is the current version before use.

PAGE 13

TABLE IV, under Subgroup 3 above the line for "Open circuit voltage" add the following line under appropriate headings:

(Examination & Test)	(Req. Para)	(Method of Test Para.)	(AQL)
"Open circuit voltage with deadweight load	3.5.3.4	4.7.3.3	0.65%"

4.6.1.4.2, line 1: Change title to read "Preservation of supplies".

line 2: Delete "packaged" and substitute "packed".

line 3: Delete the word "Specification" and change the word "package" to "pack".

PAGE 14

4.6.1.4.3, first sentence: Delete in its entirety and substitute:

"Packing shall be level B in accordance with MIL-B-55521 (See 5.1)."

4.6.2, entire paragraph: Delete and substitute the following:

"4.6.2 Inspection of packaging. - Inspection of packaging shall be in accordance with the Quality Assurance Provisions of MIL-B-55521."

PAGE 15

4.7.3.2, following this paragraph add new paragraph as follows:

"4.7.3.3 Open-circuit voltage with deadweight load. - The battery shall be tested for the open-circuit requirement in 3.5.3.4. The test shall be performed by applying a deadweight load of 4.0 ± 0.1 pounds to the top surface of the terminal (negative) while the battery is in the vertical position. An approved digital readout voltmeter shall be used to measure the voltage. Testing is non-destructive and accepted batteries shall be returned to the inspection lot."

PAGE 16

4.7.10, line 4: Delete "32,000" and substitute "32,500".

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:45Z
Check the source to verify that this is the current version before use.

PAGES 16 and 17

4.7.9, 4.7.10 and 4.7.11, in each of these three paragraphs delete the last two sentences and substitute the following:

"Voltage monitoring using an approved digital readout voltmeter shall be performed a minimum of once every ten (10) minutes of run-down time, and printout for the first 48 hours shall be at least once an hour. Printout data after the first 48 hours shall be obtained at least once a day."

PAGE 18

SECTION 5: Delete this section in its entirety and substitute the following:

"5. PACKAGING

5.1 Packaging requirements. - Packaging requirements shall be in accordance with MIL-B-55521."

6.1, item (c): Delete in its entirety.

6.1.1, line 1: Delete ", packing and marking" and substitute "requirements".

Custodian:
Army-EL

Review activity:
Army-PA

Preparing activity:
Army-EL
(Project 6135-A145)

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:45Z
Check the source to verify that this is the current version before use.