MILITARY SPECIFICATION

MINE, ANTITANK, PRACTICE: XM79 ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings, and provides Quality Assurance Provisions for the fabrication of parts, assembling and packing for one type of mine designated as Mine, Antitank, Practice: XM79.

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Asssurance Provisions, General Specificcation For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspections By Attributes (ABC-STD-105)

FSC: 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESERACH AND DEVELOPMENT COMMAND (ARRADCOM)

9243805	-	Pkg & Mkg for Shipping & Storage Container, Mine: XM619, for Mine, AT: HE, XM75; Mine, AP: HE, XM74; or Mine, AT, Practice: XM79 in Plastic Ammunition Center: PA-83
9317994	-	Mine, Antitank, Practice: XM79
9333791	-	Pkg for Plastic Ammunition Container: PA-83, for Mine, AP: HE, XM74 or Mine, Antitank, Practice: XM79.

U.S. ARMY MATERIAL DEVELOPMEMT AND READINESS COMMAND (ARRCOM)

19-48-4116/95M-20PA 1002	- Unitization Procedures for Boxed Ammunition and Components on 4-WAY ENTRY PALLETS.

(Copies of specifications, standards, drawings, and publications required by Contractors in connection with specification procurement functions should be obtained from the procuring office or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specfication and standards.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (Dwg.) 9317994 and all associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Push out test. After staking, the Lid shall withstand an push out LOAD of 2000 pounds (lbs) minimun (min), without disassembling. The examination shall be conducted as specified in 4.5.1.

3.4 First article inspection. This specification contains technical provisions for First Article Inspection. Requirements for submission of First Article Samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated and assembled in a through, workmanlike manner, and all manufacturing, processing, and assembling operations shall be correctly performed. All parts and assemblies shall be clean, free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any part, nor shall the parts be contamined by the cleaning agent exterior surface coating shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in the quantities as indicated.

PART DESCRIPTION	DRAWINGS	QUANTITY
Lid	9317996	15
Body	9317995	15
Mine, Antitank, Practice: XM79	9317994	15

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63380(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Mine, Antitank, Practice: XM79				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Lid				
	(Dwg. 9317996)				
	Examination for defects	15	--	3.2	4.4.2.1
	Body				
	(Dwg. 9317995)				
	Examination for defects	15	--	3.2	4.4.2.2
	Mine, Antitank, Practice: XM79				
	(Dwg. 9317994)				
	Examination for defects	15	--	3.2	4.4.2.3
	Push Out Test	15	--	3.3	4.5.1

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2008-10-28T06:45Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formations. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63380(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9317996
4.4.2.1	Lid				NEXT HIGHER ASSEMBLY 9317994
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Diameter		0.40%	3.2	Gage
103	Blank radius more than one side		0.40%	3.2	Visual
Minor					
201	Protective finish improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9317995
4.4.2.2	Body				NEXT HIGHER ASSEMBLY 9317994
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wall thickness		0.40%	3.2	Gage
102	Height		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	Diameter of shoulder		0.40%	3.2	Gage
105	Depth from outer edge to shoulder (both ends)		0.40%	3.2	Gage
Minor					
201	Protective finish improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Mine, Antitank, Practice: XM79	1 OF 1	9317994
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total height (max)		0.40%	3.2	Gage
102	Outside diameter (max)		0.40%	3.2	Gage
103	Stake(s) missing, incomplete		0.40%	3.2	Visual
104	Push out test	(a)	--	3.3	4.5.1
Minor					
201	Protective finish improper		0.65%	3.2	Visual
202	Marking missing, incomplete, or illegible		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

(a) Sampling and rejection in accordance to MIL-STD-105, Level S-3 and accept 0, reject 1, criteria.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Pkg for Plastic Ammunition Contanier: PA-83, for Mine, AP: HE, XM74 or Mine, AT, Practice: XM79	1 OF 1	9333791
			NEXT HIGHER ASSEMBLY 9243805

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any mines missing		0.40%	3.2	Visual/Manual
102	Retainers (2) not secured properly		0.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2006-10-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.5	Pkg & Mkg for Shipping & Storage Contanier: Mine: XM619 for Mine, AT: HE, XM75; Mine, AP: HE, XM74; or Mine, AT, Practice: XM79, in Plastic Ammo Container: PA-83	1	1	9243805
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
	Prior to Securing Cover:				
101	Marking missing, incorrect or illegible		100%	3.2	Visual
102	Bag(s) of Desiccant missing		0.40%	3.2	Visual
103	Filler on bottom missing		0.40%	3.2	Visual
104	Any Plastic Ammo Container missing		0.40%	3.2	Visual
105	Number of Slotted Fillers not adequate for tight packing		0.40%	3.2	Visual/Manual
106	Slotted Fillers positioned incorrectly		0.40%	3.2	Visual
107	Number of top fillers not adequate for tight packing		0.40%	3.2	Visual/Manual
108	Dirt or foreign material on Gasket or Gasket Track (Cover and Base)		0.40%	3.2	Visual
109	Any of the lifting straps missing (8 required)		0.40%	3.2	Visual
	After Securing Cover:				
110	Vent Assembly Cap not hand tight		0.40%	3.2	Manual
111	Humidity Indicator torqued improperly		0.40%	3.2	Gage
112	Fastener Nut(s) torqued improperly		0.40%	3.2	Gage
113	Vent Assembly nut torqued improperly		0.40%	3.2	Gage
114	Humidity Indicator dots not proper color		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4. Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6. herein.

4.5 Methods of inspection.

4.5.1 Push out test of staked lid. The assembly shall be cut approximately in half parallel to the lids and each half assembled to a test fixture which does not aid the unit under test in passing the test. The load shall be applied at the center of each lid in the director specified on the drawing, using a 2 inch diameter ram and a speed of 0.05 inches per minute, until the lid separates from the body. The force shall be recorded. Observation shall be made for compliance with the requirement of 3.3. This is a destructive test and test components subjected to this test shall not be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A. The mines shall be preserved and packaged in accordance with Dwg. 9243805.

5.2 Packing

5.2.1 Level A. Packing shall be in accordance with Dwg. 9243805.

5.3 Marking

5.3.1 Level A. Marking shall be in accordance with Dwg. 9243805.

5.4 Unitization

5.4.1 Level A. Unitization of mines as packed in 5.2.1 shall be in accordance with Dwg. 19-48-4116/95M-20PA1002 (DARCOM Ammo Center).

6. NOTES

6.1 Intended use. The Mine, Antitank, Practice: XM79 is intended to be used to simulate the XM74 and XM75 Mines in loading and launching drills from the XM128 Mine Dispenser.

6.2 Ordering data. See MIL-A-48078

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards and test data. Distribution of data cards and test data shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading "US ARMY ARMEMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)" may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the compliance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1345-A106

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.