MIL-S-48741 (AR)
AMENDMENT 5
19 NOVEMBER 1980
SUPERSEDING
AMENDMENT 4
19 October 1976

MILITARY SPECIFICATION

SHIPPING AND STORAGE CONTAINER, XM612
PARTS AND ASSEMBLY

This Amendment forms a part of Military Specification MIL-S-48741 (AR), dated 28 March 1975.

PAGE 2

* Para 2.1, DRAWINGS - Delete the Title: "DRAWINGS", "PICATINNY ARSENAL" and "PRODUCT AND PACKAGING DRAWINGS" and substitute the following:

DRAWINGS (See 6.6)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

Paragraph 3.3 - Delete in its entirety and substitute:

3.3 Assembly, disassembly and fit - The container shall accept the warhead section, with spacer assembly attached, without evidence of excessive effort in assembly or disassembly of the warhead section or closing the securing of the cover. With the warhead section assembled to the base a 1.44 - .01 diameter by 4.37 + .01 long cylinder shall fit between the warhead section and the three (3) sling recesses in the base. In addition, the gaps between the warhead section and the base, the cover and base with warhead section assembled, and the warhead section and cover shall not exceed the drawing requirement.

PAGE 5

* Table 1 - First Article Inspection - Delete in its entirety and substitute attached Table 1.

FSC: 8140

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Shipping and Storage Container XM612				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shipping and Storage Container XM612 (Dwg. 9288556)				
	Examination for Defects	1		3.2	4.4.2.5
	Vibration	1		3.4.1	4.5.2.1
	Edgewise Drop	1		3.4.2	4.5.2.2
	Cornerwise drop	1		3.4.3	4.5.2.3
	Fork-lifting	1		3.4.4	4.5.2.4
	Stacking	1		3.4.5	4.5.2.5
	Base (Dwg. 9288553)				
	Examination for Defects	2*		3.2	4.4.2.1
	Percentage of Extract, Max.	2**		3.2	4.5.3
	Density, Max.	2**		3.2	4.5.4
	Cover (Dwg. 9288554)				
	Examination for Defects	2*		3.2	4.4.2.2
	Percentage of Extract, Max.	2**		3.2	4.5.3
	Density, Max.	2**		3.2	4.5.4
	Spacer Assembly (Dwg. 9288555)				
	Examination for Defects	2*		3.2	4.4.2.3

NOTES: *One (1) of each of these parts comprises the complete container that is to be examined for defects and performance tested.
**Samples from part

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48741 (AR) Amend 5

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Shipping and Storage Container XM612				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pad (Dwg. 9254984) Examination for Defects	2*		3.2	4.4.2.4

NOTES:

*One (1) of each of these parts comprises the complete container that is to be examined for defects and performance tested.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74, which is obsolete

Source: https://assist.dla.mil - Downloaded: 2026-01-27T19:38Z
Check the source to verify that this is the current version before use.

PAGE 8

Paragraph 4.4.2.1, Major 102 - Change "Wall Thickness" to "Wall Thickness, min".

Para 4.4.2.1 - Add:

	Major			
127	Longitudinal location of forward drain hole	0.40%	3.2	Gage
128	Longitudinal location of center drain hole	0.40%	3.2	Gage
129	Longitudinal location of aft drain hole	0.40%	3.2	Gage

Delete Majors 127 thru 129 and substitute:

127.	Longitudinal location of drain hole in forward strap recess	0.40%	3.2	Gage
128.	Longitudinal location of drain hole in center strap recess	0.40%	3.2	Gage
129.	Longitudinal location of drain hole in aft strap recess	0.40%	3.2	Gage
130.	Longitudinal location of drain hole in spacer assembly recess	0.40%	3.2	Gage
131.	Distance from side to drain hole in forward strap recess	0.40%	3.2	Gage
132.	Distance from side to drain hole in center strap recess	0.40%	3.2	Gage
133.	Distance from side to drain hole in aft strap recess	0.40%	3.2	Gage
134.	Distance from side to drain hole in spacer assembly recess	0.40%	3.2	Gage

PAGE 9

Para 4.4.2.2, Major 101 - Change "Wall Thickness" to "Wall Thickness, min".

PAGE 11

* Para 4.4.2.3 - Add Major 115 as follows:

"115.	Stencil missing, incomplete or illegible.	100%	3.2	Visual"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

PAGE 13

Para 4.4.2.5, Major 101 - Change "Assembly and disassembly" to "Assembly, disassembly and fit".

PAGE 15

Para 4.5.1 - Delete in its entirety and substitute:

4.5.1 Assembly, disassembly and fit - The warhead section, with spacer assembly attached, shall be loaded into the base. Inspection shall be performed for fit in the three (3) sling recesses and for the gap between the warhead section and base.

The cover shall be installed and inspection shall be performed for the gap between cover and base. The warhead section and cover shall then be removed from the base. The cover shall be placed on the warhead section and inspection performed for the gap between the warhead section and cover. During assembly and disassembly, observation shall be made for any excessive effort required to perform the operations.

PAGE 17

* Para 6.3 - Change address to read as follows: "Commander, ARRADCOM, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801."

* Para 6.4 - Change address to read as follows: "Commander, ARRADCOM, ATTN: DRDAR-QAR-R, Dover, New Jersey 07801."

* Para 6.5 - Delete in its entirety.

* Para 6 - Add para 6.6 as follows:

6.6 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:38Z
Check the source to verify that this is the current version before use.

Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 8140-A538

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.