NOTICE OF
CHANGE

DOD-STD-35-126(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

CYLINDERS, ACTUAUING, LINEAR

TO ALL HOLDERS OF DOD-STD-35-126(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-126(MI) HAVE BEEN REVISED) AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	30 JUNE 1978
1	30 JUNE 1978 (Reprinted without change)		
2	18 SEPTEMBER 1992	2	30 JUNE 1978
3	18 SEPTEMBER 1992	3	30 JUNE 1978
5	18 SEPTEMBER 1992	5	30 JUNE 1978
6	18 SEPTEMBER 1992	6	30 JUNE 1978
11	18 SEPTEMBER 1992	11	30 JUNE 1978
12	18 SEPTEMBER 1992	12	30 JUNE 1978
29	30 JUNE 1978 (Reprinted without change)		
30	18 SEPTEMBER 1992	30	30 JUNE 1978
31	18 SEPTEMBER 1992	31	30 JUNE 1978
32	18 SEPTEMBER 1992	32	30 JUNE 1978
33	18 SEPTEMBER 1992	33	30 JUNE 1978
34	18 SEPTEMBER 1992	34	30 JUNE 1978
35	18 SEPTEMBER 1992	35	30 JUNE 1978
36	30 JUNE 1978 (Reprinted without change)		

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-126(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army – MI

(Project EGDS-A460)

AMSC N/A

AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

CONTENTS

Page

Paragraph 1. SCOPE---------- 1
1.1 General---------- 1
1.2 Purpose---------- 1
1.3 Utilization---------- 1
1.4 Military Specification Exception Title Index---------- 1

2. APPLICABLE DOCUMENTS---------- 5
2.1 Government docunments---------- 5
2.2 Non-Government publications---------- 6

3. DEFINITIONS---------- 7

4. GENERAL REQUIREMENTS---------- 9
4.1 Introduction---------- 9
4.2 Specification Requirement Sheet (SRS)---------- 9
4.3 Configuration---------- 9
4.3.1 Dimensions---------- 9
4.3.2 Illustrations---------- 9
4.4 Units of measure---------- 9

5 DETAILED REQUIREMENTS---------- 11
5.1 Introduction---------- 11
5.2 MSE Formats---------- 11
5.3 Referenced documents---------- 11
5.4 Deleted---------- 11
5.5 Tablation---------- 13
5.6 Keyword Code Index (KCI) and Standard Paragraphs---------- 15
5.6.1 Interrelationship of Codes---------- 15
5.6.2 Automatic MSE Data---------- 15
5.6.3 DOD-STD-35 Tables---------- 15

TABLES

Table I. Title Index---------- 2
II. Deleted---------- 12
III. Tabulation Candidates---------- 13

APPENDICES

Appendix A. Illustrations---------- 117
B. Characteristic Code Index---------- 127

Index---------- 133

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for linear actuating cylinders.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirerment Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment OF a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index entered on an SRS, specifies that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index, is compatible with the document(s) listed with that title under base documents The list of base documents may or may not be a complete listing. The information is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CYLINDER, ACTUATING, LINEAR	249001	MIL-A-5503	HYDRAULIC CYLINDERS, AERONAUTICAL SYSTEMS
		MIL-C-52464	HYDRAULIC CYLINDERS, VEHICLE BRIDGE LAUNCHER
CYLINDER ASSEMBLIES, ACTUATING, LINEAR	249002	MIL-A-5503	HYDRAULIC CYLINDERS, AERONAUTICAL SYSTEMS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
	249002 (CONT)	MIL-C-52464	HYDRAULIC CYLINDERS , VEHICLE BRIDGE LAUNCHER

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-5503	Cylinders, Aeronautical, Hydraulic Actuating, General Requirements For
MIL-C-52464	Cylinder Assemblies, Actuating, Linerar, Hydraulic, for Bridge and Bridge Launcher

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-453	Inspection, Radiographic
MIL–STD-810	Environmental Test Methods
MIL-STB-1949	Inspection, Magnetic Particle
MIL-STD-6866	Inspection, Liquid Penetrant

(Unless othewise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are three listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM B 117	Salt Spray (Fog) Testing, Method of Test For
ASTM E 380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials., 1916 Race St., Philadelphia, Pa. 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

THIS PAGE DELETED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1640	CUSHION . CUSHION-HEAD END IS REQUIRED.
1642	CUSHION. CUSHION-CAP END IS REQUIRED.
1644	CUSHION. CUSHIONS-BOTH ENDS ARE REQUIRED.
1646	CUSHION. CUSHIONS ARE NOT REQUIRED.
1660	JOINT FABRICATION. STEEL JOINTS SHALL BE HYDROGEN BRAZED.
1662	JOINT FABRICATION. STEEL JOINTS SHALL BE WELDED.
1670	OPERATING MEDIA. THE OPERATING MEDIA SHALL BE FILTERED AIR.
1672	OPERATING MEDIA. THE OPERATING MEDIA SHALL BE WATER.
1674	OPERATING MEDIA. THE OPERATING MEDIA SHALL BE 1674.
1676	THE OPERATING MEDIA SHALL BE IN ACCORDANCE WITH 1676.
	OPERATING PRESSURE.
1690	THE NOMINAL OPERATING PRESSURE SHALL BE 1690 POUNDS PER SQUARE INCH.
1694	THE OPERATING PRESSURE SHALL BE NOT LESS THAN 1694 POUNDS PER SQUARE INCH.
1698	THE OPERATING PRESSURE SHALL BE NOT GREATER THAN 1698 POUNDS PER SQUARE INCH.

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
OPERATING PRESSURE (CONT)	
SI	
NOMINAL (KIL-OPASCALS)	1692
MINIMUM (KILOPWCALS)	1696
MAXIMUM (KILOPASCALS)	1700
OPERATION TYPE (SELECT ONE)	
HYDRAULIC.	1710
PNEUMATIC.	1712
PORT ONE	
(DOC DES)	1720
NOMINAL SIZE (SELECT ONE)	
(INCHES)	1722
(MILLIWERS)	1724
THREAD ____	1726
THREAD DESIGNATION (SELECT ONE)	
FED-STD-H28.	1728
PER DOCUMENT (DOC DES)	1730
DESIGNATION ____	1732

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1692	THE NOMINAL OPERATING PRESSURE SHALL BE 1692 KILOPASCAL(S) .
1696	THE OPERATING PRESSURE SHALL BE NOT LESS THAN 1696 KILOPASCAL(S).
1700	THE OPERATING PRESSURE SHALL BE NOT GREATER THAN 1700 KILOPASCAL(S).
1710	OPERATION TYPE . THE TYPE OF OPERATION SHALL BE HYDRAULIC.
1712	OPERATION TYPE. THE TYPE OF OPERATION SHALL BE PNEUMATIC.
	PORT ONE.
1720	PORT ONE SHALL BE IN ACCORDANCE WITH 1720.
1722	THE NOMINAL SIZE OF PORT ONE SHALL BE 1722 INCH(S).
1724	THE NOMINAL SIZE OF PORT ONE SHALL BE 1724 MILLIMETER(S).
1726	THE THREAD SIZE OF PORT ONE SHALL BE 1726.
1728	PORT ONE THREADS SHALL BE IN ACCORDANCE WITH FED-STD-H28.
1730	PORT ONE THREADS SHALL BE IN ACCORDANCE WITH 1730.
1732	PORT ONE DESIGNATION SHALL BE 1732.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
FORT TWO	
(DOC DES)	1736
NOMINAL SIZE (SELECT ONE)	
(INCHES)	1738
(MILLIMETERS)	1740
THREAD ____	1742
THREAD DESIGNATION (SELECT ONE)	
FED-STD-H28.	1744
PER DOCUMENT (DOC DES)	1746
DESIGNATION ____	1748
STROKE	
EXTENDED (SELECT ONE)	
(INCHES)	1780
(MILLIMETERS)	1782
RETRACTED (SELECT ONE)	
(INCHES)	1784
(MILIMETERS)	1786

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	PORT TWO.
1736	PORT TWO SHALL BE IN ACCORDANCE WITH 1736.
1738	THE NOMINAL SIZE OF PORT TWO SHALL BE 1738 INVH(S).
1740	THE NOMINAL SIZE OF PORT TWO SHALL BE 1740 MILLIMETER(S).
1742	THE THREAD SIZE OF PORT TWO SHALL BE 1742.
1744	PORT TWO THREADS SHALL BE IN ACCORDANCE WITH FED-STD-H28.
1746	PORT TWO THREADS SHALL BE IN ACCORDANCE WITH 1746.
1748	PORT TWO DESIGNATION SHALL BE 1748.
	STROKE.
1780	THE EXTENDED STROKE SHALL BE 1780 INCH(S).
1782	THE EXTENDED STROKE SHALL BE 1782 MILLIMETER(S).
1784	THE RETRACTED STROKE SHALL BE 1784 INCH(S).
1786	THE RETRACTED STROKE SHALL BE 1786 MILLIMETER(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
STROKE (CONT)	
STROKE TOLERANCE (SELECT ONE)	
(INCHES)	1788
(MILLIMETERS)	1790
PISTON ROD THREADS	
CYLINDER-HEAD-END (SELECT ONE)	
FED-STD-H28.	1796
PER DOCUMENT (DOC DES)	1798
CYLINDER-CAP-END (SELECT ONE)	
FED-STD-H28.	1800
PER DOCUMENT (DOC DES)	1802
WEIGHT	
MAXIMUM WEIGHT PER UNIT (SELECT ONE)	
(POUNDS)	7023
(KILOGRAMS)	7024

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1788	THE STROKE TOLERANCE SHALL BE 1788 INCH(S) l
1790	THE STROKE TOLERANCE SHALL BE 1790 MILLIMETER(S) l
	PISTON ROD THREADS.
1796	CYLINDER-HEAD-END PISTON ROD THREADS SHALL BE IN ACCORDANCE WITH FED-STD-H28.
1798	CYLINDER-HEAD-END PISTON ROD THREADS SHALL BE IN ACCORDANCE WITH 1798.
1800	CYLINDER-CAP-END PISTON ROD THREADS SHALL BE IN ACCORDANCE WITH FED-STD-H28.
1802	CYLINDER-CAP-END PISTON ROD THREADS SHALL BE IN ACCORDANCE WITH 1802.
7023	MAXIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT GREATER THAN 7023 POUND(S).
7024	MAXIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT GREATER THAN 7024 KILOGRAM(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CYCLES	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1814
NO EVIDENCE OF LEAKAGE.	1815
MAXIMUM LEAKAGE OF ONE DROP PER (CYCLES)	1816
MAXIMUM LEAKAGE (SELECT ONE)	
PER CYCLE (CUBIC CENTIMETERS)	1817
PER HOUR (CUBIC CENTIMETERS)	1818
PER MINUTE (CUBIC CENTIMETERS)	1819
TEST METHODS (SELECT ONE)	
PER EASE DOCUMENT EXCEPT ____	1820
PER DOCUMENT (DOC DES)	1821
PRESSURE APPLIED) (SELECT ONE)	
(POUNDS PER SQUARE INCH)	1822
TOLERANCE (POUNDS PER SQUARE INCH)	1823
(KILOPASCALS)	1824
TOLERANCE (KILOPASCALS)	1825

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:04Z
Check the source to verify that this is the current version before use.