DOD-L-63317A (AR)
28 September 1981
SUPERSEDING
DOD-L-63317 (AR)
31 January 1979

MILITARY SPECIFICATION

LINER, SUPPLEMENTARY CHARGE, THREADED

This specification is approved for use by U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. Scope

1.1 This specification covers the threaded supplementary charge liner.

2. Applicable Documents.

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-Ammunition and Special Weapons, General Specification For
MIL-I-45607	-Inspection Equipment, Supply and Maintenance Of
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-1169	-Packing and Marking for Shipment of Inert Ammunition Components: General Specification For

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARRADCOM

9331677 - Liner, Suppl Chg, Thd

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg) 9331677 and with all requirements specified in applicable specifications.

3.3 Body. The body shall be free of cracks, splits, punctures and shall not be distorted.

3.4 Workmanship. All parts shall be dry and free of chips, burrs, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078(AR) shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections. The following types of Inspections shall be performed on this item:

a. First Article Inspection.
b. Quality Conformance Inspection.

4.3 First Article Inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

4.3.1 Submission. The contractor shall submit a First Article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The First Article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Liner	9331677	25

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

DOD-L-63317A (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9331677
	Liner				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Liner (Dwg. 9331677) Examination for Defects		25	3.2	4.4.2.1

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection.

4.4.1 Lot Formation. Lots shall comply with the formation provisions of MIL-A-48078(AR).

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

DOD-L-63317A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Liner		9331677
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length		0.40%	3.2	Gage
102	Wall thickness (3 places)		0.40%	3.2	Gage
103	Crack, split, puncture or similar damage extending through material		0.40%	3.3	Visual
104	Inside diameter		0.40%	3.2	Gage
105	Thickness through base		0.40%	3.2	Gage
106	Thread pitch diameter, min.		0.40%	3.2	Gage
107	Thread major diameter, min.		0.40%	3.2	Gage
Minor					
201	Damage (not extending through material) or distortions		0.65%	3.3	Visual
202	Chamfers or radii missing		0.65%	3.2	Visual
203	Thread pitch diameter, max.		0.65%	3.2	Visual
204	Length of full thread		0.65%	3.2	Gage
205	Slots missing		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The tests (First Article and Quality Conformance) listed in the Item Detail Specification shall be performed on Inspection Lots as defined in 4.4.1 of this specification.

4.4.4 Inspection Equipment. The inspection equipment required to perform the examinations and test prescribed herein are described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval of inspection equipment designs in accordance with the contract. See Section 6 of MIL-A-48078(AR) and 6.3 herein.

4.5 Test Methods and Procedures. In place of the normal sampling associated with the Classification of Defects, and with the approval of the contracting officer, a sample of at least twenty-five (25) parts may be dimensionally inspected to qualify the tool used in the sampling process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production. If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from the production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action. All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above.

5. PREPARATION FOR DELIVERY. Preservation, packaging, packing and marking shall be Level C of MIL-STD-1169.

6. NOTES

6.1 Intended use. The component covered by this specification is intended for use on the 155MM, HE, XM795 Projectile.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection procedures and/or equipment designs for approval - See MIL-A-48078(AR). Submit equipment designs as required to: Commander, ARRADCOM, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

6.4 Inspection lot size. It is noted that the size of inspection lots of components, assemblies or items of delivery may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria and sampling provisions of this specification are maintained.

6.5 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristics may be measured or gaged to determine acceptability.

6.6 Alternative testing procedures. Alternative testing procedures may be used by the contractor when such testing and procedures provide as a minimum the quality assurance provisions specified herein. Prior to applying alternative procedures, the contractor shall describe them in a written proposal and shall demonstrate for the approval of the responsible government technical agency that their effectiveness is equal to, or better than the quality assurance provisions specified herein.

Custodian:
Army - AR

Preparing Activity:
Army - AR

Project No.: 1315-A367

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.