MILITARY SPECIFICATION

BODY ASSEMBLY, TANK PERISCOPE: 10513620

This amendment forms a part of Military Specification MIL-B-60133(MU) dated 22 January 1965.

* Paragraph 2.1, under DRAWINGS add:

"D7560124 Millidioptometer, 20X"

Paragraph 3.6: Delete last sentence and substitute: "The incident line of sight shall also emerge parallel to a plane, defined by the 2-inch-long shoulder (generated by the machining of the two pads) adjacent to Valve Assembly 8201751, within 45 minutes of arc."

Paragraph 3.7: Delete paragraph and substitute:

"3.7 Image tilt.- The image of a target line originally perpendicular to a plane, defined by the 2-inch-long shoulder (generated by the machining of the two pads) adjacent to Valve Assembly 8201751, shall emerge perpendicular to the same plane within 45 minutes of arc."

Add the following new paragraphs:

* "4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) body assemblies plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

* 4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

FSC 6650

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.

* 4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.5.5: Delete paragraph and substitute:

"4.5.5 Light deviation.- This test shall be performed utilizing an auxiliary telescope, containing a horizontal and vertical reticle line, mounted on a supporting device. The device shall be capable of holding the telescope and body assembly in a position permitting an incident line of sight to be directed from a calibrated target in a collimator projector, through the body assembly to the auxiliary telescope. Utilize the vertical surface of the 2-inch shoulder adjacent to the valve assembly to centrally position the body assembly in the device with the machined top surfaces of the pads on the same plane with the line of sight through the telescope. The target pattern shall consist of a horizontal and vertical crossline with limit marks 45 minutes from the intersection of the crossline. Limit marks shall also be added in each quadrant, offset 45 minutes of arc from the horizontal crossline, to subsequently measure image tilt. The collimating projector shall be positioned in front of the body assembly with the center vertical line of the target in a plane parallel to a plumb line and on the same plane with the vertical surface of the 2-inch shoulder adjacent to the valve assembly. The auxiliary telescope reticle line shall be adjusted parallel to a plumb line. With the body assembly installed in the device, the line of sight shall be determined by viewing through the telescope and observing coincidence between the intersecting point of the auxiliary telescopes reticle and the corresponding intersecting point of the collimator target line. This coincidence must be maintained within the limits of the tolerance line of the collimator target to assure conformance with the requirement outlined in 3.6."

Paragraph 4.5.7: Delete and substitute:

* "4.5.7 Spherical power.- Spherical power shall be checked in accordance with the set up and operating instructions outlined on Drawing D7560124. The test equipment shall conform to Drawing D7560124, except that the target (Resolving power chart) shall contain four line sets as shown in Figure 1 of MIL-O-13830. Spherical power at any point in the scanning area shall not exceed the tolerance (millidiopter) specified in 3.8, as measured on the millidiopter scale."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.7: Delete and substitute:

* "4.5.8 Astigmatism.- Perform this test utilizing the test procedure in 4.5.7. Astigmatism at any point in the scanning area shall not exceed the tolerance (millidiopter) specified in 3.9, as measured on the millidiopter scale."

* Paragraph 6.2: Add: "(e) Requirement for first article testing."

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 6650-A025

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.