MILITARY SPECIFICATION

CARTRIDGE, 7.62X39MM, BALL

This Amendment forms a part of Military Specification MIL-C-50701A (MU), dated 20 August 1971, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

Delete "AMCR 715-505 Volume 3" wherever it appears in the specification and substitute "SCATP-7.62."

PAGE 2

3.10 - Delete the word "ambient" and substitute "room."

PAGE 6

4.3.3.1 - Table II: Delete the heading "Ambient Temp" and substitute "70 ± 2°F."

PAGE 8

4.3.3.2 - Table III: Change defect numbers from "3, 4, 5 and 6" to "4, 5, 6 and 7" respectively. Then insert new defect number 3 as follows:

"3. Hangfire 7/ 0 -"

PAGE 9

4.3.3.2 - Table III: Add footnote 7/ to Table III as follows:

"7/ For definition of hangfire, see SCATP-7.62 paragraph 10.6.2."

PAGE 10

4.4.9.2 - Delete the phrase "for not less than 4 hours" and substitute "for 4 to 5 hours."

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:34Z
Check the source to verify that this is the current version before use.

Add new section 4.4.9.3 as follows:

"4.4.9.3 Room temperature tests. The test sample shall be conditioned for not less than 2 hours at 68°F to 72°F (room temperature) and fired at that temperature."

4.4.10 - Delete the word "ambient" and substitute the word "room."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-A984)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:34Z
Check the source to verify that this is the current version before use.