MILITARY SPECIFICATION

CARRIER ASSEMBLY

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type ofcarrier assembly.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for propsal, form a part of this specification to the extent specified herein:

STANDARDS

FEDERAL

FED-STD-123 - Marking for Shipment (Civil Agencies).

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWING AND TECHNICAL DATA PACKAGE LIST (TDPL)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

TDPL 122-3-143 - Carrier Assembly.

FSC 1040

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight classification

(Application for copies of these ratings, rules and regulations should be addressed to Unifom Classification Committee, Room 1106, 222 South Riverside Plaza, Illinois 60606.)

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N.W., Washington, D.C. 20036).

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on TDPL 122-3-143 and on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the carrier assembly shall conform to the specifications and drawings listed TDPL 122-3-143.

3.2 Preproduction. Prior to the start of regular production, a preproduction lot of carrier assemblies shall be produced in accordance with this specification for examination and test (see 4.3).

3.4 Workmanship. The carrier assembly shall be free from burrs, sharp edges, foreign matter and damages such as cracks or deformation which could impair its intended use.

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T21:01Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies,and services conform to prescribed requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections.

(a) Preproduction inspection (4.3).
(b) Quality conformance inspection (4.4).

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of 100 each components for carrier assemblies shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For exaination. A sample of 10 each components subassemblies and assemblies shall be examined 1CO percent to all drawing dimensions.

4.3.2.2 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations specified in 4.3.2 to be acceptable. The acceptance number is zero. The contractor shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 conformance inspection.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

4.4.2 Sampling. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure.

4.4.3.1 Examination. Sample carrier assembly components shall be examined in accordance with the classification of defects and with MIL-STD-105.

4.4.3.2 Classification of defects.

(a) Case inseparable assembly (Drawing D122-3-59).

Categories		Defects
Critical:		None defined
Major:		AQL 1.0 percent defective
	101	Component missing
	102	Component incorrectly assembled

(b) Ejector, projectile (Drawing C122.3-41).

Categories		Defects
Critical:		None defined
Major:		AQL 1.5 percent defective
	101	Projectile interface OD incorrect
	102	Location of flange incorrect
	103	Profile of flange incorrect
	104	Diameter of flange incorrect
	105	Internal tapers incorrect
	106	External tapers incorrect

(c) Holder, projectile (Drawing C122-3-42).

Categories		Defects
Critical:		None defined
Major:		AQL 1.5 percent defective
	101	ID of projectile interface incorrect
	102	OD of bead incorrect
	103	Slots incorrect or incorrectly located
	104	ID of ejector interface incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

(d) Holder cartaridge (Drawing C122-3-61).

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	OD incorrect

(e) Cushion (Drawing B122-3-58).

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	Diameter incorrect
102	Length incorrect

(f) Container, telescopic (Drawing D122-3-57).

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	2.590 diameter incorrect

5. PACKAGING

5.1 Packing, interplant shipment. Like components shall be packed in containers, together with internal Packaging, constructed as to give assurance that the items being shipped will remain in prome condition and adequate to assure safe delivery to destination without damage to content. The containers shall comply with the Unifom Freight Classifications, National Motor Freight Classifications or National Motcr Freight Classifications as applicable, and be acceptable for shipment at the most favorable rate, The containers shall be sufficiently rigid to withstand transportation and permit storing in tiers at least 10 feet high without damage to containers or contents. The gross weight and size limitations of the containers shall not exceed the tariff or classification limitations specified therein and the containers shall be closed or strapped securely in accordance with the requirements applicable to the specific container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

5.2 Marking. In addition to any special marking required by the contract or order, marking shall be in accordance with the requirements of FED-STD123 and shipping containerss shall include the contractor's name, address, contract number and the date of manufacture.

6. NOTES

6.1 Intended use. The carrier assembly covered by this specification is intended to be used as packaging and dispenser for the 64mm riot control projectiles, M743 and XM742.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Reproduction.

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

6.3 Supersession data. This specification supersedes Chemical Systems Laboratory Purchase Description, EA-C-1147B dated 28 June 1978.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1040-A149

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-5541E

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:01Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DOD-314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament Research
and Development Command
ATTN: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE: 1980—603-121/3143 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

INCH-POUND

MIL-C-51475(EA)
NOTICE 2
8 November 1995

SUPERSEDING
NOTICE 1
24 February 1987

MILITARY SPECIFICATION

CARRIER ASSEMBLY

This notice should be filed in front of MIL-C-51475(EA) dated 16 June 1980.

MIL–C–51475(EA) is inactive for new design and is no-longer used except for replacement purposes.

Preparing activity:

Army – EA

AMSC N/A **FSC 1040**

DISTRIBUTION STATEMENT A. **Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:01Z
Check the source to verify that this is the current version before use.