INCH-POUND

MIL-C-70793(AR)
AMENDMENT 1
27 November 1991

MILITARY SPECIFICATION

CARTRIDGE, 20MM, MULTIPURPOSE
TRACE SELF-DESTRUCT, M940

This amendment forms a part of Military Specification MIL-C-70793(AR), dated 31 March 1989 and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.6.2, Add "-" before 65°F.

PAGE 10

4.3.2, TABLE I, Make the following changes:

Projectile Trace -65°± 5°F, Delete "100" and substitute "29"
145°± 5°F, Delete "100" and substitute "29".

Projectile Self-Destruct -65°± 5°F, Delete "100" and substitute "33"
145°± 5°F, Delete "100" and substitute "33".

PAGE 15

4.4.2, Add the following:

"f. Special defect. Unless otherwise specified, one hundred percent examination shall be performed for all special defects.".

PAGE 16

4.4.2.1, Make the following changes:

Delete under Critical "1. .06 depth from metering disc to tracer igniter, max. (prior to inspection of seal and metering disc) ($\bar{X}$ & R Chart), 100%, 3.2, AAIE 4.4.6.1/SPC 4.4.4" and substitute "None defined".

Delete under Critical "2. Seal missing or perforated (P-Chart), 100%, 3.2, AAIE 4.4.6.1/SPC 4.4.4".

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:03Z
Check the source to verify that this is the current version before use.

Add: "Special" classification category and "001. Seal missing or perforated (P-Chart), 100%, 3.2, Visual/SPC 4.4.4".

Major 101, Delete in its entirety and substitute "101. .06 Depth from metering disc seat to tracer igniter, (prior to insertion of seal and metering disc) ($\bar{X}$ & R Chart), 100%, 3.2, Gage/SPC 4.4.4".

PAGE 19

4.4.2.4, Make the following changes:

Delete under Critical "1. Crack in projectile (P-Chart), 100%, 3.2, AAIE 4.4.6.1/SPC 4.4.4" and substitute "None defined".

Add: "Special" Classification category and "001. Crack in projectile (P-Chart), 100%, 3.2, Gage/SPC 4.4.4".

PAGE 20

4.4.2.5, Make the following changes.

Delete under Critical "1. Split or perforated case (P-Chart), 100%, 3.2, AAIE 4.4.6.1/SPC 4.4.4".

Add: "Special" classification category and "001. Split or perforated case (P-Chart), 100%, 3.2, Visual/SPC 4.4.4".

PAGE 22

4.4.2.6, NOTE 1, Delete "7258001" and substitute "7258801".

PAGE 26

4.4.3.5, Delete in its entirety and substitute the following:

"4.4.3.5. Pressure. If the average pressure ($\bar{X}$) plus 0.84 times the average range ($\bar{R}$) of the sample cartridges exceeds 60,500 psi a retest sample of 40 cartridges shall be tested. The lot shall be rejected if the average pressure ($\bar{X}$) plus 0.91 times the average ($\bar{R}$) of the retest sample exceeds 60,500 psi (see 6.8).".

4.4.3.8, Line 7, Delete "11" and substitute "17".

PAGE 31

4.5.3.4 b., Delete "200 feet" and substitute "200 yards".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AE03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:03Z
Check the source to verify that this is the current version before use.