MILITARY SPECIFICATION

PROJECTILE, 20MM, HEIT-SD, M246; METAL PARTS

This amendment forms a part of Military Specification MIL-P-60679A(MU), 10 December 1969, and is approved for use by all Departments and Agencies of the Department of Defense.

Para 2.1, under STANDARDS, delete "FEDERAL - Federal Test Method Standard No. 151 - Metals; Test Methods."

After para 2.1, add the following:

"2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM)
ASTM B117-64 -- Method of Test for Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Technical Society and Technical Association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using federal agencies."

Para 4.3.1.a., add the following:

"(5) 3 Test panels (see TT-C-490)"

Para 4.4.3.3, under Major defects, make the following changes:

"115" Delete in its entirety and substitute:

"115. Void at junction of rotating band and body ---------- Visual"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.

Para 4.4.3.3, under Major defects, make the following changes:

"117" Delete in its entirety.

"118" Delete the word "datum" and substitute the word "basic".

"125" Delete the word "Thickness" and substitute the word "Width".

Add the following defect:

"130. Concentricity, boss (tracer cavity) with datum surface ---- Gage"

"131" Delete in its entirety and substitute:

"131. Length, boss (tracer cavity) to basic diameter (igniter cavity) ---------- Gage"

"132" Delete in its entirety.

* Para 4.4.3.5, under Major defects, make the following additions:

"109. Paint in igniter cavity ---------- Visual
110. Perforation or fracture of metal between cavities --------- Visual"

Para 4.5.7, delete entire paragraph and substitute the following:

"4.5.7 Corrosion resistance. The method of test shall be as prescribed in American Society for Testing and Materials (ASTM) ASTM B117. The paint shall not be disturbed; however, the rotating band and unpainted surfaces of the sample projectiles may be masked out by a wax coating or other suitable material. The salt spray solution and exposure time shall be as specified in 3.6.3."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A808

Source: https://assist.dla.mil - Downloaded: 2026-10-23T00:55Z
Check the source to verify that this is the current version before use.